


# AOTF27S60L Datasheet

[www.digi-electronics.com](http://www.digi-electronics.com)



<https://www.DiGi-Electronics.com>

|                              |   |
|------------------------------|---|
| DiGi Electronics Part Number | AOTF27S60L-DG   |
| Manufacturer                 | <a href="#">Alpha &amp; Omega Semiconductor Inc.</a>    |
| Manufacturer Product Number  | AOTF27S60L  |
| Description                  | MOSFET N-CH 600V 27A TO220-3F                           |
| Detailed Description         | N-Channel 600 V 27A (Tc) 50W (Tc) Through Hole T O-220F |



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.



## Purchase and inquiry

**Manufacturer Product Number:**

AOTF27S60L

**Series:**

aMOST™

**FET Type:**

N-Channel

**Drain to Source Voltage (Vdss):**

600 V

**Drive Voltage (Max Rds On, Min Rds On):**

10V

**Vgs(th) (Max) @ Id:**

4V @ 250µA

**Vgs (Max):**

±30V

**FET Feature:**

-

**Operating Temperature:**

-55°C ~ 150°C (Tj)

**Supplier Device Package:**

TO-220F

**Base Product Number:**

AOTF27

**Manufacturer:**

Alpha &amp; Omega Semiconductor Inc.

**Product Status:**

Not For New Designs

**Technology:**

MOSFET (Metal Oxide)

**Current - Continuous Drain (Id) @ 25°C:**

27A (Tc)

**Rds On (Max) @ Id, Vgs:**

160mOhm @ 13.5A, 10V

**Gate Charge (Qg) (Max) @ Vgs:**

26 nC @ 10 V

**Input Capacitance (Ciss) (Max) @ Vds:**

1294 pF @ 100 V

**Power Dissipation (Max):**

50W (Tc)

**Mounting Type:**

Through Hole

**Package / Case:**

TO-220-3 Full Pack

## Environmental & Export classification

**RoHS Status:**

ROHS3 Compliant

**REACH Status:**

REACH Unaffected

**HTSUS:**

8541.29.0095

**Moisture Sensitivity Level (MSL):**


1 (Unlimited)


**ECCN:**

EAR99



**AOT27S60L/AOB27S60L/AOTF27S60L/AOTF27S60**  
**600V 27A  $\alpha$ MOS™ Power Transistor**

|  |  |                      |      |          |      |                  |               |             |      |                  |           |
|--|--|----------------------|------|----------|------|------------------|---------------|-------------|------|------------------|-----------|
| <p><b>General Description</b></p> <p>The AOT27S60L &amp; AOB27S60L &amp; AOTF27S60L &amp; AOTF27S60 have been fabricated using the advanced <math>\alpha</math>MOS™ high voltage process that is designed to deliver high levels of performance and robustness in switching applications.</p> <p>By providing low <math>R_{DS(on)}</math>, <math>Q_g</math> and <math>E_{OSS}</math> along with guaranteed avalanche capability these parts can be adopted quickly into new and existing offline power supply designs.</p> | <p><b>Product Summary</b></p> <table border="0"> <tr> <td><math>V_{DS} @ T_{j,max}</math></td> <td>700V</td> </tr> <tr> <td><math>I_{DM}</math></td> <td>110A</td> </tr> <tr> <td><math>R_{DS(ON),max}</math></td> <td>0.16<math>\Omega</math></td> </tr> <tr> <td><math>Q_{g,typ}</math></td> <td>26nC</td> </tr> <tr> <td><math>E_{oss} @ 400V</math></td> <td>6<math>\mu</math>J</td> </tr> </table> <p>100% UIS Tested<br/>                 100% <math>R_g</math> Tested</p>  | $V_{DS} @ T_{j,max}$ | 700V | $I_{DM}$ | 110A | $R_{DS(ON),max}$ | 0.16 $\Omega$ | $Q_{g,typ}$ | 26nC | $E_{oss} @ 400V$ | 6 $\mu$ J |
| $V_{DS} @ T_{j,max}$   | 700V   |                      |      |          |      |                  |               |             |      |                  |           |
| $I_{DM}$   | 110A   |                      |      |          |      |                  |               |             |      |                  |           |
| $R_{DS(ON),max}$   | 0.16 $\Omega$  |                      |      |          |      |                  |               |             |      |                  |           |
| $Q_{g,typ}$  | 26nC   |                      |      |          |      |                  |               |             |      |                  |           |
| $E_{oss} @ 400V$   | 6 $\mu$ J  |                      |      |          |      |                  |               |             |      |                  |           |



| Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted                    |                 |                                 |           |            |                    |
|---|-----------------|---------------------------------|-----------|------------|--------------------|
| Parameter   | Symbol          | AOT27S60L/AOB27S60L             | AOTF27S60 | AOTF27S60L | Units              |
| Drain-Source Voltage  | $V_{DS}$        | 600                             |           |            | V                  |
| Gate-Source Voltage   | $V_{GS}$        | $\pm 30$                        |           |            | V                  |
| Continuous Drain Current  | $I_D$           | $T_C=25^\circ\text{C}$          | 27        | 27*        | A                  |
|   |                 | $T_C=100^\circ\text{C}$         | 17        | 17*        |                    |
| Pulsed Drain Current <sup>C</sup>   | $I_{DM}$        | 110                             |           |            | A                  |
| Avalanche Current <sup>C</sup>  | $I_{AR}$        | 7.5                             |           |            | A                  |
| Repetitive avalanche energy <sup>C</sup>  | $E_{AR}$        | 110                             |           |            | mJ                 |
| Single pulsed avalanche energy <sup>G</sup>   | $E_{AS}$        | 480                             |           |            | mJ                 |
| Power Dissipation <sup>B</sup>  | $P_D$           | $T_C=25^\circ\text{C}$          | 357       | 50         | W                  |
|   |                 | Derate above $25^\circ\text{C}$ | 2.9       | 0.4        |                    |
| MOSFET $dv/dt$ ruggedness   | $dv/dt$         | 100                             |           |            | V/ns               |
| Peak diode recovery $dv/dt$ <sup>H</sup>  | $dv/dt$         | 20                              |           |            | V/ns               |
| Junction and Storage Temperature Range  | $T_J, T_{STG}$  | -55 to 150                      |           |            | $^\circ\text{C}$   |
| Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds <sup>J</sup> | $T_L$           | 300                             |           |            | $^\circ\text{C}$   |
| Thermal Characteristics   |                 |                                 |           |            |                    |
| Parameter   | Symbol          | AOT27S60L/AOB27S60L             | AOTF27S60 | AOTF27S60L | Units              |
| Maximum Junction-to-Ambient <sup>A,D</sup>  | $R_{\theta JA}$ | 65                              | 65        | 65         | $^\circ\text{C/W}$ |
| Maximum Case-to-sink <sup>A</sup>   | $R_{\theta CS}$ | 0.5                             | --        | --         | $^\circ\text{C/W}$ |
| Maximum Junction-to-Case  | $R_{\theta JC}$ | 0.35                            | 2.5       | 3.1        | $^\circ\text{C/W}$ |

\* Drain current limited by maximum junction temperature.


**Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)**

| Symbol                      | Parameter   | Conditions   | Min | Typ  | Max  | Units |
|-----------------------------|---|--|-----|------|------|-------|
| <b>STATIC PARAMETERS</b>    |   |  |     |      |      |       |
| BV <sub>DSS</sub>           | Drain-Source Breakdown Voltage                            | I <sub>D</sub> =250μA, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C                           | 600 | -    | -    | V     |
|                             |   | I <sub>D</sub> =250μA, V <sub>GS</sub> =0V, T <sub>J</sub> =150°C                          | 650 | 700  | -    |       |
| I <sub>DSS</sub>            | Zero Gate Voltage Drain Current                           | V <sub>DS</sub> =600V, V <sub>GS</sub> =0V   | -   | -    | 1    | μA    |
|                             |   | V <sub>DS</sub> =480V, T <sub>J</sub> =150°C   | -   | 10   | -    |       |
| I <sub>GSS</sub>            | Gate-Body leakage current                                 | V <sub>DS</sub> =0V, V <sub>GS</sub> =±30V   | -   | -    | ±100 | nA    |
| V <sub>GS(th)</sub>         | Gate Threshold Voltage                                    | V <sub>DS</sub> =5V, I <sub>D</sub> =250μA   | 2.5 | 3.3  | 4    | V     |
| R <sub>DS(ON)</sub>         | Static Drain-Source On-Resistance                         | V <sub>GS</sub> =10V, I <sub>D</sub> =13.5A, T <sub>J</sub> =25°C                          | -   | 0.14 | 0.16 | Ω     |
|                             |   | V <sub>GS</sub> =10V, I <sub>D</sub> =13.5A, T <sub>J</sub> =150°C                         | -   | 0.38 | 0.44 | Ω     |
| V <sub>SD</sub>             | Diode Forward Voltage                                     | I <sub>S</sub> =13.5A, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C                           | -   | 0.85 | -    | V     |
| I <sub>S</sub>              | Maximum Body-Diode Continuous Current                     |  | -   | -    | 27   | A     |
| I <sub>SM</sub>             | Maximum Body-Diode Pulsed Current                         |  | -   | -    | 110  | A     |
| <b>DYNAMIC PARAMETERS</b>   |   |  |     |      |      |       |
| C <sub>iss</sub>            | Input Capacitance   | V <sub>GS</sub> =0V, V <sub>DS</sub> =100V, f=1MHz   | -   | 1294 | -    | pF    |
| C <sub>oss</sub>            | Output Capacitance  |  | -   | 80   | -    | pF    |
| C <sub>o(er)</sub>          | Effective output capacitance, energy related <sup>H</sup> | V <sub>GS</sub> =0V, V <sub>DS</sub> =0 to 480V, f=1MHz                                    | -   | 69   | -    | pF    |
| C <sub>o(tr)</sub>          | Effective output capacitance, time related <sup>I</sup>   |  | -   | 221  | -    | pF    |
| C <sub>rss</sub>            | Reverse Transfer Capacitance                              | V <sub>GS</sub> =0V, V <sub>DS</sub> =100V, f=1MHz   | -   | 2.3  | -    | pF    |
| R <sub>g</sub>              | Gate resistance   | V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz   | 2.4 | 4.7  | 6.7  | Ω     |
| <b>SWITCHING PARAMETERS</b> |   |  |     |      |      |       |
| Q <sub>g</sub>              | Total Gate Charge   | V <sub>GS</sub> =10V, V <sub>DS</sub> =480V, I <sub>D</sub> =13.5A                         | -   | 26   | -    | nC    |
| Q <sub>gs</sub>             | Gate Source Charge  |  | -   | 6.2  | -    | nC    |
| Q <sub>gd</sub>             | Gate Drain Charge   |  | -   | 8.8  | -    | nC    |
| t <sub>D(on)</sub>          | Turn-On Delay Time  | V <sub>GS</sub> =10V, V <sub>DS</sub> =400V, I <sub>D</sub> =13.5A,<br>R <sub>G</sub> =25Ω | -   | 31   | -    | ns    |
| t <sub>r</sub>              | Turn-On Rise Time   |  | -   | 33   | -    | ns    |
| t <sub>D(off)</sub>         | Turn-Off Delay Time                                       |  | -   | 99   | -    | ns    |
| t <sub>f</sub>              | Turn-Off Fall Time  |  | -   | 34   | -    | ns    |
| t <sub>rr</sub>             | Body Diode Reverse Recovery Time                          | I <sub>F</sub> =13.5A, dI/dt=100A/μs, V <sub>DS</sub> =400V                                | -   | 440  | -    | ns    |
| I <sub>rm</sub>             | Peak Reverse Recovery Current                             | I <sub>F</sub> =13.5A, dI/dt=100A/μs, V <sub>DS</sub> =400V                                | -   | 28   | -    | A     |
| Q <sub>rr</sub>             | Body Diode Reverse Recovery Charge                        | I <sub>F</sub> =13.5A, dI/dt=100A/μs, V <sub>DS</sub> =400V                                | -   | 7.5  | -    | μC    |

A. The value of R<sub>θJA</sub> is measured with the device in a still air environment with T<sub>A</sub>=25°C.

B. The power dissipation P<sub>D</sub> is based on T<sub>J(MAX)</sub>=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150°C. Ratings are based on low frequency and duty cycles to keep initial T<sub>J</sub>=25°C.

D. The R<sub>θJA</sub> is the sum of the thermal impedance from junction to case R<sub>θJC</sub> and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300 μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of T<sub>J(MAX)</sub>=150°C. The SOA curve provides a single pulse rating.

G. L=60mH, I<sub>AS</sub>=4A, V<sub>DD</sub>=150V, Starting T<sub>J</sub>=25°C

H. C<sub>o(er)</sub> is a fixed capacitance that gives the same stored energy as C<sub>oss</sub> while V<sub>DS</sub> is rising from 0 to 80% V<sub>(BR)DSS</sub>.

I. C<sub>o(tr)</sub> is a fixed capacitance that gives the same charging time as C<sub>oss</sub> while V<sub>DS</sub> is rising from 0 to 80% V<sub>(BR)DSS</sub>.

J. Wave soldering only allowed at leads.

APPLICATIONS OR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.



**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




Figure 1: On-Region Characteristics@25° C




Figure 2: On-Region Characteristics@125° C




Figure 3: Transfer Characteristics




Figure 4: On-Resistance vs. Drain Current and Gate Voltage




Figure 5: On-Resistance vs. Junction Temperature




Figure 6: Break Down vs. Junction Temperature



**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




Figure 7: Body-Diode Characteristics (Note E)




Figure 8: Gate-Charge Characteristics




Figure 9: Capacitance Characteristics




Figure 10: Coss stored Energy




Figure 11: Maximum Forward Biased Safe Operating Area for AOT(B)27S60L (Note F)






Figure 12: Maximum Forward Biased Safe Operating Area for AOTF27S60 (Note F)




**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**



**Figure 13: Maximum Forward Biased Safe Operating Area for AOTF27S60L(Note F)**



**Figure 14: Avalanche energy**



**Figure 15: Current De-rating (Note B)**



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 16: Normalized Maximum Transient Thermal Impedance for AOT(B)27S60L (Note F)




Figure 17: Normalized Maximum Transient Thermal Impedance for AOTF27S60 (Note F)






Figure 18: Normalized Maximum Transient Thermal Impedance for AOTF27S60L (Note F)




Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.