

FP100R12KT4BOSA1 Datasheet



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	FP100R12KT4BOSA1-DG
Manufacturer	Infineon Technologies
Manufacturer Product Number	FP100R12KT4BOSA1
Description	IGBT MOD 1200V 100A 515W
Detailed Description	IGBT Module Trench Field Stop Three Phase Inverter 1200 V 100 A 515 W Chassis Mount Module

This model FP100R12KT4BOSA1 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

FP100R12KT4BOSA1

Series:

EconoPIM™ 3

IGBT Type:

Trench Field Stop

Voltage - Collector Emitter Breakdown (Max):

1200 V

Power - Max:

515 W

Current - Collector Cutoff (Max):

1 mA

Input:

Standard

Operating Temperature:

-40°C ~ 150°C

Package / Case:

Module

Base Product Number:

FP100R12

Manufacturer:

Infineon Technologies

Product Status:

Active

Configuration:

Three Phase Inverter

Current - Collector (Ic) (Max):

100 A

Vce(on) (Max) @ Vge, Ic:

2.2V @ 15V, 100A

Input Capacitance (Cies) @ Vce:

6.3 nF @ 25 V

NTC Thermistor:

Yes

Mounting Type:

Chassis Mount

Supplier Device Package:

Module

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8541.29.0095

Moisture Sensitivity Level (MSL):

Not Applicable

ECCN:

EAR99

Final datasheet

EconoPIM™3 module with fast Trench/Fieldstop IGBT4 and emitter controlled 4 diode

Features

- Electrical features
 - $V_{CES} = 1200\text{ V}$
 - $I_{C\text{ nom}} = 100\text{ A} / I_{CRM} = 200\text{ A}$
 - Low switching losses
 - $T_{vj,op} = 150^{\circ}\text{C}$
 - $V_{CE,sat}$ with positive temperature coefficient
 - Low $V_{CE,sat}$
- Mechanical features
 - High power and thermal cycling capability
 - Copper base plate
 - Solder contact technology
 - Standard housing



Typical appearance


Potential applications

- Auxiliary inverters
- Medical applications
- Motor drives
- Servo drives

Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

Description



FP100R12KT4

EconoPIM™3 module

Table of contents

Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	IGBT, Inverter	3
3	Diode, Inverter	5
4	Diode, Rectifier	6
5	IGBT, Brake-Chopper	7
6	Diode, Brake-Chopper	8
7	NTC-Thermistor	9
8	Characteristics diagrams	10
9	Circuit diagram	14
10	Package outlines	15
11	Module label code	16
	Revision history	17
	Disclaimer	18

FP100R12KT4

EconoPIM™3 module

1 Package

1 Package

Table 1 Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	V_{ISOL}	$t = 1 \text{ min}$	2.5	kV
Material of module baseplate			Cu	
Internal isolation			Al_2O_3	
Creepage distance	d_{Creep}		10.0	mm
Clearance	d_{Clear}		7.5	mm
Comparative tracking index	CTI		> 200	
Relative thermal index (electrical)	RTI		120	°C

Table 2 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Thermal resistance, case to heat sink	R_{thCH}	$\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$		0.009		K/W
Stray inductance module	L_{sCE}			40		nH
Module lead resistance, terminals - chip	$R_{AA'+CC'}$			3		mΩ
Module lead resistance, terminals - chip	$R_{CC'+EE'}$			4		mΩ
Storage temperature	T_{stg}		-40		125	°C
Mounting torque for module mounting	M	M5	3		6	Nm
Weight	G			300		g

2 IGBT, Inverter

Table 3 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Collector-emitter voltage	V_{CES}	$T_{vj} = 25 \text{ °C}$	1200	V
Continuous DC collector current	I_{CDC}	$T_{vj \text{ max}} = 175 \text{ °C}$ $T_C = 95 \text{ °C}$	100	A
Repetitive peak collector current	I_{CRM}	t_p limited by $T_{vj \text{ op}}$	200	A
Gate-emitter peak voltage	V_{GES}		±20	V

FP100R12KT4

EconoPIM™3 module

2 IGBT, Inverter

Table 4 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Collector-emitter saturation voltage	$V_{CE\ sat}$	$I_C = 150\ A, V_{GE} = 15\ V$	$T_{vj} = 25\ ^\circ C$		1.75	2.10	V
			$T_{vj} = 125\ ^\circ C$		2.05		
			$T_{vj} = 150\ ^\circ C$		2.10		
Gate threshold voltage	V_{GETh}	$I_C = 3.8\ mA, V_{CE} = V_{GE}, T_{vj} = 25\ ^\circ C$		5.20	5.80	6.40	V
Gate charge	Q_G	$V_{GE} = \pm 15\ V$			0.8		μC
Internal gate resistor	R_{Gint}	$T_{vj} = 25\ ^\circ C$			7.5		Ω
Input capacitance	C_{ies}	$f = 1000\ kHz, T_{vj} = 25\ ^\circ C, V_{CE} = 25\ V, V_{GE} = 0\ V$			6.3		nF
Reverse transfer capacitance	C_{res}	$f = 1000\ kHz, T_{vj} = 25\ ^\circ C, V_{CE} = 25\ V, V_{GE} = 0\ V$			0.27		nF
Collector-emitter cut-off current	I_{CES}	$V_{CE} = 1200\ V, V_{GE} = 0\ V$	$T_{vj} = 25\ ^\circ C$			1	mA
Gate-emitter leakage current	I_{GES}	$V_{CE} = 0\ V, V_{GE} = 20\ V, T_{vj} = 25\ ^\circ C$				100	nA
Turn-on delay time (inductive load)	t_{don}	$I_C = 150\ A, V_{CC} = 600\ V, V_{GE} = \pm 15\ V, R_{Gon} = 1.6\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.160		μs
			$T_{vj} = 125\ ^\circ C$		0.170		
			$T_{vj} = 150\ ^\circ C$		0.170		
Rise time (inductive load)	t_r	$I_C = 150\ A, V_{CC} = 600\ V, V_{GE} = \pm 15\ V, R_{Gon} = 1.6\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.030		μs
			$T_{vj} = 125\ ^\circ C$		0.040		
			$T_{vj} = 150\ ^\circ C$		0.040		
Turn-off delay time (inductive load)	t_{doff}	$I_C = 150\ A, V_{CC} = 600\ V, V_{GE} = \pm 15\ V, R_{Goff} = 1.6\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.330		μs
			$T_{vj} = 125\ ^\circ C$		0.430		
			$T_{vj} = 150\ ^\circ C$		0.450		
Fall time (inductive load)	t_f	$I_C = 150\ A, V_{CC} = 600\ V, V_{GE} = \pm 15\ V, R_{Goff} = 1.6\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.080		μs
			$T_{vj} = 125\ ^\circ C$		0.150		
			$T_{vj} = 150\ ^\circ C$		0.170		
Turn-on energy loss per pulse	E_{on}	$I_C = 150\ A, V_{CC} = 600\ V, L_\sigma = 40\ nH, V_{GE} = \pm 15\ V, R_{Gon} = 1.6\ \Omega, di/dt = 3000\ A/\mu s (T_{vj} = 150\ ^\circ C)$	$T_{vj} = 25\ ^\circ C$		5.5		mJ
			$T_{vj} = 125\ ^\circ C$		8.5		
			$T_{vj} = 150\ ^\circ C$		9.5		
Turn-off energy loss per pulse	E_{off}	$I_C = 150\ A, V_{CC} = 600\ V, L_\sigma = 40\ nH, V_{GE} = \pm 15\ V, R_{Goff} = 1.6\ \Omega, dv/dt = 3600\ V/\mu s (T_{vj} = 150\ ^\circ C)$	$T_{vj} = 25\ ^\circ C$		5.5		mJ
			$T_{vj} = 125\ ^\circ C$		8.5		
			$T_{vj} = 150\ ^\circ C$		9.5		
SC data	I_{SC}	$V_{GE} \leq 15\ V, V_{CC} = 800\ V, V_{CEmax} = V_{CES} - L_{sCE} * di/dt$	$t_P \leq 10\ \mu s, T_{vj} = 150\ ^\circ C$		400		A

(table continues...)

FP100R12KT4

EconoPIM™3 module

3 Diode, Inverter

Table 4 (continued) Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Thermal resistance, junction to case	R_{thJC}	per IGBT			0.290	K/W
Thermal resistance, case to heat sink	R_{thCH}	per IGBT, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$		0.130		K/W
Temperature under switching conditions	T_{vjop}		-40		150	°C

3 Diode, Inverter

Table 5 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	V_{RRM}	$T_{vj} = 25 \text{ °C}$	1200	V	
Continuous DC forward current	I_F		100	A	
Repetitive peak forward current	I_{FRM}	$t_p = 1 \text{ ms}$	200	A	
I^2t - value	I^2t	$t_p = 10 \text{ ms}, V_R = 0 \text{ V}$	$T_{vj} = 125 \text{ °C}$	1550	A^2s
			$T_{vj} = 150 \text{ °C}$	1500	

Table 6 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	V_F	$I_F = 100 \text{ A}, V_{GE} = 0 \text{ V}$	$T_{vj} = 25 \text{ °C}$	1.70	2.15	V
			$T_{vj} = 125 \text{ °C}$	1.65		
			$T_{vj} = 150 \text{ °C}$	1.65		
Peak reverse recovery current	I_{RM}	$V_{CC} = 600 \text{ V}, I_F = 100 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 3000 \text{ A}/\mu\text{s} (T_{vj} = 150 \text{ °C})$	$T_{vj} = 25 \text{ °C}$	115		A
			$T_{vj} = 125 \text{ °C}$	125		
			$T_{vj} = 150 \text{ °C}$	130		
Recovered charge	Q_r	$V_{CC} = 600 \text{ V}, I_F = 100 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 3000 \text{ A}/\mu\text{s} (T_{vj} = 150 \text{ °C})$	$T_{vj} = 25 \text{ °C}$	9.5		μC
			$T_{vj} = 125 \text{ °C}$	17.5		
			$T_{vj} = 150 \text{ °C}$	20.5		
Reverse recovery energy	E_{rec}	$V_{CC} = 600 \text{ V}, I_F = 100 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 3000 \text{ A}/\mu\text{s} (T_{vj} = 150 \text{ °C})$	$T_{vj} = 25 \text{ °C}$	3.5		mJ
			$T_{vj} = 125 \text{ °C}$	6		
			$T_{vj} = 150 \text{ °C}$	7.5		

(table continues...)

FP100R12KT4

EconoPIM™3 module

4 Diode, Rectifier

Table 6 (continued) Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Thermal resistance, junction to case	R_{thJC}	per diode			0.500	K/W
Thermal resistance, case to heat sink	R_{thCH}	per diode, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$		0.225		K/W
Temperature under switching conditions	$T_{vj,op}$		-40		150	°C

4 Diode, Rectifier

Table 7 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	V_{RRM}	$T_{vj} = 25 \text{ °C}$	1600	V	
Maximum RMS forward current per chip	I_{FRMSM}	$T_C = 80 \text{ °C}$	100	A	
Maximum RMS current at rectifier output	I_{RMSM}	$T_C = 80 \text{ °C}$	150	A	
Surge forward current	I_{FSM}	$t_p = 10 \text{ ms}$	$T_{vj} = 25 \text{ °C}$	1150	A
			$T_{vj} = 150 \text{ °C}$	880	
I^2t - value	I^2t	$t_p = 10 \text{ ms}$	$T_{vj} = 25 \text{ °C}$	6600	A ² s
			$T_{vj} = 150 \text{ °C}$	3850	

Table 8 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	V_F	$I_F = 100 \text{ A}$, $T_{vj} = 150 \text{ °C}$		1.00		V
Reverse current	I_r	$T_{vj} = 150 \text{ °C}$, $V_R = 1600 \text{ V}$		1		mA
Thermal resistance, junction to case	R_{thJC}	per diode			0.400	K/W
Thermal resistance, case to heat sink	R_{thCH}	per diode, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$		0.180		K/W
Temperature under switching conditions	$T_{vj,op}$		-40		150	°C

FP100R12KT4

EconoPIM™3 module

5 IGBT, Brake-Chopper

5 IGBT, Brake-Chopper

Table 9 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Collector-emitter voltage	V_{CES}	$T_{vj} = 25\text{ °C}$	1200	V
Continuous DC collector current	I_{CDC}	$T_{vj\text{ max}} = 175\text{ °C}$ $T_C = 95\text{ °C}$	50	A
Repetitive peak collector current	I_{CRM}	t_p limited by $T_{vj\text{ op}}$	100	A
Gate-emitter peak voltage	V_{GES}		± 20	V

Table 10 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{CE\text{ sat}}$	$I_C = 50\text{ A}$, $V_{GE} = 15\text{ V}$	$T_{vj} = 25\text{ °C}$	1.85	2.15	V
			$T_{vj} = 125\text{ °C}$	2.15		
			$T_{vj} = 150\text{ °C}$	2.25		
Gate threshold voltage	V_{GETh}	$I_C = 1.6\text{ mA}$, $V_{CE} = V_{GE}$, $T_{vj} = 25\text{ °C}$	5.20	5.80	6.40	V
Gate charge	Q_G	$V_{GE} = \pm 15\text{ V}$	0.38			μC
Internal gate resistor	R_{Gint}	$T_{vj} = 25\text{ °C}$	4			Ω
Input capacitance	C_{ies}	$f = 1000\text{ kHz}$, $T_{vj} = 25\text{ °C}$, $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$	2.8			nF
Reverse transfer capacitance	C_{res}	$f = 1000\text{ kHz}$, $T_{vj} = 25\text{ °C}$, $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$	0.1			nF
Collector-emitter cut-off current	I_{CES}	$V_{CE} = 1200\text{ V}$, $V_{GE} = 0\text{ V}$ $T_{vj} = 25\text{ °C}$			1	mA
Gate-emitter leakage current	I_{GES}	$V_{CE} = 0\text{ V}$, $V_{GE} = 20\text{ V}$, $T_{vj} = 25\text{ °C}$			100	nA
Turn-on delay time (inductive load)	t_{don}	$I_C = 50\text{ A}$, $V_{CC} = 600\text{ V}$, $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 15\text{ }\Omega$	$T_{vj} = 25\text{ °C}$	0.160		μs
			$T_{vj} = 125\text{ °C}$	0.170		
			$T_{vj} = 150\text{ °C}$	0.170		
Rise time (inductive load)	t_r	$I_C = 50\text{ A}$, $V_{CC} = 600\text{ V}$, $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 15\text{ }\Omega$	$T_{vj} = 25\text{ °C}$	0.030		μs
			$T_{vj} = 125\text{ °C}$	0.040		
			$T_{vj} = 150\text{ °C}$	0.040		
Turn-off delay time (inductive load)	t_{doff}	$I_C = 50\text{ A}$, $V_{CC} = 600\text{ V}$, $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 15\text{ }\Omega$	$T_{vj} = 25\text{ °C}$	0.330		μs
			$T_{vj} = 125\text{ °C}$	0.430		
			$T_{vj} = 150\text{ °C}$	0.450		

(table continues...)

FP100R12KT4 EconoPIM™3 module

6 Diode, Brake-Chopper

Table 10 (continued) Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Fall time (inductive load)	t_f	$I_C = 50 \text{ A}, V_{CC} = 600 \text{ V},$ $V_{GE} = \pm 15 \text{ V}, R_{Goff} = 15 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}$	0.080		μs
			$T_{vj} = 125 \text{ }^\circ\text{C}$	0.150		
			$T_{vj} = 150 \text{ }^\circ\text{C}$	0.170		
Turn-on energy loss per pulse	E_{on}	$I_C = 50 \text{ A}, V_{CC} = 600 \text{ V},$ $L_\sigma = 20 \text{ nH}, V_{GE} = \pm 15 \text{ V},$ $R_{Gon} = 15 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}$	5.7		mJ
			$T_{vj} = 125 \text{ }^\circ\text{C}$	7.7		
			$T_{vj} = 150 \text{ }^\circ\text{C}$	8.4		
Turn-off energy loss per pulse	E_{off}	$I_C = 50 \text{ A}, V_{CC} = 600 \text{ V},$ $L_\sigma = 20 \text{ nH}, V_{GE} = \pm 15 \text{ V},$ $R_{Goff} = 15 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}$	2.8		mJ
			$T_{vj} = 125 \text{ }^\circ\text{C}$	4.3		
			$T_{vj} = 150 \text{ }^\circ\text{C}$	4.8		
SC data	I_{SC}	$V_{GE} \leq 15 \text{ V}, V_{CC} = 800 \text{ V},$ $V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$	$t_p \leq 10 \mu\text{s},$ $T_{vj} = 125 \text{ }^\circ\text{C}$	180		A
Thermal resistance, junction to case	R_{thJC}	per IGBT			0.540	K/W
Thermal resistance, case to heat sink	R_{thCH}	per IGBT, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$		0.245		K/W
Temperature under switching conditions	$T_{vj op}$		-40		150	$^\circ\text{C}$

6 Diode, Brake-Chopper

Table 11 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	V_{RRM}	$T_{vj} = 25 \text{ }^\circ\text{C}$	1200	V	
Continuous DC forward current	I_F		25	A	
Repetitive peak forward current	I_{FRM}	$t_p = 1 \text{ ms}$	50	A	
I^2t - value	I^2t	$t_p = 10 \text{ ms}, V_R = 0 \text{ V}$	$T_{vj} = 125 \text{ }^\circ\text{C}$	90	A^2s
			$T_{vj} = 150 \text{ }^\circ\text{C}$	80	

FP100R12KT4 EconoPIM™3 module

7 NTC-Thermistor

Table 12 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Forward voltage	V_F	$I_F = 25 \text{ A}$, $V_{GE} = 0 \text{ V}$	$T_{vj} = 25 \text{ °C}$		1.75	2.15	V
			$T_{vj} = 125 \text{ °C}$		1.75		
			$T_{vj} = 150 \text{ °C}$		1.75		
Peak reverse recovery current	I_{RM}	$V_{CC} = 600 \text{ V}$, $I_F = 25 \text{ A}$, $-di_F/dt = 1200 \text{ A}/\mu\text{s}$ ($T_{vj} = 150 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$		39		A
			$T_{vj} = 125 \text{ °C}$		40		
			$T_{vj} = 150 \text{ °C}$		41		
Recovered charge	Q_r	$V_{CC} = 600 \text{ V}$, $I_F = 25 \text{ A}$, $-di_F/dt = 1200 \text{ A}/\mu\text{s}$ ($T_{vj} = 150 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$		2.4		μC
			$T_{vj} = 125 \text{ °C}$		4.1		
			$T_{vj} = 150 \text{ °C}$		4.4		
Reverse recovery energy	E_{rec}	$V_{CC} = 600 \text{ V}$, $I_F = 25 \text{ A}$, $-di_F/dt = 1200 \text{ A}/\mu\text{s}$ ($T_{vj} = 150 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$		0.9		mJ
			$T_{vj} = 125 \text{ °C}$		1.5		
			$T_{vj} = 150 \text{ °C}$		1.7		
Thermal resistance, junction to case	R_{thJC}	per diode			1.35	K/W	
Thermal resistance, case to heat sink	R_{thCH}	per diode, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$		0.610		K/W	
Temperature under switching conditions	$T_{vj\text{op}}$		-40		150	$^{\circ}\text{C}$	

7 NTC-Thermistor

Table 13 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	R_{25}	$T_{NTC} = 25 \text{ °C}$		5		k Ω
Deviation of R_{100}	$\Delta R/R$	$T_{NTC} = 100 \text{ °C}$, $R_{100} = 493 \text{ }\Omega$	-5		5	%
Power dissipation	P_{25}	$T_{NTC} = 25 \text{ °C}$			20	mW
B-value	$B_{25/50}$			3375		K
B-value	$B_{25/80}$			3411		K
B-value	$B_{25/100}$			3433		K

Note: Specification according to the valid application note.

FP100R12KT4
EconoPIM™3 module


8 Characteristics diagrams

8 Characteristics diagrams

Output characteristic (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$V_{GE} \leq 15\text{ V}$



Output characteristic field (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$T_{vj} = 150\text{ °C}$



Transfer characteristic (typical), IGBT, Inverter

$I_C = f(V_{GE})$


$V_{CE} = 20\text{ V}$



Switching losses (typical), IGBT, Inverter

$E = f(I_C)$

$R_{Goff} = 1.6\ \Omega, R_{Gon} = 1.6\ \Omega, V_{GE} = \pm 15\text{ V}, V_{CC} = 600\text{ V}$




FP100R12KT4
EconoPIM™3 module

8 Characteristics diagrams

Switching losses (typical), IGBT, Inverter

$E = f(R_G)$


$V_{GE} = \pm 15\text{ V}$, $I_C = 150\text{ A}$, $V_{CC} = 600\text{ V}$



Reverse bias safe operating area (RBSOA), IGBT, Inverter


$I_C = f(V_{CE})$

$R_{Goff} = 1.6\ \Omega$, $V_{GE} = \pm 15\text{ V}$, $T_{vj} = 150\text{ °C}$




Transient thermal impedance, IGBT, Inverter

$Z_{th} = f(t)$



Forward characteristic (typical), Diode, Inverter

$I_F = f(V_F)$




FP100R12KT4
EconoPIM™3 module

8 Characteristics diagrams

Switching losses (typical), Diode, Inverter

$E_{rec} = f(I_F)$


$R_{Gon} = R_{Gon}(IGBT), V_{CC} = 600 V$



Switching losses (typical), Diode, Inverter


$E_{rec} = f(R_G)$

$I_F = 100 A, V_{CC} = 600 V$




Transient thermal impedance, Diode, Inverter

$Z_{th} = f(t)$



Forward characteristic (typical), Diode, Rectifier

$I_F = f(V_F)$






FP100R12KT4
EconoPIM™3 module

8 Characteristics diagrams

Output characteristic (typical), IGBT, Brake-Chopper


$I_C = f(V_{CE})$

$V_{GE} = 15\text{ V}$




Forward characteristic (typical), Diode, Brake-Chopper

$I_F = f(V_F)$



Temperature characteristic (typical), NTC-Thermistor

$R = f(T_{NTC})$



FP100R12KT4
EconoPIM™3 module

9 Circuit diagram

9 **Circuit diagram**




Figure 1

FP100R12KT4 EconoPIM™3 module

11 Module label code

11 Module label code



Module label code			
Code format	Data Matrix	Barcode Code128	
Encoding	ASCII text	Code Set A	
Symbol size	16x16	23 digits	
Standard	IEC24720 and IEC16022	IEC8859-1	
Code content	Content	Digit	Example
	Module serial number	1 - 5	71549
	Module material number	6 - 11	142846
	Production order number	12 - 19	55054991
	Date code (production year)	20 - 21	15
	Date code (production week)	22 - 23	30
Example			
	71549142846550549911530		71549142846550549911530

Figure 3

FP100R12KT4 EconoPIM™3 module

Revision history

Revision history

Document revision	Date of release	Description of changes
V2.0	2007-11-12	Preliminary datasheet
n/a	2020-09-01	Datasheet migrated to a new system with a new layout and new revision number schema: target or preliminary datasheet = 0.xy; final datasheet = 1.xy
1.00	2024-08-02	Final datasheet

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2024-08-02

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2024 Infineon Technologies AG

All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference

IFX-AAV733-002

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.