


IPP25N06S3L-22 Datasheet

www.digi-electronics.com



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	IPP25N06S3L-22-DG
Manufacturer	Infineon Technologies
Manufacturer Product Number	IPP25N06S3L-22
Description	MOSFET N-CH 55V 25A TO220-3
Detailed Description	N-Channel 55 V 25A (Tc) 50W (Tc) Through Hole PG -TO220-3-1



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

IPP25N06S3L-22

Series:

OptiMOS™

FET Type:

N-Channel

Drain to Source Voltage (Vdss):

55 V

Drive Voltage (Max Rds On, Min Rds On):

5V, 10V

Vgs(th) (Max) @ Id:

2.2V @ 20µA

Vgs (Max):

±16V

FET Feature:

-

Operating Temperature:

-55°C ~ 175°C (Tj)

Supplier Device Package:

PG-TO220-3-1

Base Product Number:

IPP25N

Manufacturer:

Infineon Technologies

Product Status:

Obsolete

Technology:

MOSFET (Metal Oxide)

Current - Continuous Drain (Id) @ 25°C:

25A (Tc)

Rds On (Max) @ Id, Vgs:

21.6mOhm @ 17A, 10V

Gate Charge (Qg) (Max) @ Vgs:

47 nC @ 10 V

Input Capacitance (Ciss) (Max) @ Vds:

2260 pF @ 25 V

Power Dissipation (Max):

50W (Tc)

Mounting Type:

Through Hole

Package / Case:

TO-220-3

Environmental & Export classification

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

REACH Status:

REACH Unaffected

HTSUS:

8541.29.0095



IPB25N06S3L-22

IPI25N06S3L-22, IPP25N06S3L-22

OptiMOS® -T2 Power-Transistor



Features

- N-channel - Enhancement mode
- Automotive AEC Q101 qualified
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- Green product (RoHS compliant)
- 100% Avalanche tested

Product Summary

V_{DS}	55	V
$R_{DS(on),max}$ (SMD version)	21.3	mΩ
I_D	25	A


PG-TO263-3-2

PG-TO262-3-1

PG-TO220-3-1



Type	Package	Marking
IPB25N06S3L-22	PG-TO263-3-2	3N06L22
IPI25N06S3L-22	PG-TO262-3-1	3N06L22
IPP25N06S3L-22	PG-TO220-3-1	3N06L22



Maximum ratings, at $T_j=25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current ¹⁾	I_D	$T_C=25\text{ °C}$, $V_{GS}=10\text{ V}$	25	A
		$T_C=100\text{ °C}$, $V_{GS}=10\text{ V}^{2)}$	25	
Pulsed drain current ²⁾	$I_{D,pulse}$	$T_C=25\text{ °C}$	100	
Avalanche energy, single pulse ²⁾	E_{AS}	$I_D=12.5\text{ A}$	120	mJ
Avalanche current, single pulse	I_{AS}		25	A
Gate source voltage ³⁾	V_{GS}		±16	V
Power dissipation	P_{tot}	$T_C=25\text{ °C}$	50	W
Operating and storage temperature	T_j, T_{stg}		-55 ... +175	°C
IEC climatic category; DIN IEC 68-1			55/175/56	



IPB25N06S3L-22

IPI25N06S3L-22, IPP25N06S3L-22

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics²⁾						
Thermal resistance, junction - case	R_{thJC}		-	-	3.3	K/W
Thermal resistance, junction - ambient, leaded	R_{thJA}		-	-	62	
SMD version, device on PCB	R_{thJA}	minimal footprint	-	-	62	
		6 cm ² cooling area ⁴⁾	-	-	40	

Electrical characteristics, at $T_j=25\text{ }^\circ\text{C}$, unless otherwise specified

Static characteristics

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=1\text{ mA}$	55	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=20\text{ }\mu\text{A}$	1.2	1.7	2.2	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=55\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ }^\circ\text{C}$	-	0.01	1	μA
		$V_{DS}=55\text{ V}, V_{GS}=0\text{ V}, T_j=125\text{ }^\circ\text{C}^{2)}$	-	1	100	
Gate-source leakage current	I_{GSS}	$V_{GS}=16\text{ V}, V_{DS}=0\text{ V}$	-	1	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=5\text{ V}, I_D=11\text{ A}$	-	32.9	39.9	m Ω
		$V_{GS}=5\text{ V}, I_D=11\text{ A},$ SMD version	-	32.6	39.6	
		$V_{GS}=10\text{ V}, I_D=17\text{ A}$	-	18.4	21.6	
		$V_{GS}=10\text{ V}, I_D=17\text{ A},$ SMD version	-	18.1	21.3	



IPB25N06S3L-22

IPI25N06S3L-22, IPP25N06S3L-22

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic characteristics²⁾

Input capacitance	C_{iss}	$V_{GS}=0\text{ V}, V_{DS}=25\text{ V},$ $f=1\text{ MHz}$	-	2260	-	pF
Output capacitance	C_{oss}		-	283	-	
Reverse transfer capacitance	C_{rss}		-	270	-	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=27.5\text{ V},$ $V_{GS}=10\text{ V}, I_D=25\text{ A},$ $R_G=14.8\ \Omega$	-	9	-	ns
Rise time	t_r		-	26	-	
Turn-off delay time	$t_{d(off)}$		-	30	-	
Fall time	t_f		-	43	-	

Gate Charge Characteristics²⁾

Gate to source charge	Q_{gs}	$V_{DD}=11\text{ V}, I_D=25\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$	-	11	-	nC
Gate to drain charge	Q_{gd}		-	6	-	
Gate charge total	Q_g		-	31	47	
Gate plateau voltage	$V_{plateau}$		-	4.7	-	V

Reverse Diode

Diode continuous forward current ²⁾	I_S	$T_C=25\text{ °C}$	-	-	25	A
Diode pulse current ²⁾	$I_{S,pulse}$		-	-	100	
Diode forward voltage	V_{SD}	$V_{GS}=0\text{ V}, I_F=25\text{ A},$ $T_J=25\text{ °C}$	0.6	0.9	1.3	V
Reverse recovery time ²⁾	t_{rr}	$V_R=27.5\text{ V}, I_F=I_S,$ $di_F/dt=100\text{ A}/\mu\text{s}$	-	15	-	ns
Reverse recovery charge ²⁾	Q_{rr}		-	15	-	nC

¹⁾ Current is limited by bondwire; with an $R_{thJC} = 3.3\text{ K/W}$ the chip is able to carry 31 A at 25°C. For detailed information see Application Note ANPS071E

²⁾ Defined by design. Not subject to production test.


³⁾ Qualified at -5V and +16V.

⁴⁾ Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical in still air.




1 Power dissipation

$P_{tot} = f(T_C); V_{GS} \geq 4 V$



2 Drain current


$I_D = f(T_C); V_{GS} \geq 4 V$



3 Safe operating area

$I_D = f(V_{DS}); T_C = 25\text{ °C}; D = 0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJC} = f(t_p)$

parameter: $D = t_p/T$






5 Typ. output characteristics

$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)} = f(I_D); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



7 Typ. transfer characteristics


$I_D = f(V_{GS}); V_{DS} = 4\text{ V}$

parameter: T_j



8 Typ. drain-source on-state resistance

$R_{DS(on)} = f(T_j); I_D = 25\text{ A}; V_{GS} = 10\text{ V}$






9 Typ. gate threshold voltage


$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}$

parameter: I_D



10 Typ. capacitances


$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$



11 Typical forward diode characteristics

$I_F = f(V_{SD})$


parameter: T_j



12 Typ. avalanche characteristics

$I_{AV} = f(t_{AV})$

parameter: $T_{j(start)}$






13 Typical avalanche energy


$E_{AS} = f(T_j)$;

parameter: I_D



14 Drain-source breakdown voltage


$V_{BR(DSS)} = f(T_j); I_D = 1 \text{ mA}$




15 Typ. gate charge

$V_{GS} = f(Q_{gate}); I_D = 25 \text{ A pulsed}$

parameter: V_{DD}



16 Gate charge waveforms





Published by
Infineon Technologies AG
81726 Munich, Germany

© Infineon Technologies AG 2007
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office. Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.



Revision History

Version	Date	Changes
Data Sheet 2.1	15.12.2006	Removal of ordering code
Data Sheet 2.1	15.12.2006	Update of Infineon Logo
Data Sheet 2.1	15.12.2006	Implementation of avalanche current single pulse
Data Sheet 2.1	15.12.2006	Removal of ESD class
Data Sheet 2.1	15.12.2006	Update of Infineon address
Data Sheet 2.1	15.12.2006	Removal of foot note 3, avalanche diagrams
Data Sheet 2.1	15.12.2006	Update of Qrr and trr typ
Data Sheet 2.1	15.12.2006	Update of disclaimer
Data Sheet 2.1	15.12.2006	Implementation of RoHS and AEC logo, update of feature list
Data Sheet 1.1	07.11.2007	Update of data sheet layout
Data Sheet 1.1	07.11.2007	Adaptation of Ias
Data Sheet 1.1	07.11.2007	implementation of footnote 2 for Eas specification
Data Sheet 1.1	07.11.2007	removal of Vdg specification from data sheet

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.