

RM024-S50-C-01 Datasheet

www.digi-electronics.com



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	RM024-S50-C-01-DG
Manufacturer	Laird Connectivity Inc.
Manufacturer Product Number	RM024-S50-C-01
Description	RF TXRX MOD ISM > 1GHZ U.FL SMD
Detailed Description	General ISM > 1GHz RAMP Transceiver Module 2.4G Hz Antenna Not Included, U.FL Surface Mount

This model RM024-S50-C-01 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

RM024-S50-C-01

Series:

-

DiGi-Electronics Programmable:

Not Verified

Protocol:

RAMP

Frequency:

2.4GHz

Power - Output:

18dBm

Serial Interfaces:

UART

Utilized IC / Part:

-

Voltage - Supply:

2.3V ~ 3.6V

Current - Transmitting:

40mA ~ 166mA

Operating Temperature:

-40°C ~ 85°C

Manufacturer:

Laird Connectivity Inc.

Product Status:

Obsolete

RF Family/Standard:

General ISM > 1GHz

Modulation:

FHSS, MSK

Data Rate:

500kbps

Sensitivity:

-95dBm

Antenna Type:

Antenna Not Included, U.FL

Memory Size:

-

Current - Receiving:

9.5mA ~ 36mA

Mounting Type:

Surface Mount

Package / Case:

Module

Environmental & Export classification

Moisture Sensitivity Level (MSL):

3 (168 Hours)

HTSUS:

0000.00.0000

ECCN:


OBSOLETE

RAMP Modules

RM024



Innovative **Technology**
for a **Connected** World



RAMP MODULES

Laird Technologies RAMP (Range Amplified MultiPoint) modules are designed to provide robust wireless communications for any number of applications requiring a wireless transport for serial data. RAMP modules feature a Frequency Hopping Spread Spectrum (FHSS) protocol for excellent interference and multipath immunity. RAMP modules Server/Client architecture allows for more than 16 million clients to be addressed and communicating within the network.

RM024

The RM024 RAMP module is based on Laird Technologies LT2510 core technology, enhanced with a new RF front end for improved sleep, improved link budget and a switchable antenna output. The RM024 is available in two versions, one with 125 mW maximum conducted output power and approved for North American and similar markets and one with 50 mW maximum conducted output power and approved for European and similar markets. These modules are identical except for output power, transmit power consumption, and the number of RF Channels available. Differences between the two versions, where applicable, will be denoted based on part number.

Enhanced API commands provide packet routing control and network intelligence. With its field-proven FHSS air interface protocol, the RM024 rejects RF noise, excels in multipath scenarios, allows for co-located systems, and provides an extremely reliable communication link. It also provides a more robust, but simpler, link than ZigBee for RF applications that do not require a mesh topology.

With a throughput of up to 280 Kb/s, RM024 delivers speedy data rates. In addition, variable output power options (up to +21 dBm) enable communication over distances that aren't achievable with competing technologies. At the same time, a range of ultra-low power modes plus low Tx/Rx power consumption make the RM024 ideal for power-restrictive or battery-operated applications. The mini SMT package is well-suited for space-constrained designs and is available in pick-and-place packaging for volume manufacturing.

FEATURES

- Retries and acknowledgements
- Configurable network parameters
- Multiple generic I/O
- 280 kbps or 500 kbps RF data stream
- Idle current draw of 9.5 mA, sleep current of 50 uA
- Software selectable interface baud rates from 1200 bps to 460.8 kbps
- Upgradable FW through serial port
- Low cost, low power, and small size ideal for high volume, portable, and battery powered applications
- All modules are qualified for Industrial temperatures (-40°C to 85°C)
- Advanced configuration available using AT commands
- Easy to use Configuration & Test Utility software
- Switchable antenna output, either integrated antenna or external antenna through U.FL

global solutions: local support™

USA: +1.800.492.2320

Europe: +44.1628.858.940

Asia: +852.2268.6567

wirelessinfo@lairdtech.com

www.lairdtech.com/wireless



Innovative **Technology**
for a **Connected** World

RAMP Modules

RM024

GENERAL																
Form Factor	SMD-ANT+U.FL, Pluggable-ANT+U.FL, SMD-U.FL, Pluggable-U.FL															
Antenna	External antenna through U.FL connector or dual antenna with integrated antenna and U.FL															
Serial Interface Data Rate	Baud rates from 1200 bps to 460800 bps. Non-standard baud rates are also supported.															
Channels	FCC: 43 or 79 selectable channels, CE: 43 selectable channels															
Security	Channelization, System ID, and Vendor ID															
Minimum Flash (EEPROM) Memory Endurance	1000 Write/Erase Cycles															
TRANSCEIVER																
Frequency Band	2400 – 2483.5 MHz															
RF Data Rate (Raw)	280 kbps or 500 kbps selectable															
Hop Bin Spacing	900 kHz over 79 hops, 1500 kHz over 43 hops															
RF Technology	Frequency Hopping Spread Spectrum															
Modulation	MSK															
Maximum Output Power Conducted	FCC: +5 to +21 dBm selectable, CE: +3.5 to +18 dBm selectable															
Supply Voltage	2.3 – 3.6 V ± 50 mV ripple															
Current Draw	<table border="1"> <tbody> <tr> <td>100% Tx</td> <td>166 mA</td> <td>85 mA</td> </tr> <tr> <td>1/8 Tx (when selected)</td> <td>40 mA</td> <td>40 mA</td> </tr> <tr> <td>100% Rx</td> <td>36 mA</td> <td>36 mA</td> </tr> <tr> <td>Rx average (idle current)</td> <td>9.5 mA</td> <td>11.6 mA</td> </tr> <tr> <td>Deep sleep</td> <td>50 µA</td> <td>50 µA</td> </tr> </tbody> </table>	100% Tx	166 mA	85 mA	1/8 Tx (when selected)	40 mA	40 mA	100% Rx	36 mA	36 mA	Rx average (idle current)	9.5 mA	11.6 mA	Deep sleep	50 µA	50 µA
100% Tx	166 mA	85 mA														
1/8 Tx (when selected)	40 mA	40 mA														
100% Rx	36 mA	36 mA														
Rx average (idle current)	9.5 mA	11.6 mA														
Deep sleep	50 µA	50 µA														
Receiver Sensitivity (1% PER)	-95 dBm at 280 kbps RF Data Rate, -94 dBm at 500 kbps RF Data Rate															
Range (based on external 2.0 dBi antenna at 280 kbps RF Data Rate)	<table border="1"> <thead> <tr> <th></th> <th>Outdoor (line-of-sight)</th> <th>Indoor (estimated)</th> </tr> </thead> <tbody> <tr> <td>FCC</td> <td>2.5 miles (4 km)</td> <td>1300 ft (400 m)</td> </tr> <tr> <td>CE</td> <td>1.5 miles (2.4 km)</td> <td>790 ft (240 m)</td> </tr> </tbody> </table>		Outdoor (line-of-sight)	Indoor (estimated)	FCC	2.5 miles (4 km)	1300 ft (400 m)	CE	1.5 miles (2.4 km)	790 ft (240 m)						
	Outdoor (line-of-sight)	Indoor (estimated)														
FCC	2.5 miles (4 km)	1300 ft (400 m)														
CE	1.5 miles (2.4 km)	790 ft (240 m)														

PRODUCT PART NUMBERS

PART NUMBER	FORM FACTOR	MAXIMUM Tx POWER	ANTENNA	EEPROM PRODUCT ID
RM024-S125-C-01	SMT	125 mW	u.FL Jack	RM024125C01
RM024-S125-M-01	SMT	125 mW	Chip Antenna	RM024125M01
RM024-P125-C-01	Pluggable	125 mW	u.FL Jack	RM024125C01
RM024-P125-M-01	Pluggable	125 mW	Chip Antenna	RM024125M01
RM024-S50-C-01	SMT	50 mW (CE)	u.FL Jack	RM02450C01
RM024-S50-M-01	SMT	50 mW (CE)	Chip Antenna	RM02450M01
RM024-P50-C-01	Pluggable	50 mW (CE)	u.FL Jack	RM02450C01
RM024-P50-M-01	Pluggable	50 mW (CE)	Chip Ant	RM02450M01

EWS-DS-RM024 1012

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.