


# PMEG100V100ELPDZ Datasheet



[www.digi-electronics.com](http://www.digi-electronics.com)

<https://www.DiGi-Electronics.com>

|                              |                                     |
|------------------------------|-------------------------------------|
| DiGi Electronics Part Number | PMEG100V100ELPDZ-DG                 |
| Manufacturer                 | <a href="#">Nexperia USA Inc.</a>   |
| Manufacturer Product Number  | PMEG100V100ELPDZ                    |
| Description                  | DIODE SCHOTTKY 100V 10A CFP15       |
| Detailed Description         | Diode 100 V 10A Surface Mount CFP15 |

This model PMEG100V100ELPDZ is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

PMEG100V100ELPDZ

Series:

-

Technology:

Schottky

Current - Average Rectified (Io):

10A

Speed:

Fast Recovery =< 500ns, > 200mA (Io)

Current - Reverse Leakage @ Vr:

1  $\mu$ A @ 100 V

Grade:

Automotive

Mounting Type:

Surface Mount

Supplier Device Package:

CFP15

Base Product Number:

PMEG100

Manufacturer:

Nexperia USA Inc.

Product Status:

Not For New Designs

Voltage - DC Reverse (Vr) (Max):

100 V

Voltage - Forward (Vf) (Max) @ If:

850 mV @ 10 A

Reverse Recovery Time (trr):

14 ns

Capacitance @ Vr, F:

135pF @ 10V, 1MHz

Qualification:

AEC-Q101

Package / Case:

TO-277, 3-PowerDFN

Operating Temperature - Junction:

175°C (Max)

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8541.10.0080

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99



# PMEG100V100ELPD

100 V, 10 A low leakage current Schottky barrier rectifier

5 April 2018

Product data sheet

## 1. General description

Maximum Efficiency General Application (MEGA) Schottky barrier rectifier, encapsulated in a CFP15 (SOT1289) power and flat lead Surface-Mounted Device (SMD) plastic package.

## 2. Features and benefits

- Average forward current:  $I_{F(AV)} \leq 10$  A
- Reverse voltage:  $V_R \leq 100$  V
- Low leakage current due to high Schottky barrier technology
- Low forward voltage
- High power capability due to clip-bonding technology and heat sink
- High temperature  $T_j \leq 175$  °C
- Small and thin SMD power plastic package, typical height 0.78 mm
- AEC-Q101 qualified

## 3. Applications

- Low voltage rectification
- Automotive LED lighting
- High efficiency DC-to-DC conversion
- Switch mode power supply
- Reverse polarity protection
- Low power consumption application



## 4. Quick reference data

Table 1. Quick reference data

| Symbol      | Parameter               | Conditions   | Min | Typ | Max | Unit    |
|-------------|-------------------------|--|-----|-----|-----|---------|
| $I_{F(AV)}$ | average forward current | $\delta = 0.5$ ; $f = 20$ kHz; $T_{amb} \leq 150$ °C; square wave        | -   | -   | 10  | A       |
| $V_R$       | reverse voltage         | $T_j = 25$ °C  | -   | -   | 100 | V       |
| $V_F$       | forward voltage         | $I_F = 10$ A; $t_p \leq 300$ $\mu$ s; $\delta \leq 0.02$ ; $T_j = 25$ °C | -   | 770 | 850 | mV      |
| $I_R$       | reverse current         | $V_R = 100$ V; $t_p \leq 3$ ms; $\delta \leq 0.03$ ; $T_j = 25$ °C       | -   | 0.2 | 0.8 | $\mu$ A |

## 5. Pinning information

Table 2. Pinning information

| Pin | Symbol | Description | Simplified outline   | Graphic symbol  |
|-----|--------|-------------|--|---|
| 1   | A      | anode       |  <p>CFP15 (SOT1289)</p> |  <p>aaa-009063</p> |
| 2   | A      | anode       |  |   |
| 3   | K      | cathode     |  |   |

## 6. Ordering information

Table 3. Ordering information

| Type number     | Package |   |         |
|-----------------|---------|---|---------|
|                 | Name    | Description   | Version |
| PMEG100V100ELPD | CFP15   | plastic, thermal enhanced ultra thin SMD package; 3 leads;<br>body: 5.8 x 4.3 x 0.78 mm | SOT1289 |

## 7. Marking

Table 4. Marking codes

| Type number     | Marking code |
|-----------------|--------------|
| PMEG100V100ELPD | 100V L10E    |

## 8. Limiting values

**Table 5. Limiting values**

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol      | Parameter                           | Conditions   |     | Min | Max  | Unit |
|-------------|-------------------------------------|--|-----|-----|------|------|
| $V_R$       | reverse voltage                     | $T_j = 25\text{ °C}$   |     | -   | 100  | V    |
| $I_F$       | forward current                     | $\delta = 1; T_{sp} \leq 145\text{ °C}$                                    |     | -   | 14   | A    |
| $I_{F(AV)}$ | average forward current             | $\delta = 0.5; f = 20\text{ kHz}; T_{amb} \leq 150\text{ °C};$ square wave |     | -   | 10   | A    |
| $I_{FSM}$   | non-repetitive peak forward current | $t_p = 8\text{ ms};$ square wave; $T_{j(init)} = 25\text{ °C}$             |     | -   | 170  | A    |
|             |                                     | $t_p = 8.3\text{ ms};$ single half sine wave; $T_{j(init)} = 25\text{ °C}$ |     | -   | 210  | A    |
| $P_{tot}$   | total power dissipation             | $T_{amb} \leq 25\text{ °C}$  | [1] | -   | 1.66 | W    |
|             |                                     |  | [2] | -   | 2.15 | W    |
|             |                                     |  | [3] | -   | 3.75 | W    |
| $T_j$       | junction temperature                |  |     | -   | 175  | °C   |
| $T_{amb}$   | ambient temperature                 |  |     | -55 | 175  | °C   |
| $T_{stg}$   | storage temperature                 |  |     | -65 | 175  | °C   |

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for cathode  $1\text{ cm}^2$ .

[3] Device mounted on a ceramic Printed-Circuit Board (PCB),  $Al_2O_3$ , standard footprint.

## 9. Thermal characteristics

**Table 6. Thermal characteristics**

| Symbol         | Parameter  | Conditions  |         | Min | Typ | Max | Unit |
|----------------|--|-------------|---------|-----|-----|-----|------|
| $R_{th(j-a)}$  | thermal resistance from junction to ambient      | in free air | [1] [2] | -   | -   | 90  | K/W  |
|                |  |             | [1] [3] | -   | -   | 70  | K/W  |
|                |  |             | [1] [4] | -   | -   | 40  | K/W  |
| $R_{th(j-sp)}$ | thermal resistance from junction to solder point |             | [5]     | -   | -   | 3   | K/W  |


[1] For Schottky barrier diodes thermal runaway has to be considered, as in some applications the reverse power losses  $P_R$  are a significant part of the total power losses.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for cathode  $1\text{ cm}^2$ .


[4] Device mounted on a ceramic PCB,  $Al_2O_3$ , standard footprint.

[5] Soldering point of cathode tab.



FR4 PCB, standard footprint

Fig. 1. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values



FR4 PCB, mounting pad for cathode  $1\text{ cm}^2$

Fig. 2. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values





Fig. 3. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values

## 10. Characteristics

Table 7. Characteristics

| Symbol      | Parameter                 | Conditions   | Min | Typ | Max | Unit |
|-------------|---------------------------|--|-----|-----|-----|------|
| $V_{(BR)R}$ | reverse breakdown voltage | $I_R = 1 \text{ mA}$ ; $t_p \leq 1.2 \text{ ms}$ ; $\delta \leq 0.12$ ; pulsed; $T_j = 25 \text{ }^\circ\text{C}$    | 100 | -   | -   | V    |
| $V_F$       | forward voltage           | $I_F = 0.1 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$ | -   | 440 | -   | mV   |
|             |                           | $I_F = 1 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -   | 545 | 650 | mV   |
|             |                           | $I_F = 2 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -   | 610 | 710 | mV   |
|             |                           | $I_F = 4 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -   | 685 | -   | mV   |
|             |                           | $I_F = 5 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -   | 700 | 790 | mV   |
|             |                           | $I_F = 6 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -   | 720 | -   | mV   |
|             |                           | $I_F = 8 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -   | 745 | -   | mV   |
|             |                           | $I_F = 10 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 25 \text{ }^\circ\text{C}$  | -   | 770 | 850 | mV   |
|             |                           | $I_F = 10 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = -40 \text{ }^\circ\text{C}$ | -   | 870 | 960 | mV   |
|             |                           | $I_F = 5 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 125 \text{ }^\circ\text{C}$  | -   | 570 | -   | mV   |
|             |                           | $I_F = 10 \text{ A}$ ; $t_p \leq 300 \text{ } \mu\text{s}$ ; $\delta \leq 0.02$ ; $T_j = 125 \text{ }^\circ\text{C}$ | -   | 635 | 730 | mV   |


| Symbol    | Parameter                     | Conditions   | Min | Typ  | Max | Unit          |
|-----------|-------------------------------|--|-----|------|-----|---------------|
| $I_R$     | reverse current               | $V_R = 60 \text{ V}; t_p \leq 3 \text{ ms}; \delta \leq 0.03;$<br>$T_j = 25 \text{ }^\circ\text{C}$                  | -   | 0.06 | -   | $\mu\text{A}$ |
|           |                               | $V_R = 80 \text{ V}; t_p \leq 3 \text{ ms}; \delta \leq 0.03;$<br>$T_j = 25 \text{ }^\circ\text{C}$                  | -   | 0.09 | -   | $\mu\text{A}$ |
|           |                               | $V_R = 100 \text{ V}; t_p \leq 3 \text{ ms}; \delta \leq 0.03;$<br>$T_j = 25 \text{ }^\circ\text{C}$                 | -   | 0.2  | 0.8 | $\mu\text{A}$ |
|           |                               | $V_R = 100 \text{ V}; t_p \leq 3 \text{ ms}; \delta \leq 0.03;$<br>$T_j = 125 \text{ }^\circ\text{C}$                | -   | 0.38 | 2.5 | $\text{mA}$   |
|           |                               | $V_R = 60 \text{ V}; t_p \leq 3 \text{ ms}; \delta \leq 0.03;$<br>$T_j = 150 \text{ }^\circ\text{C}$                 | -   | 0.92 | 3.5 | $\text{mA}$   |
| $C_d$     | diode capacitance             | $V_R = 1 \text{ V}; f = 1 \text{ MHz}; T_j = 25 \text{ }^\circ\text{C}$  | -   | 365  | -   | $\text{pF}$   |
|           |                               | $V_R = 4 \text{ V}; f = 1 \text{ MHz}; T_j = 25 \text{ }^\circ\text{C}$  | -   | 215  | -   | $\text{pF}$   |
|           |                               | $V_R = 10 \text{ V}; f = 1 \text{ MHz}; T_j = 25 \text{ }^\circ\text{C}$   | -   | 135  | -   | $\text{pF}$   |
| $t_{rr}$  | reverse recovery time         | $I_F = 0.5 \text{ A}; I_R = 0.5 \text{ A}; I_{R(\text{meas})} = 0.1 \text{ A};$<br>$T_j = 25 \text{ }^\circ\text{C}$ | -   | 14   | -   | $\text{ns}$   |
| $V_{FRM}$ | peak forward recovery voltage | $I_F = 0.5 \text{ A}; dI_F/dt = 20 \text{ A}/\mu\text{s}; T_j = 25 \text{ }^\circ\text{C}$                           | -   | 555  | -   | $\text{mV}$   |



pulsed condition

- (1)  $T_j = 175 \text{ }^\circ\text{C}$
- (2)  $T_j = 150 \text{ }^\circ\text{C}$
- (3)  $T_j = 125 \text{ }^\circ\text{C}$
- (4)  $T_j = 100 \text{ }^\circ\text{C}$
- (5)  $T_j = 85 \text{ }^\circ\text{C}$
- (6)  $T_j = 25 \text{ }^\circ\text{C}$
- (7)  $T_j = -40 \text{ }^\circ\text{C}$


**Fig. 4. Forward current as a function of forward voltage; typical values**



pulsed condition


- (1)  $T_j = 175 \text{ }^\circ\text{C}$
- (2)  $T_j = 150 \text{ }^\circ\text{C}$
- (3)  $T_j = 125 \text{ }^\circ\text{C}$
- (4)  $T_j = 100 \text{ }^\circ\text{C}$
- (5)  $T_j = 85 \text{ }^\circ\text{C}$
- (6)  $T_j = 25 \text{ }^\circ\text{C}$
- (7)  $T_j = -40 \text{ }^\circ\text{C}$

**Fig. 5. Reverse current as a function of reverse voltage; typical values**



$f = 1 \text{ MHz}; T_{\text{amb}} = 25 \text{ }^\circ\text{C}$


**Fig. 6. Diode capacitance as a function of reverse voltage; typical values**



$T_j = 100 \text{ }^\circ\text{C}$

- (1)  $\delta = 0.1$
- (2)  $\delta = 0.2$
- (3)  $\delta = 0.5$
- (4)  $\delta = 0.8$
- (5)  $\delta = 1$


**Fig. 7. Average forward power dissipation as a function of average forward current; typical values**



$T_j = 100 \text{ }^\circ\text{C}$

- (1)  $\delta = 1$
- (2)  $\delta = 0.9$
- (3)  $\delta = 0.8$
- (4)  $\delta = 0.5$
- (5)  $\delta = 0.2$


**Fig. 8. Average reverse power dissipation as a function of reverse voltage; typical values**



$T_j = 175 \text{ }^\circ\text{C}$


- (1)  $\delta = 1$
- (2)  $\delta = 0.5$
- (3)  $\delta = 0.2$
- (4)  $\delta = 0.1$

**Fig. 9. Average reverse power dissipation as a function of reverse voltage; typical values**




FR4 PCB, standard footprint  
 $T_j = 175\text{ °C}$   
 (1)  $\delta = 1$ ; DC  
 (2)  $\delta = 0.5$ ;  $f = 20\text{ kHz}$   
 (3)  $\delta = 0.2$ ;  $f = 20\text{ kHz}$   
 (4)  $\delta = 0.1$ ;  $f = 20\text{ kHz}$

**Fig. 10. Average forward current as a function of ambient temperature; typical values**




FR4 PCB, mounting pad for cathode  $1\text{ cm}^2$   
 $T_j = 175\text{ °C}$   
 (1)  $\delta = 1$ ; DC  
 (2)  $\delta = 0.5$ ;  $f = 20\text{ kHz}$   
 (3)  $\delta = 0.2$ ;  $f = 20\text{ kHz}$   
 (4)  $\delta = 0.1$ ;  $f = 20\text{ kHz}$

**Fig. 11. Average forward current as a function of ambient temperature; typical values**



Ceramic PCB,  $\text{Al}_2\text{O}_3$ , standard footprint  
 $T_j = 175\text{ °C}$   
 (1)  $\delta = 1$  (DC)  
 (2)  $\delta = 0.5$ ;  $f = 20\text{ kHz}$   
 (3)  $\delta = 0.2$ ;  $f = 20\text{ kHz}$   
 (4)  $\delta = 0.1$ ;  $f = 20\text{ kHz}$

**Fig. 12. Average forward current as a function of ambient temperature; typical values**



$T_j = 175\text{ °C}$   
 (1)  $\delta = 1$  (DC)  
 (2)  $\delta = 0.5$ ;  $f = 20\text{ kHz}$   
 (3)  $\delta = 0.2$ ;  $f = 20\text{ kHz}$   
 (4)  $\delta = 0.1$ ;  $f = 20\text{ kHz}$

**Fig. 13. Average forward current as a function of solder point temperature; typical values**

### 11. Test information




Fig. 14. Reverse recovery definition




Fig. 15. Forward recovery definition




Fig. 16. Duty cycle definition

The current ratings for the typical waveforms are calculated according to the equations:  
 $I_{F(AV)} = I_M \times \delta$  with  $I_M$  defined as peak current,  $I_{RMS} = I_{F(AV)}$  at DC, and  $I_{RMS} = I_M \times \sqrt{\delta}$  with  $I_{RMS}$  defined as RMS current.

**Quality information**

This product has been qualified in accordance with the Automotive Electronics Council (AEC) standard Q101 - Stress test qualification for discrete semiconductors, and is suitable for use in automotive applications.

**12. Package outline**




Fig. 17. Package outline CFP15 (SOT1289)

**13. Soldering**




Fig. 18. Reflow soldering footprint for CFP15 (SOT1289)

## 14. Revision history

Table 8. Revision history

| Data sheet ID       | Release date   | Data sheet status      | Change notice | Supersedes          |
|---------------------|--|------------------------|---------------|---------------------|
| PMEG100V100ELPD v.4 | 20180405   | Product data sheet     | -             | PMEG100V100ELPD v.3 |
| Modifications:      | <ul style="list-style-type: none"> <li><math>I_{FSM}</math> parameter added (sine wave)</li> </ul> |                        |               |                     |
| PMEG100V100ELPD v.3 | 20161004   | Product data sheet     | -             | PMEG100V100ELPD v.2 |
| PMEG100V100ELPD v.2 | 20160203   | Preliminary data sheet | -             | PMEG100V100ELPD v.1 |
| PMEG100V100ELPD v.1 | 20151117   |                        |               | -                   |

## 15. Legal information

### Data sheet status

| Document status [1][2]         | Product status [3] | Definition  |
|--------------------------------|--------------------|---|
| Objective [short] data sheet   | Development        | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification      | This document contains data from the preliminary specification.                       |
| Product [short] data sheet     | Production         | This document contains the product specification.                                     |

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions".
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

### Definitions

**Preview** — The document is a preview version only. The document is still subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia' aggregate and cumulative liability towards customer

for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use in automotive applications** — This Nexperia product has been qualified for use in automotive applications. Unless otherwise agreed in writing, the product is not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Translations** — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

### Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 16. Contents

---

|                                 |    |
|---------------------------------|----|
| 1. General description.....     | 1  |
| 2. Features and benefits.....   | 1  |
| 3. Applications.....            | 1  |
| 4. Quick reference data.....    | 1  |
| 5. Pinning information.....     | 2  |
| 6. Ordering information.....    | 2  |
| 7. Marking.....                 | 2  |
| 8. Limiting values.....         | 3  |
| 9. Thermal characteristics..... | 3  |
| 10. Characteristics.....        | 5  |
| 11. Test information.....       | 9  |
| 12. Package outline.....        | 10 |
| 13. Soldering.....              | 10 |
| 14. Revision history.....       | 11 |
| 15. Legal information.....      | 12 |

---

© Nexperia B.V. 2018. All rights reserved

For more information, please visit: <http://www.nexperia.com>  
 For sales office addresses, please send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)  
 Date of release: 5 April 2018

---

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.