

# PMN27UP,115 Datasheet

[www.digi-electronics.com](http://www.digi-electronics.com)



<https://www.DiGi-Electronics.com>

|                              |  |
|------------------------------|--|
| DiGi Electronics Part Number | PMN27UP,115-DG   |
| Manufacturer                 | <a href="#">Nexperia USA Inc.</a>                                    |
| Manufacturer Product Number  | PMN27UP,115  |
| Description                  | MOSFET P-CH 20V 5.7A 6TSOP   |
| Detailed Description         | P-Channel 20 V 5.7A (Ta) 540mW (Ta), 6.25W (Tc) Surface Mount 6-TSOP |



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

### Manufacturer Product Number:

PMN27UP,115

### Series:

-

### FET Type:

P-Channel

### Drain to Source Voltage (Vdss):

20 V

### Drive Voltage (Max Rds On, Min Rds On):

1.8V, 4.5V

### Vgs(th) (Max) @ Id:

950mV @ 250µA

### Vgs (Max):

±8V

### FET Feature:

-

### Operating Temperature:

-55°C ~ 150°C (Tj)

### Supplier Device Package:

6-TSOP

### Manufacturer:

Nexperia USA Inc.

### Product Status:

Obsolete

### Technology:

MOSFET (Metal Oxide)

### Current - Continuous Drain (Id) @ 25°C:

5.7A (Ta)

### Rds On (Max) @ Id, Vgs:

32mOhm @ 2.4A, 4.5V

### Gate Charge (Qg) (Max) @ Vgs:

31 nC @ 4.5 V

### Input Capacitance (Ciss) (Max) @ Vds:

2340 pF @ 10 V

### Power Dissipation (Max):

540mW (Ta), 6.25W (Tc)

### Mounting Type:

Surface Mount

### Package / Case:

SC-74, SOT-457

## Environmental & Export classification

### RoHS Status:

ROHS3 Compliant

### REACH Status:

REACH Unaffected

### HTSUS:

8541.29.0095

### Moisture Sensitivity Level (MSL):

1 (Unlimited)

### ECCN:

EAR99



# PMN27UP

20 V, 5.7 A P-channel Trench MOSFET

Rev. 1 — 13 July 2011

Product data sheet

## 1. Product profile

### 1.1 General description

P-channel enhancement mode Field-Effect Transistor (FET) in a small SOT457 (SC-74) Surface-Mounted Device (SMD) plastic package using Trench MOSFET technology.

### 1.2 Features and benefits

- 1.8 V  $R_{DSon}$  rated
- Very fast switching
- Trench MOSFET technology

### 1.3 Applications

- Relay driver
- High-speed line driver
- High-side load switch
- Switching circuits

### 1.4 Quick reference data

Table 1. Quick reference data

| Symbol                        | Parameter                        | Conditions  | Min | Typ | Max  | Unit |
|-------------------------------|----------------------------------|---|-----|-----|------|------|
| $V_{DS}$                      | drain-source voltage             | $T_j = 25\text{ °C}$  | -   | -   | -20  | V    |
| $V_{GS}$                      | gate-source voltage              |   | -8  | -   | 8    | V    |
| $I_D$                         | drain current                    | $V_{GS} = -4.5\text{ V}; T_{amb} = 25\text{ °C}$                  | [1] | -   | -5.7 | A    |
| <b>Static characteristics</b> |                                  |   |     |     |      |      |
| $R_{DSon}$                    | drain-source on-state resistance | $V_{GS} = -4.5\text{ V}; I_D = -2.4\text{ A}; T_j = 25\text{ °C}$ | -   | 27  | 32   | mΩ   |

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated, mounting pad for drain 6 cm<sup>2</sup>.

## 2. Pinning information

Table 2. Pinning information

| Pin | Symbol | Description | Simplified outline    | Graphic symbol   |
|-----|--------|-------------|-----------------------|------------------|
| 1   | D      | drain       | <p>SOT457 (TSOP6)</p> | <p>017aaa094</p> |
| 2   | D      | drain       |                       |                  |
| 3   | G      | gate        |                       |                  |
| 4   | S      | source      |                       |                  |
| 5   | D      | drain       |                       |                  |
| 6   | D      | drain       |                       |                  |

### 3. Ordering information

Table 3. Ordering information

| Type number | Package |  | Version |
|-------------|---------|--|---------|
|             | Name    | Description                                      |         |
| PMN27UP     | TSOP6   | plastic surface-mounted package (TSOP6); 6 leads | SOT457  |

### 4. Marking

Table 4. Marking codes

| Type number | Marking code |
|-------------|--------------|
| PMN27UP     | ZU           |

### 5. Limiting values


Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol                    | Parameter               | Conditions   | Min | Max | Unit |    |
|---------------------------|-------------------------|--|-----|-----|------|----|
| $V_{DS}$                  | drain-source voltage    | $T_j = 25\text{ °C}$   | -   | -20 | V    |    |
| $V_{GS}$                  | gate-source voltage     |  | -8  | 8   | V    |    |
| $I_D$                     | drain current           | $V_{GS} = -4.5\text{ V}; T_{amb} = 25\text{ °C}$                         | [1] | -   | -5.7 | A  |
|                           |                         | $V_{GS} = -4.5\text{ V}; T_{amb} = 100\text{ °C}$                        | [1] | -   | -3.5 | A  |
| $I_{DM}$                  | peak drain current      | $T_{amb} = 25\text{ °C};$ single pulse; $t_p \leq 10\text{ }\mu\text{s}$ | -   | -23 | A    |    |
| $P_{tot}$                 | total power dissipation | $T_{amb} = 25\text{ °C}$   | [2] | -   | 540  | mW |
|                           |                         |  | [1] | -   | 1385 | mW |
|                           |                         | $T_{sp} = 25\text{ °C}$  |     | -   | 6250 | mW |
| $T_j$                     | junction temperature    |  | -55 | 150 | °C   |    |
| $T_{amb}$                 | ambient temperature     |  | -55 | 150 | °C   |    |
| $T_{stg}$                 | storage temperature     |  | -65 | 150 | °C   |    |
| <b>Source-drain diode</b> |                         |  |     |     |      |    |
| $I_S$                     | source current          | $T_{amb} = 25\text{ °C}$   | [1] | -   | -1.5 | A  |


[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated, mounting pad for drain 6 cm<sup>2</sup>.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.




$$P_{der} = \frac{P_{tot}}{P_{tot(25^{\circ}\text{C})}} \times 100 \%$$

**Fig 1. Normalized total power dissipation as a function of junction temperature**



$$I_{der} = \frac{I_D}{I_{D(25^{\circ}\text{C})}} \times 100 \%$$

**Fig 2. Normalized continuous drain current as a function of junction temperature**



$I_{DM}$  = single pulse

- (1)  $t_p = 100 \mu\text{s}$
- (2)  $t_p = 1 \text{ ms}$
- (3)  $t_p = 10 \text{ ms}$
- (4) DC;  $T_{sp} = 25^{\circ}\text{C}$
- (5)  $t_p = 100 \text{ ms}$
- (6) DC;  $T_{amb} = 25^{\circ}\text{C}$ ; drain mounting pad  $6 \text{ cm}^2$

**Fig 3. Safe operating area; junction to ambient; continuous and peak drain currents as a function of drain-source voltage**


## 6. Thermal characteristics

**Table 6. Thermal characteristics**


| Symbol         | Parameter  | Conditions  | Min | Typ | Max | Unit |     |
|----------------|--|-------------|-----|-----|-----|------|-----|
| $R_{th(j-a)}$  | thermal resistance from junction to ambient      | in free air | [1] | -   | 200 | 230  | K/W |
|                |  |             | [2] | -   | 78  | 90   | K/W |
| $R_{th(j-sp)}$ | thermal resistance from junction to solder point |             | -   | 12  | 20  | K/W  |     |

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for drain 6 cm<sup>2</sup>.



**Fig 4. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values**




**Fig 5. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values**

## 7. Characteristics


Table 7. Characteristics

| Symbol                         | Parameter                        | Conditions   | Min   | Typ   | Max   | Unit          |
|--------------------------------|----------------------------------|--|-------|-------|-------|---------------|
| <b>Static characteristics</b>  |                                  |  |       |       |       |               |
| $V_{(BR)DSS}$                  | drain-source breakdown voltage   | $I_D = -250 \mu\text{A}$ ; $V_{GS} = 0 \text{ V}$ ; $T_j = 25 \text{ }^\circ\text{C}$  | -20   | -     | -     | V             |
| $V_{GSth}$                     | gate-source threshold voltage    | $I_D = -250 \mu\text{A}$ ; $V_{DS} = V_{GS}$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -0.45 | -0.7  | -0.95 | V             |
| $I_{DSS}$                      | drain leakage current            | $V_{DS} = -20 \text{ V}$ ; $V_{GS} = 0 \text{ V}$ ; $T_j = 25 \text{ }^\circ\text{C}$  | -     | -     | -1    | $\mu\text{A}$ |
|                                |                                  | $V_{DS} = -20 \text{ V}$ ; $V_{GS} = 0 \text{ V}$ ; $T_j = 150 \text{ }^\circ\text{C}$   | -     | -     | -10   | $\mu\text{A}$ |
| $I_{GSS}$                      | gate leakage current             | $V_{GS} = -8 \text{ V}$ ; $V_{DS} = 0 \text{ V}$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -     | -     | -100  | nA            |
| $R_{DSon}$                     | drain-source on-state resistance | $V_{GS} = -4.5 \text{ V}$ ; $I_D = -2.4 \text{ A}$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -     | 27    | 32    | m $\Omega$    |
|                                |                                  | $V_{GS} = -4.5 \text{ V}$ ; $I_D = -2.4 \text{ A}$ ; $T_j = 150 \text{ }^\circ\text{C}$  | -     | 41    | 48    | m $\Omega$    |
|                                |                                  | $V_{GS} = -2.5 \text{ V}$ ; $I_D = -2.0 \text{ A}$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -     | 36    | 41    | m $\Omega$    |
|                                |                                  | $V_{GS} = -1.8 \text{ V}$ ; $I_D = -1.8 \text{ A}$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -     | 57    | 66    | m $\Omega$    |
| $g_{fs}$                       | forward transconductance         | $V_{DS} = -5 \text{ V}$ ; $I_D = -2.4 \text{ A}$ ; $T_j = 25 \text{ }^\circ\text{C}$   | -     | 14    | -     | S             |
| <b>Dynamic characteristics</b> |                                  |  |       |       |       |               |
| $Q_{G(tot)}$                   | total gate charge                | $V_{DS} = -10 \text{ V}$ ; $I_D = -1 \text{ A}$ ; $V_{GS} = -4.5 \text{ V}$ ;<br>$T_j = 25 \text{ }^\circ\text{C}$   | -     | 21    | 31    | nC            |
| $Q_{GS}$                       | gate-source charge               |  | -     | 4.2   | -     | nC            |
| $Q_{GD}$                       | gate-drain charge                |  | -     | 2.8   | -     | nC            |
| $C_{iss}$                      | input capacitance                | $V_{DS} = -10 \text{ V}$ ; $f = 1 \text{ MHz}$ ; $V_{GS} = 0 \text{ V}$ ;<br>$T_j = 25 \text{ }^\circ\text{C}$   | -     | 2340  | -     | pF            |
| $C_{oss}$                      | output capacitance               |  | -     | 210   | -     | pF            |
| $C_{rss}$                      | reverse transfer capacitance     |  | -     | 150   | -     | pF            |
| $t_{d(on)}$                    | turn-on delay time               | $V_{DS} = -10 \text{ V}$ ; $V_{GS} = -4.5 \text{ V}$ ; $R_{G(ext)} = 6 \text{ }^\circ\Omega$ ;<br>$T_j = 25 \text{ }^\circ\text{C}$ ; $I_D = -1 \text{ A}$ | -     | 19    | -     | ns            |
| $t_r$                          | rise time                        |  | -     | 20    | -     | ns            |
| $t_{d(off)}$                   | turn-off delay time              |  | -     | 95    | -     | ns            |
| $t_f$                          | fall time                        |  | -     | 27    | -     | ns            |
| <b>Source-drain diode</b>      |                                  |  |       |       |       |               |
| $V_{SD}$                       | source-drain voltage             | $I_S = -2.4 \text{ A}$ ; $V_{GS} = 0 \text{ V}$ ; $T_j = 25 \text{ }^\circ\text{C}$  | -     | -0.75 | -1    | V             |



$T_j = 25\text{ }^\circ\text{C}$


**Fig 6. Output characteristics: drain current as a function of drain-source voltage; typical values**



$T_j = 25\text{ }^\circ\text{C}; V_{DS} = -3\text{ V}$

- (1) minimum values
- (2) typical values
- (3) maximum values


**Fig 7. Sub-threshold drain current as a function of gate-source voltage**



$T_j = 25\text{ }^\circ\text{C}$

- (1)  $V_{GS} = -1.5\text{ V}$
- (2)  $V_{GS} = -1.8\text{ V}$
- (3)  $V_{GS} = -2.0\text{ V}$
- (4)  $V_{GS} = -2.5\text{ V}$
- (5)  $V_{GS} = -4.5\text{ V}$

**Fig 8. Drain-source on-state resistance as a function of drain current; typical values**




$I_D = -2.4\text{ A}$

- (1)  $T_j = 150\text{ }^\circ\text{C}$
- (2)  $T_j = 25\text{ }^\circ\text{C}$


**Fig 9. Drain-source on-state resistance as a function of gate-source voltage; typical values**






$V_{DS} > I_D \times R_{DS(on)}$   
 (1)  $T_j = 25\text{ }^\circ\text{C}$   
 (2)  $T_j = 150\text{ }^\circ\text{C}$

Fig 10. Transfer characteristics: drain current as a function of gate-source voltage; typical values




$$a = \frac{R_{DS(on)}}{R_{DS(on)@25^\circ\text{C}}}$$

Fig 11. Normalized drain-source on-state resistance as a function of junction temperature; typical values




$I_D = -0.25\text{ mA}$ ;  $V_{DS} = V_{GS}$   
 (1) maximum values  
 (2) typical values  
 (3) minimum values

Fig 12. Gate-source threshold voltage as a function of junction temperature



$f = 1\text{ MHz}$ ;  $V_{GS} = 0\text{ V}$   
 (1)  $C_{iss}$   
 (2)  $C_{oss}$   
 (3)  $C_{rss}$

Fig 13. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values



$I_D = -2.4$  A;  $V_{DS} = -10$  V;  $T_{amb} = 25$  °C

Fig 14. Gate-source voltage as a function of gate charge; typical values





Fig 15. Gate charge waveform definitions



$V_{GS} = 0$  V  
 (1)  $T_j = 150$  °C  
 (2)  $T_j = 25$  °C

Fig 16. Source current as a function of source-drain voltage; typical values

## 8. Test information




Fig 17. Duty cycle definition

9. Package outline

Plastic surface-mounted package (TSOP6); 6 leads

SOT457




Fig 18. Package outline SOT457 (TSOP6)

10. Soldering




Fig 19. Reflow soldering footprint for SOT457 (TSOP6)




Fig 20. Wave soldering footprint for SOT457 (TSOP6)

## 11. Revision history

Table 8. Revision history

| Document ID | Release date | Data sheet status  | Change notice | Supersedes |
|-------------|--------------|--------------------|---------------|------------|
| PMN27UP v.1 | 20110713     | Product data sheet | -             | -          |

## 12. Legal information

### 12.1 Data sheet status

| Document status <sup>[1]</sup> <sup>[2]</sup> | Product status <sup>[3]</sup> | Definition  |
|---|-------------------------------|---|
| Objective [short] data sheet                  | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet                | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet                    | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

### 12.2 Definitions

**Preview** — The document is a preview version only. The document is still subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### 12.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

## 12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 13. Contact information

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)



## 14. Contents

---

|           |  |           |
|-----------|--|-----------|
| <b>1</b>  | <b>Product profile</b> . . . . .         | <b>1</b>  |
| 1.1       | General description . . . . .            | 1         |
| 1.2       | Features and benefits . . . . .          | 1         |
| 1.3       | Applications . . . . .                   | 1         |
| 1.4       | Quick reference data . . . . .           | 1         |
| <b>2</b>  | <b>Pinning information</b> . . . . .     | <b>1</b>  |
| <b>3</b>  | <b>Ordering information</b> . . . . .    | <b>2</b>  |
| <b>4</b>  | <b>Marking</b> . . . . .                 | <b>2</b>  |
| <b>5</b>  | <b>Limiting values</b> . . . . .         | <b>2</b>  |
| <b>6</b>  | <b>Thermal characteristics</b> . . . . . | <b>4</b>  |
| <b>7</b>  | <b>Characteristics</b> . . . . .         | <b>5</b>  |
| <b>8</b>  | <b>Test information</b> . . . . .        | <b>9</b>  |
| <b>9</b>  | <b>Package outline</b> . . . . .         | <b>10</b> |
| <b>10</b> | <b>Soldering</b> . . . . .               | <b>11</b> |
| <b>11</b> | <b>Revision history</b> . . . . .        | <b>12</b> |
| <b>12</b> | <b>Legal information</b> . . . . .       | <b>13</b> |
| 12.1      | Data sheet status . . . . .              | 13        |
| 12.2      | Definitions . . . . .                    | 13        |
| 12.3      | Disclaimers . . . . .                    | 13        |
| 12.4      | Trademarks . . . . .                     | 14        |
| <b>13</b> | <b>Contact information</b> . . . . .     | <b>14</b> |

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.