

MIMXRT1172DVMAA Datasheet

www.digi-electronics.com



| DiGi Electronics Part Number | MIMXRT1172DVMAA-DG |
|------------------------------|---|
| Manufacturer | NXP USA Inc. |
| Manufacturer Product Number | MIMXRT1172DVMAA |
| Description | IC MCU 32BIT EXT MEM 289MAPBGA |
| Detailed Description | ARM® Cortex®-M7 RT1170 Microcontroller IC 32-Bit S ingle-Core 800MHz External Program Memory 289- LFBGA (14x14) |

https://www.DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.



Purchase and inquiry

| Manufacturer Product Number: | Manufacturer: |
|--|---|
| MIMXRT1172DVMAA | NXP USA Inc. |
| Series: | Product Status: |
| RT1170 | Active |
| DiGi-Electronics Programmable: | Core Processor: |
| Not Verified | ARM [®] Cortex [®] -M7 |
| Core Size: | Speed: |
| 32-Bit Single-Core | 800MHz |
| Connectivity: | Peripherals: |
| CANbus, EBI/EMI, Ethernet, I2C, MMC/SD/SDIO, SAI, SPDIF, SPI, UART/L | JSBARTIV DISELLO DISECT/Reset, DMA, POR, PWM, WDT |
| Program Memory Size: | Program Memory Type: |
| | External Program Memory |
| EEPROM Size: | RAM Size: |
| | 2M x 8 |
| Voltage - Supply (Vcc/Vdd): | Data Converters: |
| - | A/D 2x12b; D/A 1x12b |
| Oscillator Type: | Operating Temperature: |
| Internal | 0°C ~ 95°C (TJ) |
| Mounting Type: | Supplier Device Package: |
| Surface Mount | 289-LFBGA (14x14) |
| Package / Case: | Base Product Number: |
| 289-LFBGA | MIMXRT1172 |

Environmental & Export classification

| RoHS Status: | Moisture Sensitivity Level (MSL): |
|------------------|-----------------------------------|
| ROHS3 Compliant | 3 (168 Hours) |
| REACH Status: | |
| REACH Unaffected | |



i.MX RT1170 CROSSOVER MCUs Ushering in the GHZ ERA

i.MX RT1170 crossover MCUs are setting speed records at 1GHz. This ground-breaking family combines superior computing power and multiple media capabilities with ease of use and real-time functionality.

PRODUCT HIGHLIGHTS

- High-performing Arm® Cortex®-M based device
 - Up to 6468 total CoreMarks[®] with Cortex-M7 @ 1 GHz + Cortex-M4 @ 400 MHz
- Real-time, low-latency response
 - Up to 2 MB SRAM:
 - 512 KB Cortex-M7 TCM + 128 KB ECC
 - \circ 256 KB Cortex-M4 TCM with ECC
 - 1 MB on-chip RAM + 128 KB ECC
 - Fast real-time response with latency as low as 12 ns
- Low-power operation
 - Low dynamic power with integrated DC-DC converter
 - Low-power run modes at 24 MHz
- Highly integrated
 - Advanced multimedia for GUI and enhanced HMI
 - Multiple display and CMOS sensor interfaces
 - OpenVG[™] graphics accelerator running up to 500 MHz

- Extensive memory interface options
 - Quad/Octal SPI and HyperFlash™/HyperRAM™, SDRAM, NAND/NOR Flash, SD/eMMC, PSRAM, LPSDRAM
- Security
 - Hardware Elliptic Curve Cryptography
 - Hardware-protected keys for secure boot
 - AES engine for data encryption
 - On-the-fly AES decryption for execute-in-place (NOR) from Quad/Octal SPI/HyperFlash
 - Part of the EdgeLock[™] Assurance program, more details available at nxp.com/EdgeLockAssurance

TARGET APPLICATIONS

- ML-based edge applications
- Industrial computing designs
- Motor control and power conversion
- Personal health and fitness
- Voice-enabled IoT devices

i.MX RT1170 CROSSOVER MCU FAMILY BLOCK DIAGRAM



Available on certain products within the family

i.MX RT1170 MCU FAMILY CONFIGURATIONS

| Device | i.MX RT1171 | i.MX RT1172 | i.MX RT1173 | i.MX RT1175 | i.MX RT1176 |
|--|--|--|-------------------------|--|--|
| Arm [®] Cortex [®] -M7 | 1 GHz/800 MHz* | 1 GHz/800 MHz* | 800 MHz | 1 GHz/800 MHz* | 1 GHz/800 MHz* |
| Cortex-M4 | - | - | 400 MHz | 400 MHz | 400 MHz |
| MIPI CSI / DSI | - | Y | Y | - | Y |
| OpenVG™ 1.1 | - | Y | Y | - | Y |
| CSI / LCDIF / PXP | - | Y | Y | - | Y |
| Ethernet | Y | Y | Y | Y | Y |
| TSN | - | - | - | - | Y |
| Tamper Protection | - | - | Y | - | - |
| HAB/AES/DES | Y | Y | Y | Y | Y |
| Packages | 289 MAPBGA | 289 MAPBGA | 289 MAPBGA | 289 MAPBGA | 289 MAPBGA |
| Qualification/ Temperature | Commercial/0-95 °C Industrial/-40 – 105 °C Auto/-40 – 125 °C | Commercial/0 – 95 °C Industrial/-40 – 105 °C Auto/-40 – 125 °C | Industrial/-40 – 105 °C | Commercial/0 – 95 °C Industrial/-40 – 105 °C Auto/-40 – 125 °C | Commercial/0 – 95 °C Industrial/-40 – 105 °C Auto/-40 – 125 °C |
| Part Numbers | MIMXRT1171DVMAA MIMXRT1171CVM8A MIMXRT1171AVM8A | MIMXRT1172DVMAA MIMXRT1172CVM8A MIMXRT1172AVM8A | MIMXRT1173CVM8A | MIMXRT1175DVMAA MIMXRT1175CVM8A MIMXRT1175AVM8A | MIMXRT1176DVMAA MIMXRT1176CVM8A MIMXRT1176AVM8A |

*First speed listed is speed for commercial-qualified device. Second speed listed is for industrial- and automotive-qualified devices.

i.MX RT1170 EVK FEATURES

| Processor | MIMXRT1176DVMAA |
|----------------------|--|
| Memory | 512 Mbit SDRAM memory 512 Mbit Octal flash 128 Mbit QSPI flash 2 Gbit Raw NAND flash 64 Mbit LPSPI flash TF socket for SD card |
| Graphics | MIPI LCD connectorMIPI camera sensor connector |
| Audio | Audio codec 4-pole audio headphone jack External speaker connection Microphone (analog and digital) SPDIF connector |
| Connectivity | 2 x Micro USB OTG connectors Ethernet (10/100/1000M) connector Ethernet (10/100M) connector M.2 connector CAN transceivers Arduino[®] interface FRDM motor control interface SIM card slot |
| Debug | JTAG connectorOnboard DAP-Link debugger |
| Sensor | 6-Axis ecompass (3-Axis magnetometer, 3-Axis accelerometer) sensor FXOS8700CQ |
| Ordering Information | MIMXRT1170-EVKRK055HDMIPI4M (5.5" 720p display) |



GET STARTED NOW

The i.MX RT1170 evaluation kit (EVK) helps you take your design to the next level by reducing complexity and accelerating time to market.

SOFTWARE AND TOOLS

NXP's MCUXpresso software and

tools offer comprehensive development solutions designed to optimize, ease and accelerate embedded system development of applications based on Cortex-M core devices from NXP, including its general purpose, crossover and Bluetooth-enabled MCUs.

nxp.com/iMXRT1170

NXP, the NXP logo and Kinetis and eIQ are trademarks of NXP B.V. All other product or service names are the property of their respective owners. OpenVG and the OpenVG logo are trademarks of the Khronos Group, Inc. Arm and Cortex are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2021 NXP B.V.







OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we striciy control the quality of products and services. Welcome your RFQ to Email: Info@DiGi-Electronics.com

| <section-header></section-header> | | |
|---|---|--|
| Herein Harris Harris Harris Harris Harris Harris Harris Harris Harris Harris Harris Harris Harris <t< td=""><td>Handbard Barran and Angel and Angel</td><td>A SA B CONTRACTOR OF A SA CONTRA</td></t<> | Handbard Barran and Angel | A SA B CONTRACTOR OF A SA CONTRA |





Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.