


AIML-1206-R56K-T Datasheet

www.digi-electronics.com



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	AIML-1206-R56K-T-DG
Manufacturer	Abracon LLC
Manufacturer Product Number	AIML-1206-R56K-T
Description	FIXED IND 560NH 150MA 550MOHM SM
Detailed Description	560 nH Shielded Multilayer Inductor 150 mA 550mOhm Max 1206 (3216 Metric)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

AIML-1206-R56K-T

Series:

AIML-1206

Type:

Multilayer

Inductance:

560 nH

Current Rating (Amps):

150 mA

Shielding:

Shielded

Q @ Freq:

35 @ 25MHz

Ratings:

-

Inductance Frequency - Test:

25 MHz

Package / Case:

1206 (3216 Metric)

Size / Dimension:

0.126" L x 0.063" W (3.20mm x 1.60mm)

Manufacturer:

Abracon LLC

Product Status:

Active

Material - Core:

Ferrite

Tolerance:

±10%

Current - Saturation (Isat):

-

DC Resistance (DCR):

550mOhm Max

Frequency - Self Resonant:

130MHz

Operating Temperature:

-55°C ~ 125°C

Mounting Type:

Surface Mount

Supplier Device Package:

1206

Height - Seated (Max):

0.055" (1.40mm)

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8504.50.8000

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

Multilayer Ferrite Chip Inductor



AIML-1206 Series

Request Samples



Check Inventory



3.2 x 1.6 x 0.85 mm
RoHS/RoHS II Compliant
MSL Level = 1

Features

- Monolithic structure for higher reliability, compact size, & lightweight
- Magnetically shielded design to eliminate cross coupling
- Excellent solderability and heat resistance for reflow soldering
- Perfect shape for PCB mounting with no polarity

Applications

- Resonance circuit, traps and filter circuits
- RF choke for cordless phones and radio equipment
- Communications, video and audio equipment, computers and remote Control.

Electrical Specifications

Part Number	L	Tolerance	Q	Test Frequency	SRF	DCR	Ir
	0.1MHz/1.0V		Min.				
Units	μH	%		MHz	MHz	Ω	mA
AIML-1206-R047	0.047	K, M	20	50	320	0.15	300
AIML-1206-R068	0.068	K, M	20	50	280	0.25	300
AIML-1206-R10	0.100	K	20	25	235	0.25	250
AIML-1206-R12	0.120	K	20	25	220	0.3	250
AIML-1206-R15	0.150	K	20	25	200	0.3	250
AIML-1206-R18	0.180	K	20	25	185	0.4	250
AIML-1206-R22	0.220	K	20	25	170	0.4	250
AIML-1206-R27	0.270	K	20	25	150	0.5	250
AIML-1206-R33	0.330	K	20	25	145	0.6	250
AIML-1206-R39	0.390	K	25	25	135	0.5	200
AIML-1206-R47	0.470	K	25	25	125	0.6	200
AIML-1206-R56	0.560	K	25	25	115	0.7	150
AIML-1206-R68	0.680	K	25	25	105	0.8	150
AIML-1206-R82	0.820	K	25	25	100	0.9	150
AIML-1206-1R0	1.0	K	45	10	75	0.40	100
AIML-1206-1R2	1.2	K	45	10	65	0.5	100
AIML-1206-1R5	1.5	K	45	10	60	0.5	50
AIML-1206-1R8	1.8	K	45	10	55	0.50	50
AIML-1206-2R2	2.2	K	45	10	50	0.6	50
AIML-1206-2R7	2.7	K	45	10	45	0.6	50
AIML-1206-3R3	3.3	K	45	10	41	0.7	50
AIML-1206-3R9	3.9	K	45	10	38	0.8	50
AIML-1206-4R7	4.7	K	45	10	35	0.9	50
AIML-1206-5R6	5.6	K	50	4	32	0.7	25



5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION E : 8/5/2024

ABRACON IS
ISO9001-2015
CERTIFIED

Multilayer Ferrite Chip Inductor



AIML-1206 Series

Request Samples



Check Inventory



3.2 x 1.6 x 0.85 mm
RoHS/RoHS II Compliant
 MSL Level = 1

Part Number	L	Tolerance	Q	Test Frequency	SRF	DCR	Ir
	0.1MHz/1.0V		Min.				
Units	μH	%		MHz	MHz	Ω	mA
AIML-1206-6R8	6.8	K	50	4	29	0.8	25
AIML-1206-8R2	8.2	K	50	4	26	0.9	25
AIML-1206-100	10.0	K	50	2	24	1	25
AIML-1206-120	12.0	K	50	2	22	1.05	15
AIML-1206-150	15.0	K	35	1	19	0.7	5
AIML-1206-180	18.0	K	35	1	18	0.7	5
AIML-1206-220	22.0	K	35	1	16	0.90	5
AIML-1206-270	27.0	K	35	1	14	0.90	5
AIML-1206-330 ^s	33.0	K	35	1	13	1.05	5
AIML-1206-390 ^s	39.0	K	40	1	11	3	5
AIML-1206-470 ^s	47.0	K	40	1	10	3.4	5

^s Height of this component is 1.10 ±0.2mm [0.043 ±0.008 inches]

Test Conditions and equipment

Q: HP4291 Impedance Analyzer, 50mV

DCR: HP4263A LCR meter

SRF: HP4291 Impedance analyzer

Ir: HP4291 Impedance Analyzer, DC power HP6632 and Adapter HP16200. ΔL/L (initial) ≥ -5%

Unless otherwise specified

Temperature: Ordinary Temperature (5 to 35°C)

Humidity: Ordinary Humidity (25 to 85% RH)

AIML-1206 Series is RoHS Compliant and Pb free

Part Identification

AIML-1206-6R8K-T ABRACON LLC FIXED IND 200MH 1206M 220MH0H 2M

AIML - 1206 - [] [] - []

Inductance Code

See Electrical Specification table

Tolerance

K = ± 10%
 M = ± 20%

Packaging

T: Tape and Reel (See Packaging)



ABRACON

5101 Hidden Creek Ln, Spicewood TX 78669
 Phone: 512-371-6159 Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISION E: 8/5/2024

ABRACON IS
 ISO9001-2015
 CERTIFIED

Multilayer Ferrite Chip Inductor



AIML-1206 Series

Request Samples




Check Inventory



3.2 x 1.6 x 0.85 mm
RoHS/RoHS II Compliant
MSL Level = 1

No Marking


Mechanical Specifications



Series	L	W	T	a1, a2
AIML-1206	3.20±0.20	1.60±0.20	0.85±0.2	0.50±0.30
	[0.126±0.008]	[0.063±0.008]	[0.033±0.008]	[0.02±0.012]

Note: Height of AIML-1206-330, AIML-1206-390, and AIML-1206-470 is 1.10 ±0.2mm [0.043 ±0.008 inches]

Dimensions: mm[inch]



Materials



5101 Hidden Creek Ln, Spicewood TX 78669
 Phone: 512-371-6159 Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISION E : 8/5/2024

ABRACON IS
 ISO9001-2015
 CERTIFIED

Multilayer Ferrite Chip Inductor



AIML-1206 Series

Request Samples




Check Inventory



3.2 x 1.6 x 0.85 mm
RoHS/RoHS II Compliant
MSL Level = 1

	Components	Material
1	Base Material	Ferrite (Ni-Cu-Zn series)
2	Internal Conductor	Ag
3	Terminal Electrode	Ag
4	Terminal Electrode	Ni-Sn

Reflow Profile



Zone	Description	Temperature	Times
1	Preheat	$T_{SMIN} \sim T_{SMAX}$ 150°C ~ 200°C	60 ~ 180 sec.
2	Reflow	T_L 217°C	60 ~ 150 sec.
3	Peak heat	T_P 260°C	3 ~ 4 sec. MAX

Packaging



5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION E : 8/5/2024

ABRACON IS
ISO9001-2015
CERTIFIED

Multilayer Ferrite Chip Inductor



AIML-1206 Series

Request Samples




Check Inventory




3.2 x 1.6 x 0.85 mm
RoHS/RoHS II Compliant
MSL Level = 1

Tape & Reel: 3,000 pcs/reel



Codes	A	B	C	D	E	F	G	H	ΦJ	t(max)
AIML-1206	2.0±0.2	3.6±0.2	8.0±0.3	3.5±0.05	1.75±0.1	4.0±0.1	2.0±0.05	4.0±0.1	1.5+0.1/-0	2.0±0.05



A	B	C	D	E	W	t	R
178±2	60±2	13.0±0.5	21.0±0.8	2.0±0.5	10.0±1.15	1.2±0.2	1.0±0.25

AIML-1206-328K-1 VPL9CON LLC FIXED IND 200NH 120MA 220MOHM 2M

Dimensions: mm

ATTENTION: Abracon LLC's products are Commercial-Off-The-Shelf (COTS), which are designed, intended and validated for use in commercial, industrial and automotive applications. The customer is responsible for testing and verifying the performance of an Abracon solution to meet their system-level requirements.



5101 Hidden Creek Ln, Spicewood TX 78669
 Phone: 512-371-6159 Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISION E : 8/5/2024

ABRACON IS
 ISO9001-2015
 CERTIFIED

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we strictly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.