


PA4337.334NLT Datasheet

www.digi-electronics.com



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	PA4337.334NLT-DG
Manufacturer	Pulse Electronics
Manufacturer Product Number	PA4337.334NLT
Description	FIXED IND 330UH 570MA 1.651 OHM
Detailed Description	330 μ H Shielded Inductor 570 mA 1.651Ohm Max Nonstandard



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

PA4337.334NLT

Series:

PA4337.XXXNLT

Type:

-

Inductance:

330 μ H

Current Rating (Amps):

570 mA

Shielding:

Shielded

Q @ Freq:

-

Ratings:

-

Inductance Frequency - Test:

100 kHz

Mounting Type:

Surface Mount

Supplier Device Package:

-

Height - Seated (Max):

0.177" (4.50mm)

Manufacturer:

Pulse Electronics

Product Status:

Active

Material - Core:

Iron

Tolerance:

\pm 20%

Current - Saturation (Isat):

570mA

DC Resistance (DCR):

1.651Ohm Max

Frequency - Self Resonant:

-

Operating Temperature:

-40°C ~ 125°C

Features:

-

Package / Case:

Nonstandard

Size / Dimension:

0.236" L x 0.236" W (6.00mm x 6.00mm)

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8504.50.8000

Moisture Sensitivity Level (MSL):

1 (Unlimited)






ECCN:

EAR99

SMT Power Inductors

Shielded Drum Core - PA4337.XXXNLT Series



-  **Height:** 4.5mm Max
-  **Footprint:** 6.3mm x 6.3mm Max
-  **Current Rating:** up to 6.5A
-  **Inductance Range:** 0.47uH to 1500uH
-  *Shielded magnetic circuit reduces leakage flux, Fe base metal core enables high saturation and metalized core termination results in excellent shock resistance.*

Electrical Specifications @ 25°C - Operating Temperature -40°C to +125°C


Part Number	Inductance 100 KHz, 1V	DC Resistance	Saturation Current	Rated Current
		± 30%	≤30% Drop	<40°C Rise
	uH	mΩ	A	A
PA4337.471NLT	0.47±30%	8	10.00	6.50
PA4337.472NLT	4.7±20%	26	5.00	3.00
PA4337.103NLT	10.0±20%	46	3.30	2.50
PA4337.333NLT	33.0±20%	140	1.65	1.40
PA4337.104NLT	100±20%	416	1.00	0.80
PA4337.334NLT	330±20%	2000	0.50	0.45
PA4337.105NLT	1000±20%	4500	0.30	0.30
PA4337.155NLT	1500±20%	6989	0.28	0.21

Notes:

- Actual temperature of the component during system operation (ambient plus temperature rise) must be within the standard operating range.
- The saturation current is the current at which the initial inductance drops approximately 30% at the stated ambient temperature. This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effect) to the component.
- The Rated Current is the DC current required to raise the component temperature by 40 °C maximum. Take note that the component's performance varies depending on the system condition. It is suggested that the component be tested at the system level, to verify the temperature rise of the component during system operation.

Mechanical

PA4337.XXXNLT



SMT Power Inductors


Shielded Drum Core - PA4337.XXXNLT Series



Series	A	B	C	D	E	F	a	b	c
PA4337.XXXNLT	6.0±0.3	6.0±0.3	4.5MAX	4.9±0.3	1.65±0.3	2.7±0.3	2.4 TYP	1.85TYP	5.1 TYP



All Dimensions in mm.

TAPE & REEL INFO



SURFACE MOUNTING TYPE, REEL/TAPE LIST						
TYPE	REEL SIZE (mm)		TAPE SIZE (mm)			QTY
	A	G	P ₁	W	K ₀	PCS/REEL
PA4337.XXXNLT	Ø330	16.5	8	16	4.75	1500


Typical Performance Curves




SMT Power Inductor

Shielded Drum Core - PA4337.XXXNLT Series


PA4337.104NLT




PA4337.334NLT



PA4337.105NLT



PA4337.155NLT



For More Information

Americas - prodinfo_power_americas@yageo.com | Europe - prodinfo_power_emea@yageo.com | Asia - prodinfo_power_asia@yageo.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. Pulse Electronics, Inc. All rights reserved.

YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.