

# PA4344.102ANLT Datasheet

[www.digi-electronics.com](http://www.digi-electronics.com)



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	PA4344.102ANLT-DG
Manufacturer	<a href="#">Pulse Electronics</a>
Manufacturer Product Number	PA4344.102ANLT
Description	FIXED IND 1UH 52A 1.2 MOHM SMD
Detailed Description	1 $\mu$ H Shielded Molded Inductor 52 A 1.2mOhm Max Nonstandard



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

PA4344.102ANLT

Series:

PA4344.XXXANLT

Type:

Molded

Inductance:

1  $\mu$ H

Current Rating (Amps):

52 A

Shielding:

Shielded

Q @ Freq:

-

Ratings:

AEC-Q200

Inductance Frequency - Test:

100 kHz

Mounting Type:

Surface Mount

Supplier Device Package:

-

Height - Seated (Max):

0.276" (7.00mm)

Manufacturer:

Pulse Electronics

Product Status:

Active

Material - Core:

-

Tolerance:

$\pm$ 20%

Current - Saturation (Isat):

50A

DC Resistance (DCR):

1.2mOhm Max

Frequency - Self Resonant:

-

Operating Temperature:

-55°C ~ 155°C

Features:

-

Package / Case:

Nonstandard

Size / Dimension:

0.701" L x 0.665" W (17.80mm x 16.90mm)

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8504.50.8000

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

# SMT Power Inductor

High Current Molded Power Inductor - PA4344.XXXANLT Series



- Ⓟ **Height:** 7.0mm Max
- Ⓟ **Footprint:** 18.3mm x 17.2mm Max
- Ⓟ **Current Rating:** up to 55.0A
- Ⓟ **Inductance Range:** 0.47uH to 82uH
- Ⓟ Shielded construction and compact design
- Ⓟ High current, low DCR, and high efficiency
- Ⓟ Minimized acoustic noise and minimized leakage flux
- Ⓟ 200 Vdc Isolation between terminal and core

## Electrical Specifications @ 25°C - Operating Temperature -55°C to +155°C

Part Number	Inductance <sup>5,8</sup> 100KHz, 1V  uH±20%	Rated <sup>7</sup> Current  A	DC Resistance		Saturation <sup>2</sup> Current	SRF	K Factor
			TYP.	MAX.	TYP.	TYP.	
			mΩ	mΩ	A	MHz	
PA4344.471ANLT	0.47	55	0.7	0.9	100	56	44.2
PA4344.561ANLT	0.56	50	0.81	0.97	70	47	56.1
PA4344.102ANLT	1	42	1.03	1.2	45	32	48.5
PA4344.152ANLT	1.5	35	1.5	1.8	40	26	31.2
PA4344.182ANLT	1.8	32	1.7	2	34	23	30.9
PA4344.222ANLT	2.2	30	1.8	2.2	32	20	25.5
PA4344.332ANLT	3.3	28	2.7	3.3	29	16	18.1
PA4344.472ANLT	4.7	26	3.7	4.5	26	14	13.4
PA4344.682ANLT	6.8	22	6	7.2	22	11	10.2
PA4344.103ANLT	10	19	9.2	10.6	19	9	7.6
PA4344.153ANLT	15	14	12.8	15.5	14	7	7.4
PA4344.223ANLT	22	11.5	20.5	24	11.5	6	5.6
PA4344.333ANLT	33	10	32	37	10	5	4.4
PA4344.473ANLT	47	8.0	40	47	8.0	4	4.3
PA4344.683ANLT	68	6.5	66	76	7.2	4	
PA4344.823ANLT	82	5.7	69	83	6.5	3	2.6

# SMT Power Inductor

High Current Molded Power Inductor - PA4344.XXXANLT Series




**Notes:**

1. Actual temperature of the component during system operation (ambient plus temperature rise) must be within the standard operating range.
2. The saturation current is the current at which the initial inductance drops by approximately 30% at the stated ambient temperature. The maximum allowable drop at this stated current is 40% of the initial inductance. This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effect) to the component.
3. The rated current is the DC current required to raise the component temperature by approximately 40°C. Take note that the components' performance varies depending on the system condition. It is suggested that the component be tested at the system level, to verify the temperature rise of the component during system operation.
4. The part temperature (ambient+temp rise) should not exceed maximum operating temperature under worst case operating conditions. Circuit design, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
5. Please note that the inductance tolerance of all parts are ±20%, except those indicated by an \* which are +/- 30%.
6. Parts shown in bold are standard catalog parts and are available through sample stock and distribution. Parts in lighter font are available but are not necessarily held in sample stock or distribution and lead times may be longer. Please contact Pulse for availability.
7. The mechanical dimensions are 100% tested in production but do not necessarily meet a product capability index (Cpk) 1.33 and therefore may not strictly conform to PPAP.
8. Special Characteristics

## Mechanical

**PA4344.XXXANLT**



Series	A	B	C	D	E	F	G	H
PA4344.XXXANLT	17.8±0.5	16.9±0.3	6.7±0.3	(11.9)	(2.3)	(12.5)	(3.15)	(12.2)


All Dimensions in mm.

# SMT Power Inductor

High Current Molded Power Inductor - PA4344.XXXANLT Series












## TAPE & REEL INFO



## SURFACE MOUNTING TYPE, REEL/TAPE LIST








	REEL SIZE (mm)		TAPE SIZE (mm)			QTY
	A	G	P <sub>1</sub>	W	K <sub>0</sub>	PCS/REEL
PA4344.XXXANLT	Ø330	32.4	24	32	7.5	200

## Typical Performance Curves



# SMT Power Inductor


High Current Molded Power Inductor - PA4344.XXXANLT Series



# SMT Power Inductor

High Current Molded Power Inductor - PA4344.XXXANLT Series

## Core Loss



$$B_{p-p} = K * L(uH) * \Delta I(A)$$

### For More Information:

Americas - [prodinfo\\_power\\_americas@yageo.com](mailto:prodinfo_power_americas@yageo.com) | Europe - [prodinfo\\_power\\_emea@yageo.com](mailto:prodinfo_power_emea@yageo.com) | Asia - [prodinfo\\_power\\_asia@yageo.com](mailto:prodinfo_power_asia@yageo.com)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. Pulse Electronics, Inc. All rights reserved.

YAGEO Corporation and its affiliates do not recommend the use of commercial, automotive, and/or COTS grade products for high reliability applications or manned space flight.

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we strictly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.