

SM3-330G Datasheet



DiGi Electronics Part Number SM3-330G-DG

Manufacturer Gowanda Electronics

Manufacturer Product Number SM3-330G

Description MOLDED UNSHIELDED INDUCTOR

Detailed Description 330 nH Unshielded Molded Inductor 1.217 A 140mO

hm Max 1210 (3225 Metric)

https://www.DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.



Purchase and inquiry

Manufacturer Product Number:	Manufacturer:
SM3-330G	Gowanda Electronics
Series:	Product Status:
SM3	Active
Type:	Material - Core:
Molded	Iron Powder
Inductance:	Tolerance:
330 nH	±2%
Current Rating (Amps):	Current - Saturation (Isat):
1.217 A	
Shielding:	DC Resistance (DCR):
Unshielded	140mOhm Max
Q @ Freq:	Frequency - Self Resonant:
	400MHz
Ratings:	Operating Temperature:
	-55°C ~ 125°C
Inductance Frequency - Test:	Features:
10 MHz	
Mounting Type:	Package / Case:
Surface Mount	1210 (3225 Metric)
Supplier Device Package:	Size / Dimension:
1210	0.126" L x 0.098" W (3.20mm x 2.49mm)
Height - Seated (Max):	
0.102" (2.60mm)	

Environmental & Export classification

8504.50.8000

RoHS Status:	Moisture Sensitivity Level (MSL):
Not applicable	1 (Unlimited)
REACH Status:	ECCN:
REACH Unaffected	EAR99
HTSUS:	



OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we striciy control the quality of products and services. Welcome your RFQ to Email: Info@DiGi-Electronics.com

















Tel: +00 852-30501935