

SML32S-820M Datasheet



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	SML32S-820M-DG
Manufacturer	Gowanda Electronics
Manufacturer Product Number	SML32S-820M
Description	MOLDED SHIELDED INDUCTOR
Detailed Description	820 nH Shielded Molded Inductor 588 mA 600mOhm Max 1210 (3225 Metric)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

SML32S-820M

Series:

SML32S

Type:

Molded

Inductance:

820 nH

Current Rating (Amps):

588 mA

Shielding:

Shielded

Q @ Freq:

-

Ratings:

-

Inductance Frequency - Test:

25 MHz

Mounting Type:

Surface Mount

Supplier Device Package:

1210

Height - Seated (Max):

0.102" (2.60mm)

Manufacturer:

Gowanda Electronics

Product Status:

Active

Material - Core:

Iron Powder

Tolerance:

±20%

Current - Saturation (Isat):

-

DC Resistance (DCR):

600mOhm Max

Frequency - Self Resonant:

170MHz

Operating Temperature:

-55°C ~ 125°C

Features:

-

Package / Case:

1210 (3225 Metric)

Size / Dimension:

0.126" L x 0.098" W (3.20mm x 2.49mm)

Environmental & Export classification

RoHS Status:

Not applicable

REACH Status:

REACH Unaffected

HTSUS:

8504.50.8000

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.