

SMRF1812-561M Datasheet



DiGi Electronics Part Number SMRF1812-561M-DG

Manufacturer Gowanda Electronics

Manufacturer Product Number SMRF1812-561M

Description MOLDED UNSHIELDED INDUCTOR

Detailed Description 5.6 μH Unshielded Molded Inductor 427 mA 1.10hm

Max 1812 (4532 Metric)

https://www.DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.



Purchase and inquiry

| Manufacturer Product Number: | Manufacturer: |
|--|--|
| SMRF1812-561M | Gowanda Electronics |
| Series: | Product Status: |
| SMRF1812 | Active |
| Type: | Material - Core: |
| Molded | Ferrite |
| Inductance: | Tolerance: |
| 5.6 µH | ±20% |
| Current Rating (Amps): | Current - Saturation (Isat): |
| 427 mA | |
| Shielding: | DC Resistance (DCR): |
| Unshielded | 1.10hm Max |
| Q@Freq: | Frequency - Self Resonant: |
| 50 @ 7.9MHz | 33MHz |
| Ratings: | Operating Temperature: |
| | -55°C ~ 125°C |
| Inductance Frequency - Test: | Features: |
| 7.9 MHz | |
| Mounting Type: | Package / Case: |
| Surface Mount | 1812 (4532 Metric) |
| Supplier Device Package: | Size / Dimension: |
| 1812 | 0.175" L x 0.126" W (4.45mm x 3.20mm) |
| Height - Seated (Max): | |
| 0.138" (3.50mm) | |
| 7.9 MHz Mounting Type: Surface Mount Supplier Device Package: 1812 Height - Seated (Max): | Package / Case: 1812 (4532 Metric) Size / Dimension: |

Environmental & Export classification

| Moisture Sensitivity Level (MSL): | REACH Status: | |
|-----------------------------------|------------------|--|
| 1 (Unlimited) | REACH Unaffected | |
| ECCN: | HTSUS: | |
| EAR99 | 8504.50.8000 | |



OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we striciy control the quality of products and services. Welcome your RFQ to Email: Info@DiGi-Electronics.com

















Tel: +00 852-30501935