

RC2012F7151CS Datasheet



<https://www.DiGi-Electronics.com>

| | |
|------------------------------|---|
| DiGi Electronics Part Number | RC2012F7151CS-DG |
| Manufacturer | Samsung Electro-Mechanics |
| Manufacturer Product Number | RC2012F7151CS |
| Description | RES 7.15K OHM 1% 1/8W 0805 |
| Detailed Description | 7.15 kOhms \pm 1% 0.125W, 1/8W Chip Resistor 0805 (2012 Metric) Moisture Resistant Thick Film |

This model RC2012F7151CS is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

RC2012F7151CS

Series:

RC

Resistance:

7.15 kOhms

Power (Watts):

0.125W, 1/8W

Features:

Moisture Resistant

Operating Temperature:

-55°C ~ 155°C

Supplier Device Package:

0805

Height - Seated (Max):

0.026" (0.66mm)

Failure Rate:

-

Manufacturer:

Samsung Electro-Mechanics

Product Status:

Active

Tolerance:

±1%

Composition:

Thick Film

Temperature Coefficient:

±100ppm/°C

Package / Case:

0805 (2012 Metric)

Size / Dimension:

0.079" L x 0.049" W (2.00mm x 1.25mm)

Number of Terminations:

2

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8533.21.0030

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

Thick Film General Chip Resistors

- 0402(01005), 0603(0201), 1005(0402), 1608(0603), 2012(0805), 3216(1206), 3225(1210), 5025(2010), 6432(2512)

■ Features

- Small, thin and lightweight
- High reliability
- Applicable Both flow and reflow soldering.
- Suitable size and package for surface mount assembly
- RoHS Compliant.



■ Part Number System

| RC | |
|---------------|-------------------------------|
| Type (Series) | |
| RC | General purpose chip resistor |

| 0603 | |
|------------------|-------------------|
| Size : mm (inch) | |
| 0402 | 0.4×0.2mm (01005) |
| 0603 | 0.6×0.3mm (0201) |
| 1005 | 1.0×0.5mm (0402) |
| 1608 | 1.6×0.8mm (0603) |
| 2012 | 2.0×1.2mm (0805) |
| 3216 | 3.2×1.6mm (1206) |
| 3225 | 3.2×2.5mm (1210) |
| 5025 | 5.0×2.5mm (2010) |
| 6432 | 6.4×3.2mm (2512) |


| F | |
|-----------|-------|
| Tolerance | |
| D | ±0.5% |
| F | ±1.0% |
| G | ±2.0% |
| J | ±5.0% |

* Jumper : 'J'

| 2552 | |
|-------------------------------------|--|
| Resistance Value | |
| - 3-digit code System (E-24 series) | |
| - 4-digit code System (E-96 series) | |
| - Jumper : '000' | |
| - 2552 : 25.5KΩ | |

| CS | |
|--------------|----------|
| Packing Type | |
| CS | 7" reel |
| ES | 10" reel |
| AS | 13" reel |

■ Structure and Dimensions



[Unit : mm]


| Size(mil) | L | W | T | A | B | Unit Weight |
|---------------|-----------|-----------|-----------|-----------|-----------|-------------|
| RC0402(01005) | 0.40±0.02 | 0.20±0.02 | 0.13±0.02 | 0.10±0.03 | 0.10±0.03 | 0.04mg |
| RC0603(0201) | 0.60±0.03 | 0.30±0.03 | 0.23±0.03 | 0.10±0.05 | 0.15±0.05 | 0.15mg |
| RC1005(0402) | 1.00±0.05 | 0.50±0.05 | 0.35±0.05 | 0.20±0.10 | 0.25±0.10 | 0.6mg |
| RC1608(0603) | 1.60±0.10 | 0.80±0.10 | 0.45±0.10 | 0.30±0.20 | 0.35±0.10 | 2.1mg |
| RC2012(0805) | 2.00±0.20 | 1.25±0.15 | 0.55±0.10 | 0.40±0.20 | 0.35±0.20 | 4.9mg |
| RC3216(1206) | 3.20±0.20 | 1.60±0.15 | 0.55±0.10 | 0.45±0.20 | 0.40±0.20 | 9.5mg |
| RC3225(1210) | 3.20±0.20 | 2.55±0.20 | 0.55±0.10 | 0.45±0.20 | 0.40±0.20 | 16mg |
| RC5025(2010) | 5.00±0.20 | 2.50±0.20 | 0.55±0.10 | 0.60±0.20 | 0.60±0.20 | 26mg |
| RC6432(2512) | 6.30±0.20 | 3.20±0.20 | 0.55±0.10 | 0.60±0.20 | 0.60±0.20 | 41mg |

Applications and Ratings

| Type | Size (mil) | Rated Power [W] | Rated Voltage [V] | Max Working Voltage [V] | Tolerance [%] | Resistance Range [Ω] | T.C.R [ppm/°C] | Working Temp. [°C] | Moisture Level |
|--------|------------|-----------------|--|-------------------------|----------------|---------------------------------|---------------------------------|--------------------|----------------|
| RC0402 | 01005 | 1/32 | $\sqrt{P \times R}$ P : Rated Power(W) R : Resistance(Ω) | 15 | ±1(F) ±5(J) | 1 ~ 1M | 1~9.9Ω : ± 300 10~1MΩ ± 250 | -55~125 | Level 1 |
| RC0603 | 0201 | 1/20 | | 25 | | 1 ~ 10M | 1~9.9Ω : ±300 10~10MΩ : ±250 | | |
| RC1005 | 0402 | 1/16 | | 50 | 1 ~ 10M | 1~9.9Ω : ±300 10~10MΩ : ±100 | -55 ~ 155 | | |
| RC1608 | 0603 | 1/10 | | 50 | | | | | |
| RC2012 | 0805 | 1/8 | | 150 | | | | | |
| RC3216 | 1206 | 1/4 | | 200 | | | | | |
| RC3225 | 1210 | 1/3 | | 200 | | | | | |
| RC5025 | 2010 | 2/3 | | 200 | | | | | |
| RC6432 | 2512 | 1 | | 200 | | | | | |

• Please contact our sales representatives or engineers for other specifications

Power Derating Curve



Jumper Ratings

| Type | Rated Current [A] | Max Overload Current [A] | Resistance [Ω] | Working Temp.[°C] |
|-----------------------|-------------------|--------------------------|----------------|-------------------|
| 0402, 0603 | 0.5 | 1 | 0.05max | -55 ~ 125 |
| 1005, 1608 | 1 | 2 | | -55 ~ 155 |
| 2012 and bigger sizes | 2 | 4 | | |

Rated Voltage

$$V = \sqrt{P \times R}$$

E : Rated Voltage (V)
 P : Rated Power (W)
 R : Resistance Value (Ω)

■ Standard Soldering Pad Dimensions



[Unit : mm]

| Size(mil) | Reflow Soldering | | | |
|---------------|------------------|------|--------|------|
| | A | B | 2A + B | C |
| RC0402(01005) | 017 | 0.20 | 0.54 | 0.18 |
| RC0603(0201) | 0.37 | 0.28 | 1.02 | 0.29 |
| RC1005(0402) | 0.60 | 0.50 | 1.70 | 0.50 |
| RC1608(0603) | 0.80 | 0.80 | 2.40 | 0.80 |
| RC2012(0805) | 0.90 | 1.40 | 3.20 | 1.20 |
| RC3216(1206) | 1.30 | 1.80 | 4.40 | 1.50 |
| RC3225(1210) | 1.30 | 1.80 | 4.40 | 2.40 |
| RC5025(2010) | 1.40 | 3.30 | 6.10 | 2.40 |
| RC6432(2512) | 1.40 | 4.60 | 7.40 | 3.00 |

■ Performance Characteristics

| ITEM | Requirements Specification | Test Conditions (JIS C 5201-1) |
|----------------------------|----------------------------------|---|
| Resistance | Within the specified tolerance | JIS C 5201-1 4.5 |
| Temperature Characteristic | Within the specified T.C.R | JIS C 5201-1 4.8 +20°C → -55°C / +20°C → +125°C |
| Short time Overload | $\Delta R < \pm 1\% + 0.1\Omega$ | JIS C 5201-1 4.13 Rated Voltage × 2.5, 5sec |
| Solderability | Immersed over 95% | JIS C 5201-1 4.17 Rosin Ethanol (25%WT) 245+5/-0°C, 2±0.5 sec |
| Resistance to Solder Heat | $\Delta R < \pm 1\% + 0.1\Omega$ | JIS C 5201-1 4.18 260±5°C, 10±1 sec |
| Temperature Cycle | $\Delta R < \pm 1\% + 0.1\Omega$ | JIS C 5201-1 4.19 -55°C ↔ +125°C, 100 cycle |
| Moisture Resistance | $\Delta R < \pm 3\% + 0.1\Omega$ | JIS C 5201-1 4.24 40±2°C, 90~95%RH, 1,000 ⁺⁴⁸ hours 90mins ON, 30mins OFF |
| Load Life | $\Delta R < \pm 3\% + 0.1\Omega$ | JIS C 5201-1 4.25 Rated Voltage, 70±2°C, 1,000 ⁺⁴⁸ hours 90mins ON, 30mins OFF |
| High Temp. Exposure | $\Delta R < \pm 3\% + 0.1\Omega$ | JIS C 5201-1 4.25.3 155±2°C, 1,000 ⁺⁴⁸ hours |

※ The reliability test condition can be replaced by the corresponding accelerated test condition.

 Product specifications included in the specifications are effective as of March 01, 2015.

Please be advised that they are standard product specifications for reference only.

We may change, modify or discontinue the product specifications without notice at any time.

So, you need to approve the product specifications before placing an order.

Should you have any question regarding the product specifications,

please contact our sales personnel or application engineers.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.