

# HW-08-10-G-D-440-SM Datasheet



DiGi Electronics Part Number	HW-08-10-G-D-440-SM-DG
Manufacturer	<a href="#">Samtec Inc.</a>
Manufacturer Product Number	HW-08-10-G-D-440-SM
Description	CONN HDR 16POS 0.1 STACK SMD
Detailed Description	16 Position Header Spacer Connector 0.100" (2.54mm) Gold Surface Mount

<https://www.DiGi-Electronics.com>

This model HW-08-10-G-D-440-SM is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

HW-08-10-G-D-440-SM

Series:

Flex Stack, HW

Number of Positions:

16

Number of Rows:

2

Length - Overall Pin:

0.765" (19.431mm)

Length - Stack Height:

0.440" (11.176mm)

Mounting Type:

Surface Mount

Contact Finish - Post (Mating):

Gold

Color:

Black

Manufacturer:

Samtec Inc.

Product Status:

Active

Pitch:

0.100" (2.54mm)

Row Spacing:

0.100" (2.54mm)

Length - Post (Mating):

0.325" (8.255mm)

Length - Tail:

-

Termination:

Solder

Contact Finish Thickness - Post (Mating):

10.0µin (0.25µm)

Base Product Number:

HW-08-10

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

ECCN:

EAR99

Moisture Sensitivity Level (MSL):

Not Applicable


HTSUS:

8536.69.4040

# FLEX STACK

## FLEXIBLE .025" SQ BOARD STACKERS

(2.54 mm) .100" PITCH • HW SERIES



### HW

#### Board Mates:

SSW, SSQ, ESW, ESQ, CES, SLW, BSW, BCS, SSM, HLE, PHF

#### Cable Mates:

IDSS, IDSD

### SPECIFICATIONS

#### Insulator Material:

HW-SM Top = Natural LCP  
HW-SM Bottom = Black LCP  
HW-TH = Natural LCP

#### Terminal Material:

Phosphor Bronze

#### Plating:

Au or Sn over  
50 μm (1.27 μm) Ni

#### Operating Temp Range:

-55 °C to +125 °C with Gold  
-55 °C to +105 °C with Tin

### PROCESSING

#### Lead-Free Solderable:

Yes

#### SMT Lead Coplanarity:

(0.15 mm) .006" max\*  
\*(.004" stencil solution may be available; contact ipg@samtec.com)

### ALSO AVAILABLE MOQ Required

#### Other platings

Locking Clip available with double row HW-SM  
(Manual placement required)

#### Notes:

For added mechanical stability, Samtec recommends mechanical board spacers be used in applications with gold or selective gold plated connectors. Contact ipg@samtec.com for more information.

This Series is non-standard, non-returnable.

HW	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	STACKER HEIGHT	SM	OTHER OPTION
----	------------------	------------	----------------	------------	----------------	----	--------------

01 thru 50  
(Through-hole)

02 thru 36  
(Surface mount)

Specify LEAD STYLE from chart

**-F**  
= Gold flash on contact, Matte Tin on tail

**-L**  
= 10 μm (0.25 μm) Gold on contact area of longer tail, Matte Tin on tail

**-G**  
= 10 μm (0.25 μm) Gold on contact area of longer tail, Gold flash on balance

**-T**  
= Matte Tin

**-S**

= Single Row

**-D**

= Double Row

**-T**

= Triple Row (Through-hole only)

**-Q**

= Double Row .200"

(5.08 mm) row space (Through-hole only)

**-"XXX"**

= Stacker Height (in inches)

Through-hole = (5.08 mm) .200" Min.

Surface mount = (6.35 mm) .250" Min.

**SM**

Leave blank for Through-hole

**-"XXX"**

= HW-TH Tail Length (in inches)

(1.40 mm) .055" min.

Example: -250

= (6.35 mm) .250"

**-LL**

= Locking Lead (Through-hole only)

(Shortest dimension between the tail and the post is the end that will be crimped.

Available on tails from (2.29 mm) .090" to (7.87 mm) .310" only.)

Single row, 01 & 02 positions & -Q row not available

**-"XXX"**

= Polarized (Specify omitted pin position)

**-A**

= Alignment Pin (Metal or plastic at Samtec discretion) (Surface mount only)


**-TR**

= Tape & Reel (4-27 pins per row only) (Not Available on Lead Styles 10, 11, 12 & 20) (Surface mount only)


**-FR**

= Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (4-27 pins per row only) (Not Available on Lead Styles 10, 11, 12 & 20) (Surface mount only)


LEAD STYLE	OAL (TH)
-07	(10.92) .430
-08	(13.46) .530
-09	(18.54) .730
-10	(21.08) .830
-11	(23.62) .930
-12	(26.16) 1.030
-13	(31.24) 1.230
-14	(36.32) 1.430
-15	(16.00) .630
-16	(11.30) .445
-17	(12.19) .480
-19	(33.78) 1.330
-20	(28.70) 1.130




LEAD STYLE	OAL (SMT)
-08	(11.81) .465
-09	(16.89) .665
-10	(19.43) .765
-11	(21.97) .865
-12	(24.51) .965
-15	(14.35) .565
-16	(9.65) .380
-17	(10.54) .415
-20	(27.05) 1.065



**-S**




**-D**




**-T or -Q\***


-Q\* same as -T except middle row pins are removed




**HW-TH**



**-S**



**-D**



**HW-SM**

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.