


# BC846ALT3G Datasheet



<https://www.DiGi-Electronics.com>

|                              |  |
|------------------------------|--|
| DiGi Electronics Part Number | BC846ALT3G-DG  |
| Manufacturer                 | <a href="#">onsemi</a>   |
| Manufacturer Product Number  | BC846ALT3G   |
| Description                  | TRANS NPN 65V 0.1A SOT23-3   |
| Detailed Description         | Bipolar (BJT) Transistor NPN 65 V 100 mA 100MHz 300 mW Surface Mount SOT-23-3 (TO-236) |



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

BC846ALT3G

Series:

-

Transistor Type:

NPN

Voltage - Collector Emitter Breakdown (Max):

65 V

Current - Collector Cutoff (Max):

15nA (ICBO)

Power - Max:

300 mW

Operating Temperature:

-55°C ~ 150°C (TJ)

Package / Case:

TO-236-3, SC-59, SOT-23-3

Base Product Number:

BC846

Manufacturer:

onsemi

Product Status:

Active

Current - Collector (Ic) (Max):

100 mA

Vce Saturation (Max) @ Ib, Ic:

600mV @ 5mA, 100mA

DC Current Gain (hFE) (Min) @ Ic, Vce:

110 @ 2mA, 5V

Frequency - Transition:

100MHz

Mounting Type:

Surface Mount

Supplier Device Package:

SOT-23-3 (TO-236)

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8541.21.0075

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

# General Purpose Transistors

## NPN Silicon

### BC846ALT1G Series

#### Features

- Moisture Sensitivity Level: 1
- ESD Rating – Human Body Model: > 4000 V  
– Machine Model: > 400 V
- S and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

#### MAXIMUM RATINGS



| Rating   | Symbol    | Value             | Unit |
|--|-----------|-------------------|------|
| Collector-Emitter Voltage<br>BC846<br>BC847, BC850<br>BC848, BC849 | $V_{CEO}$ | 65<br>45<br>30    | Vdc  |
| Collector-Base Voltage<br>BC846<br>BC847, BC850<br>BC848, BC849    | $V_{CBO}$ | 80<br>50<br>30    | Vdc  |
| Emitter-Base Voltage<br>BC846<br>BC847, BC850<br>BC848, BC849      | $V_{EBO}$ | 6.0<br>6.0<br>5.0 | Vdc  |
| Collector Current – Continuous                                     | $I_C$     | 100               | mAdc |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

#### THERMAL CHARACTERISTICS


| Characteristic  | Symbol          | Max            | Unit                       |
|---|-----------------|----------------|----------------------------|
| Total Device Dissipation FR-5 Board,<br>(Note 1)<br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$       | $P_D$           | 225<br>1.8     | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance,<br>Junction-to-Ambient (Note 1)   | $R_{\theta JA}$ | 556            | $^\circ\text{C}/\text{W}$  |
| Total Device Dissipation<br>Alumina Substrate (Note 2)<br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 300<br>2.4     | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance,<br>Junction-to-Ambient (Note 2)   | $R_{\theta JA}$ | 417            | $^\circ\text{C}/\text{W}$  |
| Junction and Storage<br>Temperature Range   | $T_J, T_{stg}$  | -55 to<br>+150 | $^\circ\text{C}$           |

- FR-5 =  $1.0 \times 0.75 \times 0.062$  in.
- Alumina =  $0.4 \times 0.3 \times 0.024$  in 99.5% alumina.



**SOT-23**  
**CASE 318**  
**STYLE 6**

#### MARKING DIAGRAM



XX = Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or overbar may vary depending upon manufacturing location.

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 12 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 12.


**BC846ALT1G Series****ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

| Characteristic  | Symbol  | Min           | Typ               | Max               | Unit              |                     |
|---|---|---------------|-------------------|-------------------|-------------------|---------------------|
| <b>OFF CHARACTERISTICS</b>  |   |               |                   |                   |                   |                     |
| Collector – Emitter Breakdown Voltage<br>( $I_C = 10\text{ mA}$ )   | BC846A, B, C<br>BC847A, B, C, BC850B, C<br>BC848A, B, C, BC849B, C  | $V_{(BR)CEO}$ | 65<br>45<br>30    | –<br>–<br>–       | –<br>–<br>–       | V                   |
| Collector – Emitter Breakdown Voltage<br>( $I_C = 10\ \mu\text{A}$ , $V_{EB} = 0$ )   | BC846A, B, C<br>BC847A, B, C, BC850B, C<br>BC848A, B, C, BC849B, C  | $V_{(BR)CES}$ | 80<br>50<br>30    | –<br>–<br>–       | –<br>–<br>–       | V                   |
| Collector – Base Breakdown Voltage<br>( $I_C = 10\ \mu\text{A}$ )   | BC846A, B, C<br>BC847A, B, C, BC850B, C<br>BC848A, B, C, BC849B, C  | $V_{(BR)CBO}$ | 80<br>50<br>30    | –<br>–<br>–       | –<br>–<br>–       | V                   |
| Emitter – Base Breakdown Voltage<br>( $I_E = 1.0\ \mu\text{A}$ )  | BC846A, B, C<br>BC847A, B, C, BC850B, C<br>BC848A, B, C, BC849B, C  | $V_{(BR)EBO}$ | 6.0<br>6.0<br>5.0 | –<br>–<br>–       | –<br>–<br>–       | V                   |
| Collector Cutoff Current ( $V_{CB} = 30\text{ V}$ )<br>( $V_{CB} = 30\text{ V}$ , $T_A = 150^\circ\text{C}$ )                                       |   | $I_{CBO}$     | –<br>–            | –<br>–            | 15<br>5.0         | nA<br>$\mu\text{A}$ |
| <b>ON CHARACTERISTICS</b>   |   |               |                   |                   |                   |                     |
| DC Current Gain<br>( $I_C = 10\ \mu\text{A}$ , $V_{CE} = 5.0\text{ V}$ )  | BC846A, BC847A, BC848A<br>BC846B, BC847B, BC848B<br>BC846C, BC847C, BC848C                                    | $h_{FE}$      | –<br>–<br>–       | 90<br>150<br>270  | –<br>–<br>–       | –                   |
| ( $I_C = 2.0\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ )   | BC846A, BC847A, BC848A<br>BC846B, BC847B, BC848B,<br>BC849B, BC850B<br>BC846C, BC847C, BC848C, BC849C, BC850C |               | 110<br>200<br>420 | 180<br>290<br>520 | 220<br>450<br>800 |                     |
| Collector – Emitter Saturation Voltage ( $I_C = 10\text{ mA}$ , $I_B = 0.5\text{ mA}$ )<br>( $I_C = 100\text{ mA}$ , $I_B = 5.0\text{ mA}$ )        |   | $V_{CE(sat)}$ | –<br>–            | –<br>–            | 0.25<br>0.6       | V                   |
| Base – Emitter Saturation Voltage ( $I_C = 10\text{ mA}$ , $I_B = 0.5\text{ mA}$ )<br>( $I_C = 100\text{ mA}$ , $I_B = 5.0\text{ mA}$ )             |   | $V_{BE(sat)}$ | –<br>–            | 0.7<br>0.9        | –<br>–            | V                   |
| Base – Emitter Voltage ( $I_C = 2.0\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ )<br>( $I_C = 10\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ )                    |   | $V_{BE(on)}$  | 580<br>–          | 660<br>–          | 700<br>770        | mV                  |
| <b>SMALL-SIGNAL CHARACTERISTICS</b>   |   |               |                   |                   |                   |                     |
| Current – Gain – Bandwidth Product<br>( $I_C = 10\text{ mA}$ , $V_{CE} = 5.0\text{ Vdc}$ , $f = 100\text{ MHz}$ )                                   |   | $f_T$         | 100               | –                 | –                 | MHz                 |
| Output Capacitance ( $V_{CB} = 10\text{ V}$ , $f = 1.0\text{ MHz}$ )  |   | $C_{obo}$     | –                 | –                 | 4.5               | pF                  |
| Noise Figure ( $I_C = 0.2\text{ mA}$ ,<br>$V_{CE} = 5.0\text{ Vdc}$ , $R_S = 2.0\text{ k}\Omega$ ,<br>$f = 1.0\text{ kHz}$ , $BW = 200\text{ Hz}$ ) | BC846A,B,C, BC847A,B,C, BC848A,B,C<br>BC849B,C, BC850B,C  | NF            | –<br>–            | –<br>–            | 10<br>4.0         | dB                  |


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

**BC846ALT1G Series**


**BC846A, BC847A, BC848A, SBC846A**




**Figure 1. DC Current Gain vs. Collector Current**




**Figure 2. DC Current Gain vs. Collector Current**



**Figure 3. Collector Emitter Saturation Voltage vs. Collector Current**



**Figure 4. Base Emitter Saturation Voltage vs. Collector Current**



**Figure 5. Base Emitter Voltage vs. Collector Current**

## BC846ALT1G Series

BC846A, BC847A, BC848A, SBC846A




Figure 6. Collector Saturation Region




Figure 7. Base-Emitter Temperature Coefficient




Figure 8. Capacitances






Figure 9. Current-Gain - Bandwidth Product

# BC846ALT1G Series


## BC846B, SBC846B




**Figure 10. DC Current Gain vs. Collector Current**




**Figure 11. DC Current Gain vs. Collector Current**



**Figure 12. Collector Emitter Saturation Voltage vs. Collector Current**




**Figure 13. Base Emitter Saturation Voltage vs. Collector Current**




**Figure 14. Base Emitter Voltage vs. Collector Current**

**BC846ALT1G Series**


**BC846B, SBC846B**




**Figure 15. Collector Saturation Region**



**Figure 16. Base-Emitter Temperature Coefficient**



**Figure 17. Capacitance**




**Figure 18. Current-Gain - Bandwidth Product**




### BC846ALT1G Series


BC847B, BC848B, BC849B, BC850B, SBC847B, SBC848B




**Figure 19. DC Current Gain vs. Collector Current**




**Figure 20. DC Current Gain vs. Collector Current**



**Figure 21. Collector-Emitter Saturation Voltage vs. Collector Current**




**Figure 22. Base-Emitter Saturation Voltage vs. Collector Current**




**Figure 23. Base-Emitter Voltage vs. Collector Current**

**BC846ALT1G Series**


**BC847B, BC848B, BC849B, BC850B, SBC846B, SBC847B, SBC848B**




**Figure 24. Collector Saturation Region**



**Figure 25. Base-Emitter Temperature Coefficient**




**Figure 26. Capacitances**




**Figure 27. Current-Gain - Bandwidth Product**

**BC846ALT1G Series**


**BC846C, BC847C, BC848C, BC849C, BC850C, SBC847C**




**Figure 28. DC Current Gain vs. Collector Current**




**Figure 29. DC Current Gain vs. Collector Current**



**Figure 30. Collector Emitter Saturation Voltage vs. Collector Current**



**Figure 31. Base Emitter Saturation Voltage vs. Collector Current**



**Figure 32. Base Emitter Voltage vs. Collector Current**

### BC846ALT1G Series

BC846C, BC847C, BC848C, BC849C, BC850C, SBC847C




Figure 33. Collector Saturation Region




Figure 34. Base-Emitter Temperature Coefficient




Figure 35. Capacitances






Figure 36. Current-Gain - Bandwidth Product


**BC846ALT1G Series**



**Figure 37. Safe Operating Area for BC846A, BC846B, BC846C**



**Figure 38. Safe Operating Area for BC847A, BC847B, BC847C, BC850B, BC850C**



**Figure 39. Safe Operating Area for BC848A, BC848B, BC848C, BC849B, BC849C**

## BC846ALT1G Series

## ORDERING INFORMATION

| Device         | Marking              | Package             | Shipping <sup>†</sup> |                      |                      |                     |
|----------------|----------------------|---------------------|-----------------------|----------------------|----------------------|---------------------|
| BC846ALT1G     | 1A                   | SOT-23<br>(Pb-Free) | 3,000 / Tape & Reel   |                      |                      |                     |
| SBC846ALT1G*   |                      |                     |                       |                      |                      |                     |
| BC846ALT3G     |                      |                     |                       |                      |                      |                     |
| BC846BLT1G     | 1B                   |                     | SOT-23<br>(Pb-Free)   | 3,000 / Tape & Reel  |                      |                     |
| SBC846BLT1G*   |                      |                     |                       |                      |                      |                     |
| BC846BLT3G     |                      |                     |                       |                      |                      |                     |
| SBC846BLT3G*   | 10,000 / Tape & Reel |                     |                       |                      |                      |                     |
| BC846CLT1G     |                      |                     |                       | 3C                   | 3,000 / Tape & Reel  |                     |
| BC847ALT1G     |                      |                     |                       |                      |                      | 1E                  |
| BC847BLT1G     | 1F                   |                     |                       |                      |                      |                     |
| SBC847BLT1G*   |                      |                     |                       | 10,000 / Tape & Reel |                      |                     |
| BC847BLT3G     |                      |                     |                       |                      | 3,000 / Tape & Reel  |                     |
| NSVBC847BLT3G* | 10,000 / Tape & Reel |                     |                       |                      |                      |                     |
| BC847CLT1G     |                      |                     |                       | 1G                   |                      | 3,000 / Tape & Reel |
| SBC847CLT1G*   |                      |                     |                       |                      | 10,000 / Tape & Reel |                     |
| BC847CLT3G     | 3,000 / Tape & Reel  |                     |                       |                      |                      |                     |
| BC848ALT1G     |                      |                     |                       | 1J                   |                      | 3,000 / Tape & Reel |
| BC848BLT1G     |                      |                     |                       |                      | 1K                   |                     |
| SBC848BLT1G*   | 10,000 / Tape & Reel |                     |                       |                      |                      |                     |
| BC848BLT3G     |                      |                     |                       | 3,000 / Tape & Reel  |                      |                     |
| BC848CLT1G     |                      |                     |                       |                      | 1L                   | 3,000 / Tape & Reel |
| NSVBC848CLT1G* | 10,000 / Tape & Reel |                     |                       |                      |                      |                     |
| BC848CLT3G     |                      |                     |                       | 3,000 / Tape & Reel  |                      |                     |
| BC849BLT1G     |                      |                     |                       |                      | 2B                   | 3,000 / Tape & Reel |
| BC849CLT1G     | 2C                   |                     |                       |                      |                      |                     |
| BC850BLT1G     |                      |                     |                       | 2F                   |                      |                     |
| NSVBC850BLT1G* |                      |                     |                       |                      | 2G                   | 3,000 / Tape & Reel |
| BC850CLT1G     |                      |                     |                       |                      |                      |                     |
| NSVBC850CLT1G* |                      |                     |                       |                      |                      |                     |


## DISCONTINUED (Note 3)

|                |    |                     |                      |
|----------------|----|---------------------|----------------------|
| BC847ALT3G     | 1E | SOT-23<br>(Pb-Free) | 10,000 / Tape & Reel |
| NSVBC849BLT1G* | 2B |                     | 3,000 / Tape & Reel  |
| BC849BLT3G     |    |                     | 10,000 / Tape & Reel |
| BC849CLT3G     | 2C |                     | 10,000 / Tape & Reel |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*S and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.





3. **DISCONTINUED:** These devices are not recommended for new design. Please contact your **onsemi** representative for information. The most current information on these devices may be available on [www.onsemi.com](http://www.onsemi.com).



SCALE 4:1

**SOT-23 (TO-236) 2.90x1.30x1.00 1.90P**  
**CASE 318**  
**ISSUE AU**


DATE 14 AUG 2024



| MILLIMETERS |      |      |      |
|-------------|------|------|------|
| DIM         | MIN  | NOM  | MAX  |
| A           | 0.89 | 1.00 | 1.11 |
| A1          | 0.01 | 0.06 | 0.10 |
| b           | 0.37 | 0.44 | 0.50 |
| c           | 0.08 | 0.14 | 0.20 |
| D           | 2.80 | 2.90 | 3.04 |
| E           | 1.20 | 1.30 | 1.40 |
| e           | 1.78 | 1.90 | 2.04 |
| L           | 0.30 | 0.43 | 0.55 |
| L1          | 0.35 | 0.54 | 0.69 |
| HE          | 2.10 | 2.40 | 2.64 |
| T           | 0°   | ---  | 10°  |


- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
  2. CONTROLLING DIMENSIONS: MILLIMETERS.
  3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
  4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

**GENERIC MARKING DIAGRAM\***



- XXX = Specific Device Code
- M = Date Code
- = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.



\* For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**STYLES ON PAGE 2**

|                         |   |  |
|-------------------------|---|--|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42226B</b>                          | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-23 (TO-236) 2.90x1.30x1.00 1.90P</b> | <b>PAGE 1 OF 2</b>   |

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**SOT-23 (TO-236) 2.90x1.30x1.00 1.90P**  
**CASE 318**  
**ISSUE AU**

DATE 14 AUG 2024

STYLE 1 THRU 5:  
CANCELLED

STYLE 6:  
PIN 1. BASE  
2. EMITTER  
3. COLLECTOR

STYLE 7:  
PIN 1. EMITTER  
2. BASE  
3. COLLECTOR

STYLE 8:  
PIN 1. ANODE  
2. NO CONNECTION  
3. CATHODE

STYLE 9:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 10:  
PIN 1. DRAIN  
2. SOURCE  
3. GATE

STYLE 11:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE-ANODE

STYLE 12:  
PIN 1. CATHODE  
2. CATHODE  
3. ANODE

STYLE 13:  
PIN 1. SOURCE  
2. DRAIN  
3. GATE

STYLE 14:  
PIN 1. CATHODE  
2. GATE  
3. ANODE

STYLE 15:  
PIN 1. GATE  
2. CATHODE  
3. ANODE

STYLE 16:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE

STYLE 17:  
PIN 1. NO CONNECTION  
2. ANODE  
3. CATHODE

STYLE 18:  
PIN 1. NO CONNECTION  
2. CATHODE  
3. ANODE

STYLE 19:  
PIN 1. CATHODE  
2. ANODE  
3. CATHODE-ANODE

STYLE 20:  
PIN 1. CATHODE  
2. ANODE  
3. GATE

STYLE 21:  
PIN 1. GATE  
2. SOURCE  
3. DRAIN

STYLE 22:  
PIN 1. RETURN  
2. OUTPUT  
3. INPUT

STYLE 23:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 24:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE

STYLE 25:  
PIN 1. ANODE  
2. CATHODE  
3. GATE

STYLE 26:  
PIN 1. CATHODE  
2. ANODE  
3. NO CONNECTION

STYLE 27:  
PIN 1. CATHODE  
2. CATHODE  
3. CATHODE

STYLE 28:  
PIN 1. ANODE  
2. ANODE  
3. ANODE

|                         |   |   |
|-------------------------|---|---|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42226B</b>                          | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-23 (TO-236) 2.90x1.30x1.00 1.90P</b> | <b>PAGE 2 OF 2</b>  |

**onsemi** and **ONSEMI** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.



**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS:**

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

**ONLINE SUPPORT:** [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.