


PC401 Datasheet




<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	PC401-DG
Manufacturer	Sharp Microelectronics
Manufacturer Product Number	PC401
Description	OPTOISO 3.75KV OPEN COLL 5MFP
Detailed Description	Logic Output Optoisolator Open Collector 3750Vrms 1 Channel CMTI 5-MFP

This model PC401 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

PC401

Series:

OPIC™

Number of Channels:

1

Voltage - Isolation:

3750Vrms

Input Type:

DC

Current - Output / Channel:

50 mA

Propagation Delay tpLH / tpHL (Max):

3µs, 6µs

Voltage - Forward (Vf) (Typ):

1.1V

Voltage - Supply:

3V ~ 15V

Mounting Type:

Surface Mount

Supplier Device Package:

5-MFP

Manufacturer:

Sharp Microelectronics

Product Status:

Obsolete

Inputs - Side 1/Side 2:

1/0

Common Mode Transient Immunity (Min):

-

Output Type:

Open Collector

Data Rate:

-

Rise / Fall Time (Typ):

100ns, 50ns

Current - DC Forward (If) (Max):

50mA

Operating Temperature:

-25°C ~ 85°C

Package / Case:

6-SOIC (0.173", 4.40mm Width), 5 Leads

Environmental & Export classification

RoHS Status:

RoHS non-compliant

ECCN:

EAR99

Moisture Sensitivity Level (MSL):

1 (Unlimited)

HTSUS:

8541.49.8000

PC401

Compact, Surface Mount Type OPIC Photocoupler

■ Features

1. Mini-flat package
2. "High" output during light emission
3. Isolation voltage between input and output
($V_{iso} : 3\,750V_{rms}$)
4. TTL and LSTTL compatible output
5. Recognized by UL(No.64380)

■ Applications

1. Hybrid substrate which requires high density mounting
2. Personal computers, office computers and peripheral equipment
3. Electronic musical instruments

■ Package Specifications

Model No.	Package specifications	Diameter of reel	Tape width
PC401	Taping package (Net : 3 000pcs.)	370mm	12mm
PC401T	Taping package (Net : 750pcs.)	178mm	12mm
PC401Z	Sleeve package (Net : 100pcs.)	-	-

■ Absolute Maximum Ratings

($T_a = 25^\circ C$)


Parameter		Symbol	Rating	Unit
Input	Forward current	I_F	50	mA
	Reverse voltage	V_R	6	V
	Power dissipation	P	70	mW
Output	Supply voltage	V_{CC}	16	V
	High level output voltage	V_{OH}	16	V
	Low level output current	I_{OL}	50	mA
	Power dissipation	P_O	130	mW
Total power dissipation		P_{tot}	150	mW
*1	Isolation voltage	V_{iso}	3 750	V_{rms}
Operating temperature		T_{opr}	- 25 to + 85	$^\circ C$
Storage temperature		T_{stg}	- 40 to + 125	$^\circ C$
*2	Soldering temperature	T_{sol}	260	$^\circ C$

*1 AC for 1 minute, 40 to 60% RH

*2 For 10 seconds


■ Outline Dimensions

(Unit : mm)



* "OPIC" (Optical IC) is a trademark of the SHARP Corporation.

An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip.



■ Electro-optical Characteristics

(Ta = 0 to + 70°C unless otherwise specified.)

Parameter		Symbol	Conditions	MIN.	TYP.	MAX.	Unit	
Input	Forward voltage	V _F	I _F = 4mA	-	1.1	1.4	V	
			I _F = 0.3mA	0.7	1.0	-		
	Reverse current	I _R	Ta = 25°C, V _R = 3V	-	-	10	μA	
	Terminal capacitance	C _t	Ta = 25°C, V = 0, f = 1kHz	-	30	250	pF	
Output	Operating supply voltage	V _{CC}		3	-	15	V	
	Low level output voltage	V _{OL}	I _F = 0, V _{CC} = 5V, I _{OL} = 16mA	-	0.2	0.4	V	
	High level output current	I _{OH}	I _F = 4mA, V _{CC} = V _O = 15V	-	-	100	μA	
	Low level supply current	I _{CCL}	I _F = 0, V _{CC} = 5V	-	2.5	5.0	mA	
	High level supply current	I _{CCH}	I _F = 4mA, V _{CC} = 5V	-	2.7	5.5	mA	
Transfer characteristics	*3 "H→L" threshold input current	I _{FHL}	Ta = 25°C, V _{CC} = 5V, R _L = 280Ω	0.4	0.8	-	mA	
			V _{CC} = 5V, R _L = 280Ω	0.3	-	-		
	*4 "L→H" threshold input current	I _{FLH}	Ta = 25°C, V _{CC} = 5V, R _L = 280Ω	-	1.1	2.0	mA	
			V _{CC} = 5V, R _L = 280Ω	-	-	4.0		
	*5 Hysteresis		I _{FHL} / I _{FLH}	V _{CC} = 5V, R _L = 280Ω	0.5	0.7	0.9	
	Isolation resistance		R _{ISO}	Ta = 25°C, DC500V, 40 to 60% RH	5 x 10 ¹⁰	10 ¹¹	-	Ω
*6 Response time	"H→L" propagation delay time	t _{PHL}	Ta = 25°C, V _{CC} = 5V R _L = 280Ω, I _F = 4mA	-	2	6	μs	
	"L→H" propagation delay time	t _{PLH}		-	1	3		
	Fall time	t _f		-	0.05	0.5		
	Rise time	t _r		-	0.1	0.5		

*3 I_{FHL} represents forward current when output gese from high to low.

*4 I_{FLH} represents forward current when output goes from low to high.

*5 Hysteresis stands for I_{FHL} / I_{FLH}.

*6 Test circuit for response time is shown below.

Test Circuit for Response Time





Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Power Dissipation vs. Ambient Temperature




Fig. 3 Forward Current vs. Forward Voltage




Fig. 4 Relative Threshold Input Current vs. Supply Voltage




Fig. 5 Relative Threshold Input Current vs. Ambient Temperature




Fig. 6 Low Level Output Voltage vs. Low Level Output Current




Fig. 7 Low Level Output Voltage vs. Ambient Temperature




Fig. 8 High Level Output Current vs. Forward Current




Fig. 9 High Level Output Current vs. Ambient Temperature




Fig.10 Supply Current vs. Supply Voltage




Fig.11 Propagation Delay Time vs. Forward Current





Fig.12 Rise Time, Fall Time vs. Load Resistance



■ Preautions for Use

- (1) It is recommended that a by-pass capacitor of more than $0.01\mu F$ is added between V_{cc} and GND near the device in order to stabilize power supply line.
- (2) Handle this product the same as with other integrated circuits against static electricity.
- (3) As for other general cautions, refer to the chapter "Preautions for Use"

NOTICE

- The circuit application examples in this publication are provided to explain representative applications of SHARP devices and are not intended to guarantee any circuit design or license any intellectual property rights. SHARP takes no responsibility for any problems related to any intellectual property right of a third party resulting from the use of SHARP's devices.
- Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device. SHARP reserves the right to make changes in the specifications, characteristics, data, materials, structure, and other contents described herein at any time without notice in order to improve design or reliability. Manufacturing locations are also subject to change without notice.
- Observe the following points when using any devices in this publication. SHARP takes no responsibility for damage caused by improper use of the devices which does not meet the conditions and absolute maximum ratings to be used specified in the relevant specification sheet nor meet the following conditions:
 - (i) The devices in this publication are designed for use in general electronic equipment designs such as:
 - Personal computers
 - Office automation equipment
 - Telecommunication equipment [terminal]
 - Test and measurement equipment
 - Industrial control
 - Audio visual equipment
 - Consumer electronics
 - (ii) Measures such as fail-safe function and redundant design should be taken to ensure reliability and safety when SHARP devices are used for or in connection with equipment that requires higher reliability such as:
 - Transportation control and safety equipment (i.e., aircraft, trains, automobiles, etc.)
 - Traffic signals
 - Gas leakage sensor breakers
 - Alarm equipment
 - Various safety devices, etc.
 - (iii) SHARP devices shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as:
 - Space applications
 - Telecommunication equipment [trunk lines]
 - Nuclear power control equipment
 - Medical and other life support equipment (e.g., scuba).
- Contact a SHARP representative in advance when intending to use SHARP devices for any "specific" applications other than those recommended by SHARP or when it is unclear which category mentioned above controls the intended use.
- If the SHARP devices listed in this publication fall within the scope of strategic products described in the Foreign Exchange and Foreign Trade Control Law of Japan, it is necessary to obtain approval to export such SHARP devices.
- This publication is the proprietary product of SHARP and is copyrighted, with all rights reserved. Under the copyright laws, no part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, in whole or in part, without the express written permission of SHARP. Express written permission is also required before any use of this publication may be made by a third party.
- Contact and consult with a SHARP representative if there are any questions about the contents of this publication.

