


RMCS1206FT2K00 Datasheet



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	RMCS1206FT2K00-DG
Manufacturer	Stackpole Electronics Inc
Manufacturer Product Number	RMCS1206FT2K00
Description	RES 2K OHM 1% 1/4W 1206
Detailed Description	2 kOhms \pm 1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Anti-Sulfur Thick Film

This model RMCS1206FT2K00 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

RMCS1206FT2K00

Series:

RMCS

Resistance:

2 kOhms

Power (Watts):

0.25W, 1/4W

Features:

Anti-Sulfur

Operating Temperature:

-55°C ~ 155°C

Supplier Device Package:

1206

Height - Seated (Max):

0.026" (0.65mm)

Failure Rate:

-

Manufacturer:

Stackpole Electronics Inc

Product Status:

Active

Tolerance:

±1%

Composition:

Thick Film

Temperature Coefficient:

±100ppm/°C

Package / Case:

1206 (3216 Metric)

Size / Dimension:

0.122" L x 0.061" W (3.10mm x 1.55mm)

Number of Terminations:

2

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8533.21.0030

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

RMCS Series

Sulfur Resistant Thick Film Chip Resistor

Stackpole Electronics, Inc.
Resistive Product Solutions

Features:

- Inner terminations engineered to deter sulfur contamination
- Non-standard resistance values available
- Zero ohm available (max. resistance 0.05Ω)
- “-HP” denotes high power
- RoHS compliant, REACH compliant, and halogen free



Electrical Specifications								
Type/Code	Power Rating (W) @ 70°C	Maximum Working Voltage (V) ⁽¹⁾	Maximum Overload Voltage (V) ⁽²⁾	Maximum Current Jumper (A)	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance		
						0.5%	1%	5%
RMCS0201	0.05	25	50	1	±200	-	1 - 10M	
RMCS0402	0.063	50	100	1	±200	1 - 9.76		
					±100	10 - 1M		
					±200	1.02M - 10M		
RMCS0603	0.1	75	150	1	±200	1 - 9.76		
					±100	10 - 1M		
					±200	1.02M - 10M		
RMCS0805	0.125	150	300	2	±200	1 - 9.76		
					±100	10 - 1M		
					±200	1.02M - 10M		
RMCS1206	0.25	200	400	2	±200	1 - 9.76		
					±100	10 - 1M		
					±200	1.02M - 10M		
RMCS1210	0.33	200	400	2.5	±200	1 - 9.76		
					±100	10 - 1M		
					±200	1.02M - 10M		
RMCS2010	0.75	200	400	3.5	±200	1 - 9.76		
					±100	10 - 1M		
					±200	1.02M - 10M		
RMCS2512	1	250	500	4	±200	1 - 9.76		
					±100	10 - 1M		
					±200	1.02M - 10M		

(1) Lesser of $\sqrt{P \cdot R}$ or maximum working voltage, whichever is lower.

(2) $2.5 \cdot \sqrt{P \cdot R}$ or Max. Overload Voltage listed above, whichever is lower.

Electrical Specifications – High Power							
Type/Code	Power Rating (W) @ 70°C	Maximum Working Voltage (V) ⁽¹⁾	Maximum Overload Voltage (V) ⁽²⁾	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance		
					0.5% ⁽³⁾	1%, 5%	
RMCS0201-HP	0.083	25	50	±200	-	10 - 1M	
RMCS0402-HP	0.1	50	100	±200	-	1 - 9.76	
				±100	10 - 1M	10 - 1M	
RMCS0603-HP	0.25	75	150	±200	-	1 - 9.76	
				±100	10 - 1M	10 - 1M	
RMCS0805-HP	0.33	150	300	±200	-	1 - 9.76	
				±100	10 - 1M	10 - 1M	
RMCS1206-HP	0.5	200	400	±200	-	1 - 9.76	
				±100	10 - 1M	10 - 1M	
RMCS1210-HP	0.75	200	400	±200	-	1 - 9.76	
				±100	10 - 1M	10 - 1M	
RMCS2010-HP	1	200	400	±200	-	1 - 9.76	
				±100	10 - 1M	10 - 1M	
RMCS2512-HP	2	200	400	±400	-	1 - 9.76	
				±100	10 - 1M	10 - 10M	

(1) Lesser of $\sqrt{P \cdot R}$ or maximum working voltage, whichever is lower.

(2) $2.5 \cdot \sqrt{P \cdot R}$ or Max. Overload Voltage listed above, whichever is lower.

(3) 0.5% tolerance for 0603 and 0805 requires lower power rating. Contact Stackpole for details.

Mechanical Specifications



Type/Code	Typical Unit Wt. (mg)	L Body Length	W Body Width	H Body Height	a Top Termination	b Bottom Termination	Unit
RMCS0201	0.15	0.024 ± 0.001 0.60 ± 0.03	0.012 ± 0.001 0.30 ± 0.03	0.009 ± 0.001 0.23 ± 0.03	0.006 ± 0.002 0.15 ± 0.05	0.006 ± 0.002 0.15 ± 0.05	inches mm
RMCS0402	0.62	0.039 ± 0.006 1.00 ± 0.15	0.020 ± 0.002 0.50 ± 0.05	0.014 ± 0.004 0.35 ± 0.10	0.008 ± 0.006 0.20 ± 0.15	0.008 ± 0.006 0.20 ± 0.15	inches mm
RMCS0603	2.0	0.063 ± 0.008 1.60 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.018 ± 0.006 0.45 ± 0.15	0.012 ± 0.008 0.30 ± 0.20	0.012 ± 0.008 0.30 ± 0.20	inches mm
RMCS0805	4.4	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.006 1.25 ± 0.15	0.020 ± 0.006 0.50 ± 0.15	0.014 ± 0.008 0.35 ± 0.20	0.016 ± 0.008 0.40 ± 0.20	inches mm
RMCS1206	8.9	0.122 ± 0.006 3.10 ± 0.15	0.061 ± 0.010 1.55 ± 0.25	0.022 ± 0.006 0.55 ± 0.15	0.020 ± 0.012 0.50 ± 0.30	0.020 ± 0.008 0.50 ± 0.20	inches mm
RMCS1210	16.0	0.122 ± 0.006 3.10 ± 0.15	0.102 ± 0.012 2.60 ± 0.30	0.022 ± 0.006 0.55 ± 0.15	0.020 ± 0.010 0.50 ± 0.25	0.020 ± 0.008 0.50 ± 0.20	inches mm
RMCS2010	24.2	0.197 ± 0.008 5.00 ± 0.20	0.098 ± 0.008 2.50 ± 0.20	0.022 ± 0.004 0.55 ± 0.10	0.024 ± 0.010 0.60 ± 0.25	0.020 ± 0.012 0.50 ± 0.30	inches mm
RMCS2512	39.4	0.248 ± 0.008 6.30 ± 0.20	0.124 ± 0.008 3.15 ± 0.20	0.022 ± 0.006 0.55 ± 0.15	0.024 ± 0.010 0.60 ± 0.25	0.022 ± 0.010 0.55 ± 0.25	inches mm
RMCS2512-HP	39.4	0.248 ± 0.008 6.30 ± 0.20	0.126 ± 0.008 3.20 ± 0.20	0.024 ± 0.008 0.60 ± 0.20	0.024 ± 0.012 0.60 ± 0.30	0.024 ± 0.012 0.60 ± 0.30	inches mm

Performance Characteristics

Test	Test Method	Test Specification			Test Condition
		±1% and below	±5%	Jumper	
Short Time Overload	JIS-C-5201-1 4.13 IEC-60115-1 4.13	± (1% + 0.05Ω)	± (2% + 0.05Ω)	< 50mΩ	RCWV*2.5 or Max. Overload Voltage whichever is lower for 5 seconds, 2 seconds for high power series.
Insulation Resistance	JIS-C-5201-1 4.6 IEC-60115-1 4.6	≥10G			Max. Overload Voltage for 1 minute
Endurance	JIS-C-5201-1 4.25 IEC-60115-1 4.25.1	± (2% + 0.1Ω)	± (3% + 0.1Ω)	< 100mΩ	70 ± 2°C, RCWV for 1000 hours with 1.5 hours "ON" and 0.5 hour "OFF"
Damp Heat with Load	JIS-C-5201-1 4.24 IEC-60115-1 4.24	± (2% + 0.1Ω)	± (3% + 0.1Ω)	< 100mΩ	40 ± 2°C, 90~95% R.H., RCWV for 1000 hours with 1.5 hours "ON" and 0.5 hour "OFF"
Dry Heat	JIS-C-5201-1 4.23 IEC-60115-1 4.23.2	± (1% + 0.05Ω)	± (1.5% + 0.1Ω)	< 50mΩ	At +125/+155°C for 1000 hours
Bending Strength	JIS-C-5201-1 4.33 IEC-60115-1 4.33	± (1% + 0.05Ω)	± (1% + 0.05Ω)	< 50mΩ	Bending once for 5 seconds 2010, 2512 sizes: 2 mm / Other sizes: 3 mm
Solderability	JIS-C-5201-1 4.17 IEC-60115-1 4.17	95% minimum coverage			245 ± 5°C for 3 seconds
Resistance to Soldering Heat	JIS-C-5201-1 4.18 IEC-60115-1 4.18	± (0.5% + 0.05Ω)	± (1% + 0.05Ω)	< 50mΩ	260 ± 5°C for 10 seconds
Voltage Proof	JIS-C-5201-1 4.7 IEC-60115-1 4.7	No breakdown or flashover			1.42 times Max. Operating Voltage for 1 minute
Leaching	JIS-C-5201-1 4.18 IEC-60068-2-58 8.2.1	Individual leaching area ≤ 5% Total leaching area ≤ 10%			260 ± 5°C for 30 seconds
Rapid change of Temperature	JIS-C-5201-1 4.19 IEC-60115-1 4.19	± (0.5% + 0.05Ω)	± (1% + 0.05Ω)	< 50mΩ	-55 to +125°C/+155°C, 5 cycles
Sulfur Test	ASTM-B-809-95	± (0.5% + 0.05Ω)	± (0.5% + 0.05Ω)	< 50mΩ	H2S, 50 ± 2°C, 91~93% R.H., no power rating for 1000 hours

RCWV (Rated Continuous Working Voltage) = √(P*R) or Max. Operating Voltage, whichever is lower.

Recommended storage temperature: 15 ~ 28°C. Humidity < 80% R.H.

Operating temperature range is -55 to +155°C

RMCS Series
Sulfur Resistant Thick Film Chip Resistor

Stackpole Electronics, Inc.
Resistive Product Solutions

Power Derating Curve:



Packaging Specifications – Paper Tape



Type/Code	L	M	W	E	F	Unit
RMCS0201	0.015 ± 0.002	0.027 ± 0.002	0.315 ± 0.008	0.069 ± 0.004	0.138 ± 0.002	inches
	0.38 ± 0.05	0.68 ± 0.05	8.00 ± 0.20	1.75 ± 0.10	3.50 ± 0.05	mm
RMCS0402	0.026 ± 0.006	0.045 ± 0.006	0.315 ± 0.008	0.069 ± 0.004	0.138 ± 0.002	inches
	0.65 ± 0.15	1.15 ± 0.15	8.00 ± 0.20	1.75 ± 0.10	3.50 ± 0.05	mm
RMCS0603	0.043 ± 0.010	0.075 ± 0.010	0.315 ± 0.008	0.069 ± 0.004	0.138 ± 0.002	inches
	1.10 ± 0.25	1.90 ± 0.25	8.00 ± 0.20	1.75 ± 0.10	3.50 ± 0.05	mm
RMCS0805	0.063 ± 0.010	0.094 ± 0.010	0.315 ± 0.008	0.069 ± 0.004	0.138 ± 0.002	inches
	1.60 ± 0.25	2.40 ± 0.25	8.00 ± 0.20	1.75 ± 0.10	3.50 ± 0.05	mm
RMCS1206	0.075 ± 0.008	0.138 ± 0.008	0.315 ± 0.008	0.069 ± 0.004	0.138 ± 0.002	inches
	1.90 ± 0.20	3.50 ± 0.20	8.00 ± 0.20	1.75 ± 0.10	3.50 ± 0.05	mm
RMCS1210	0.110 ± 0.010	0.138 ± 0.008	0.315 ± 0.008	0.069 ± 0.004	0.138 ± 0.002	inches
	2.80 ± 0.25	3.50 ± 0.20	8.00 ± 0.20	1.75 ± 0.10	3.50 ± 0.05	mm
Type/Code	P ₀	P ₁	P ₂	ØD ₀	K1	Unit
RMCS0201	0.157 ± 0.004	0.079 ± 0.002	0.079 ± 0.002	0.059 +0.004 / -0	0.017 ± 0.008	inches
	4.00 ± 0.10	2.00 ± 0.05	2.00 ± 0.05	1.50 +0.10 / -0	0.42 ± 0.20	mm
RMCS0402	0.157 ± 0.004	0.079 ± 0.002	0.079 ± 0.002	0.059 +0.004 / -0	0.018 ± 0.008	inches
	4.00 ± 0.10	2.00 ± 0.05	2.00 ± 0.05	1.50 +0.10 / -0	0.45 ± 0.20	mm
RMCS0603	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.059 +0.004 / -0	0.028 ± 0.008	inches
	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 +0.10 / -0	0.70 ± 0.20	mm
RMCS0805	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.059 +0.004 / -0	0.033 ± 0.008	inches
	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 +0.10 / -0	0.85 ± 0.20	mm
RMCS1206	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.059 +0.004 / -0	0.033 ± 0.008	inches
	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 +0.10 / -0	0.85 ± 0.20	mm
RMCS1210	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.059 +0.004 / -0	0.030 ± 0.008	inches
	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 +0.10 / -0	0.75 ± 0.20	mm

RMCS Series
Sulfur Resistant Thick Film Chip Resistor

Stackpole Electronics, Inc.
Resistive Product Solutions

Packaging Specifications – Plastic Tape



Type/Code	L	M	W	E	F	Unit
RMCS2010	0.110 ± 0.008	0.217 ± 0.008	0.472 ± 0.012	0.069 ± 0.004	0.217 ± 0.002	inches
	2.80 ± 0.20	5.50 ± 0.20	12.00 ± 0.30	1.75 ± 0.10	5.50 ± 0.05	mm
RMCS2512	0.138 ± 0.008	0.264 ± 0.008	0.472 ± 0.012	0.069 ± 0.004	0.217 ± 0.002	inches
	3.50 ± 0.20	6.70 ± 0.20	12.00 ± 0.30	1.75 ± 0.10	5.50 ± 0.05	mm
Type/Code	P0	P1	P2	ØD0	K2	Unit
RMCS2010	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.059 +0.004 / -0	0.047 - 0	inches
	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 +0.10 / -0	1.20 - 0	mm
RMCS2512	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.002	0.059 +0.004 / -0	0.047 - 0	inches
	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.50 +0.10 / -0	1.20 - 0	mm

Recommended Pad Layout



Type/Code	a	b	c	Unit
RMCS0201	0.012	0.010	0.012	inches
	0.30	0.25	0.30	mm
RMCS0402	0.024	0.020	0.028	inches
	0.60	0.50	0.70	mm
RMCS0603	0.035	0.031	0.039	inches
	0.90	0.80	1.00	mm
RMCS0805	0.051	0.031	0.055	inches
	1.30	0.80	1.40	mm
RMCS1206	0.087	0.039	0.067	inches
	2.20	1.00	1.70	mm
RMCS1210	0.079	0.035	0.110	inches
	2.00	0.90	2.80	mm
RMCS2010	0.150	0.035	0.110	inches
	3.80	0.90	2.80	mm
RMCS2512	0.193	0.063	0.138	inches
	4.90	1.60	3.50	mm

Recommended Solder Profile

This information is intended as a reference for solder profiles for Stackpole resistive components. These profiles should be compatible with most soldering processes. These are only recommendations. Actual numbers will depend on board density, geometry, packages used, etc., especially those cells labeled with “*”.

100% Matte Tin / RoHS Compliant Terminations

Soldering iron recommended temperatures: 330 to 350°C with minimum duration.
Maximum number of reflow cycles: 3.

Wave Soldering			
Description	Maximum	Recommended	Minimum
Preheat Time	80 seconds	70 seconds	60 seconds
Temperature Diff.	140°C	120°C	100°C
Solder Temp.	260°C	250°C	240°C
Dwell Time at Max.	10 seconds	5 seconds	*
Ramp DN (°C/sec)	N/A	N/A	N/A

Temperature Diff. = Difference between final preheat stage and soldering stage.

Convection IR Reflow			
Description	Maximum	Recommended	Minimum
Ramp Up (°C/sec)	3°C/sec	2°C/sec	*
Dwell Time > 217°C	150 seconds	90 seconds	60 seconds
Solder Temp.	260°C	245°C	*
Dwell Time at Max.	30 seconds	15 seconds	10 seconds
Ramp DN (°C/sec)	6°C/sec	3°C/sec	*



Part Marking Instructions


E96 and E24 Values for 0805-2512 (1% tolerances)

The nominal resistance is marked on the surface of the overcoating with the use of **four character markings**.

1. Values <100Ω will use "R" as the decimal holder.



1.21Ω



100Ω

E24 Values for 0805-2512 (5% tolerance)

The nominal resistance is marked on the surface of the overcoating with the use of **three character markings**.

1. Values between 1Ω and 9.1Ω will use "R" as the decimal holder.



1Ω



1.2 KΩ

E24 Values for 0603 (5% tolerance)

The nominal resistance is marked on the surface of the overcoating with the use of **three character markings**.

1. Values between 1Ω and 9.1Ω will use "R" as the decimal holder.
2. Values ≥10Ω will use no decimal holder.



6.8Ω



10Ω

E96 Values for 0603 size (1% tolerances)

A two character number is assigned to each standard R-Value (E96) as shown in the chart below. This is followed by one alpha character which is used as a multiplier.

Each letter from "Y" - "F" represents a specific multiplier.



10.5Ω

Alpha Character = Multiplier	
Y = 0.1	C = 1000
X = 1	D = 10000
A = 10	E = 100000
B = 100	F = 1000000

Chip Marking	Value
01B =	10.0 x 100 = 1 KΩ
25C =	17.8 x 1000 = 17.8 KΩ
93D =	90.9 x 10000 = 909 KΩ

E96											
#	R-Value	#	R-Value	#	R-Value	#	R-Value	#	R-Value	#	R-Value
01	10.0	17	14.7	33	21.5	49	31.6	65	46.4	81	68.1
02	10.2	18	15.0	34	22.1	50	32.4	66	47.5	82	69.8
03	10.5	19	15.4	35	22.6	51	33.2	67	48.7	83	71.5
04	10.7	20	15.8	36	23.2	52	34.0	68	49.9	84	73.2
05	11.0	21	16.2	37	23.7	53	34.8	69	51.1	85	75.0
06	11.3	22	16.5	38	24.3	54	35.7	70	52.3	86	76.8
07	11.5	23	16.9	39	24.9	55	36.5	71	53.6	87	78.7
08	11.8	24	17.4	40	25.5	56	37.4	72	54.9	88	80.6
09	12.1	25	17.8	41	26.1	57	38.3	73	56.2	89	82.5
10	12.4	26	18.2	42	26.7	58	39.2	74	57.6	90	84.5
11	12.7	27	18.7	43	27.4	59	40.2	75	59.0	91	86.6
12	13.0	28	19.1	44	28.0	60	41.2	76	60.4	92	88.7
13	13.3	29	19.6	45	28.7	61	42.2	77	61.9	93	90.9
14	13.7	30	20.0	46	29.4	62	43.2	78	63.4	94	93.1
15	14.0	31	20.5	47	30.1	63	44.2	79	64.9	95	95.3
16	14.3	32	21.0	48	30.9	64	45.3	80	66.5	96	97.6

Note: 0201, and 0402 sizes are unmarked.

RMCS Series

Sulfur Resistant Thick Film Chip Resistor

Stackpole Electronics, Inc.
Resistive Product Solutions

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union’s directive regarding “Restrictions on Hazardous Substances” (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status						
Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
RMCS	Sulfur Resistant Thick Film Chip Resistor	SMD	YES(1)	100% Matte Sn over Ni	Always	Always

Note (1): RoHS Compliant by means of exemption 7c-l.

“Conflict Metals” Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the “conflict region” of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to “REACH”

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, “The Registration, Evaluation, Authorization and Restriction of Chemicals”, otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy

It is the policy of Stackpole Electronics, Inc. (SEI) to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

How to Order

R	M	C	S	0	6	0	3	J	T	4	K	7	0	-	H	P
----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

Product Series	Size	Power Rating (W)		Tolerance			Packaging				Resistance Value	Special	
		RMCS	-HP	Code	Tol	Value	Code	Description	Size	Quantity		Code	Description
RMCS Sulfur Resistant	0201	0.05	0.083	D	0.5%	E96	T	7" Reel Paper Tape	0201, 0402	10000	Four characters with the multiplier used as the decimal holder. 1 ohm = 1R00 100 Kohm = 100K 1.02 Mohm = 1M02 Zero ohm jumper = 0R00	blank	Standard
	0402	0.063	0.1	F	1%	E96, E24			0603, 0805	5000		-HP	High Power
	0603	0.1	0.25	J	5%	E24		1206, 1210					
	0805	0.125	0.33	Z	Jumper			2010, 2512	4000				
	1206	0.25	0.5										
	1210	0.33	0.75										
	2010	0.75	1										
	2512	1	2										

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we strictly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.