

RSF3JB36K0 Datasheet



<https://www.DiGi-Electronics.com>

| | |
|------------------------------|--|
| DiGi Electronics Part Number | RSF3JB36K0-DG |
| Manufacturer | Stackpole Electronics Inc |
| Manufacturer Product Number | RSF3JB36K0 |
| Description | RES 36K OHM 5% 3W AXIAL |
| Detailed Description | 36 kOhms ±5% 3W Through Hole Resistor Axial Flame Retardant Coating, Safety Metal Oxide Film |

This model RSF3JB36K0 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

RSF3JB36K0

Series:

RSF

Resistance:

36 kOhms

Power (Watts):

3W

Features:

Flame Retardant Coating, Safety

Operating Temperature:

-55°C ~ 235°C

Supplier Device Package:

Axial

Height - Seated (Max):

-

Failure Rate:

-

Manufacturer:

Stackpole Electronics Inc

Product Status:

Active

Tolerance:

±5%

Composition:

Metal Oxide Film

Temperature Coefficient:

±200ppm/°C

Package / Case:

Axial

Size / Dimension:

0.236" Dia x 0.689" L (6.00mm x 17.50mm)

Number of Terminations:

2

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8533.21.0090

Moisture Sensitivity Level (MSL):

Not Applicable

ECCN:

EAR99

RSF / RSMF Series

General Purpose Metal Oxide Resistor

Stackpole Electronics, Inc.
Resistive Product Solutions

Features:

- Lower-cost alternative to carbon comps and wirewounds
- Coating meets UL 94V-0
- Meets solvent test of Mil Standard 202, Method 215
- Cut and formed product is available on select sizes - contact Stackpole
- Higher or lower resistance values may be possible - contact Stackpole
- Flameproof
- 100% RoHS compliant and lead free without exemption
- Halogen free
- REACH compliant



Electrical Specifications

| Type/Code | Power Rating (W) @ 70°C | Maximum Working Voltage (V) ⁽¹⁾ | Maximum Overload Voltage (V) | Dielectric Withstanding Voltage (V) | TCR (ppm/°C) | Ohmic Range ⁽²⁾ (Ω) and Tolerance | | |
|-----------|-------------------------|--|------------------------------|-------------------------------------|--------------|--|------------|------------|
| | | | | | | 1% | 2% | 5% |
| RSF12 | 0.5 | 250 | 400 | 350 | ± 200 | 0.1 - 150K | 0.1 - 75K | 0.1 - 510K |
| RSF1 | 1 | 350 | 600 | 600 | ± 200 | 0.1 - 100K | | 0.1 - 510K |
| RSF2 | 2 | 350 | 600 | 600 | ± 200 | 0.1 - 120K | | 0.1 - 510K |
| RSF3 | 3 | 800 | 1000 | 750 | ± 200 | 0.1 - 470K | 0.1 - 510K | 0.1 - 510K |
| RSF5 | 5 | 1000 | 1000 | 750 | ± 200 | 0.1 - 470K | 0.1 - 510K | 0.1 - 510K |
| RSMF12 | 0.5 | 250 | 400 | 350 | ± 200 | 0.1 - 46.4K | 0.1 - 47K | 0.1 - 470K |
| RSMF1 | 1 | 350 | 600 | 500 | ± 200 | 0.1 - 75K | | 0.1 - 470K |
| RSMF2 | 2 | 350 | 600 | 500 | ± 200 | 0.1 - 100K | | 0.1 - 470K |
| RSMF3 | 3 | 500 | 800 | 600 | ± 200 | 0.1 - 118K | 0.1 - 120K | 0.1 - 470K |
| RSMF5 | 5 | 1000 | 1000 | 750 | ± 200 | 0.1 - 470K | 0.1 - 510K | 0.1 - 510K |

(1) Lesser of $\sqrt{P \cdot R}$ or maximum working voltage

(2) Contact Stackpole for resistance values outside the specified range

Mechanical Specifications



| Type/Code | A Body Length | B Body Diameter | C Lead Length (Bulk) | D Lead Diameter | Lead-Tape Specification | Unit |
|-----------|------------------|--------------------|-------------------------|--------------------|-------------------------|--------|
| RSF12 | 0.35 ± 0.04 | 0.13 ± 0.03 | 1.10 ± 0.12 | 0.03 ± 0.003 | 0.250 | inches |
| | 9.00 ± 1.00 | 3.20 ± 0.80 | 28.00 ± 3.00 | 0.70 ± 0.08 | 6.35 | mm |
| RSF1 | 0.43 ± 0.06 | 0.18 ± 0.04 | 1.10 ± 0.20 | 0.03 ± 0.002 | 0.250 | inches |
| | 11.00 ± 1.50 | 4.50 ± 1.00 | 28.00 ± 5.00 | 0.80 ± 0.05 | 6.35 | mm |
| RSF2 | 0.59 ± 0.06 | 0.22 ± 0.04 | 1.18 ± 0.20 | 0.03 ± 0.004 | 0.250 | inches |
| | 15.00 ± 1.50 | 5.50 ± 1.00 | 30.00 ± 5.00 | 0.75 ± 0.10 | 6.35 | mm |
| RSF3 | 0.69 ± 0.04 | 0.24 ± 0.02 | 1.38 ± 0.12 | 0.03 ± 0.002 | 0.250 | inches |
| | 17.50 ± 1.00 | 6.00 ± 0.50 | 35.00 ± 3.00 | 0.80 ± 0.05 | 6.35 | mm |
| RSF5 | 0.96 ± 0.04 | 0.31 ± 0.02 | 1.38 ± 0.12 | 0.03 ± 0.002 | 0.250 | inches |
| | 24.50 ± 1.00 | 8.00 ± 0.50 | 35.00 ± 3.00 | 0.80 ± 0.05 | 6.35 | mm |
| RSMF12 | 0.24 ± 0.03 | 0.09 ± 0.01 | 1.10 ± 0.12 | 0.02 ± 0.003 | 0.250 | inches |
| | 6.00 ± 0.80 | 2.30 ± 0.30 | 28.00 ± 3.00 | 0.55 ± 0.07 | 6.35 | mm |
| RSMF1 | 0.35 ± 0.04 | 0.13 ± 0.03 | 1.10 ± 0.12 | 0.03 ± 0.003 | 0.250 | inches |
| | 9.00 ± 1.00 | 3.20 ± 0.80 | 28.00 ± 3.00 | 0.70 ± 0.08 | 6.35 | mm |
| RSMF2 | 0.43 ± 0.06 | 0.18 ± 0.04 | 1.18 ± 0.20 | 0.03 ± 0.002 | 0.250 | inches |
| | 11.00 ± 1.50 | 4.50 ± 1.00 | 30.00 ± 5.00 | 0.80 ± 0.05 | 6.35 | mm |
| RSMF3 | 0.59 ± 0.06 | 0.22 ± 0.04 | 1.18 ± 0.20 | 0.03 ± 0.004 | 0.250 | inches |
| | 15.00 ± 1.50 | 5.50 ± 1.00 | 30.00 ± 5.00 | 0.75 ± 0.10 | 6.35 | mm |
| RSMF5 | 0.69 ± 0.04 | 0.24 ± 0.02 | 1.38 ± 0.08 | 0.03 ± 0.002 | 0.250 | inches |
| | 17.50 ± 1.00 | 6.00 ± 0.50 | 35.00 ± 2.00 | 0.80 ± 0.05 | 6.35 | mm |



| Performance Characteristics | | | |
|--|---------------------------------|---|------------------|
| Test | Test Method | Test Specification | Typical Results |
| Insulation Resistance | JIS C5201-1, IEC60115-1, 4.6 | $\geq 1G \Omega$ | $\geq 1G \Omega$ |
| Voltage Proof | JIS C5201-1, IEC60115-1, 4.7 | $\leq \pm (0.5\% + 0.05 \Omega)$ No mechanical damage | $< \pm 0.25\%$ |
| Short Time Overload | JIS C5201-1, IEC60115-1, 4.13 | $\leq \pm (0.75\% + 0.05 \Omega)$ | $< \pm 0.1\%$ |
| Resistance to Solder Heat | JIS C5201-1, IEC60115-1, 4.18 | $\leq \pm (2.0\% + 0.05 \Omega)$ | $< \pm 1.0\%$ |
| Endurance at 70°C | JIS C5201-1, IEC60115-1, 4.25.1 | $\leq \pm (5.0\% + 0.05 \Omega)$ | $< \pm 2.0\%$ |
| Robustness of Terminations | JIS C5201-1, IEC60115-1, 4.16 | $\leq \pm (1.0\% + 0.05 \Omega)$ | $< \pm 0.10\%$ |
| Damp Heat (Steady state) | JIS C5201-1, IEC60115-1, 4.24 | $\leq \pm (5\% + 0.05 \Omega)$ | $< \pm 1.5\%$ |
| Rapid Change of Temperature | JIS C5201-1, IEC60115-1, 4.19 | $\leq \pm (1\% + 0.05 \Omega)$ | $< \pm 0.2\%$ |
| Resistance to Solvents | JIS C5201-1, IEC60115-1, 4.29 | No damage to component or removal of marking | Pass |
| Intermittent Overload | JIS C5201-1, IEC60115-1, 4.39 | $\leq \pm (2\% + 0.05 \Omega)$ | $< \pm 0.3\%$ |
| Accidental Overload (Flame resistance) | JIS C5201-1, IEC60115-1, 4.26 | No flaming of gauze | Pass |

Operating temperature range is -55°C to +200°C (RSF12, RSMF12, RSMF1)
-55°C to +235°C (all others)

Power Derating Curve:



Surface Temperature Rise:



Repetitive Pulse Information:

If repetitive pulses are applied to resistors, pulse wave form must be less than “pulse limiting voltage”, “pulse limiting current” or “pulse limiting wattage” calculated by the formula below.

$$V_p = K\sqrt{P \times R \times T/t}$$

$$I_p = K\sqrt{P/R \times T/t}$$

$$P_p = K^2 \times P \times T/t$$

Where: V_p : Pulse limiting voltage (V)
 I_p : Pulse limiting current (A)
 P_p : Pulse limiting wattage (W)
 P : Power rating (W)
 R : Nominal resistance (ohm)
 T : Repetitive period (sec)
 t : Pulse duration (sec)
 K : Coefficient: 0.8
 $[V_r$: Rated Voltage (V), I_r : Rated Current (A)]



Note 1: If $T > 10 \rightarrow T = 10$ (sec), $T/t > 1000 \rightarrow T/t = 1000$

Note 2: If $T > 10$ and $T/t > 1000$, “Pulse Limiting power (Single pulse) is applied”

Note 3: If $V_p < V_r$ ($I_p < I_r$ or $P_p < P$), V_r (I_r , P) is V_p (I_p , P_p)


Note 4: Pulse limiting voltage (current, wattage) is applied at less than rated ambient temperature.
 If ambient temperature is more than the rated temperature (70 °C), decrease power rating according to “Power Derating Curve”

Note 5: Assure sufficient margin for use period and conditions for “pulse limiting voltage”


Note 6: If the pulse waveform is not square wave, judge after transform the waveform into square wave according to the “Waveform Transformation to Square Wave”.

Waveform Transformation to Square Wave


1. Discharge curve wave with time constant "t" → Square wave




2. Damping oscillation wave with time constant of envelope "t" → Square wave




3. Half-wave rectification wave → Square wave



4. Triangular wave → Square wave



5. Special wave → Square wave



Recommended Soldering Condition

Flow Soldering:

- Pre-heating: 110°C MAX
- Peak temperature/duration: 260°C within 10 seconds (1st, 2nd wave total)
- Temperature profile (see chart on the right)

Iron Soldering:

- 380°C, 5 seconds, once/terminal



Reel Packaging Specifications

Reeled in accordance with EIA-296-F



| Type/Code | A max ⁽¹⁾ | B max | C | D ⁽²⁾ | Tape | Unit |
|-----------|----------------------|--------|---------------|------------------|-------|--------|
| RSF12 | 2.736 | 13.504 | 0.197 ± 0.020 | 2.063 ± 0.079 | 0.250 | inches |
| | 69.50 | 343.00 | 5.00 ± 0.50 | 52.40 ± 2.00 | 6.35 | mm |
| RSF1 | 2.815 | 13.504 | 0.197 ± 0.020 | 2.063 ± 0.079 | 0.250 | inches |
| | 71.50 | 343.00 | 5.00 ± 0.50 | 52.40 ± 2.00 | 6.35 | mm |
| RSF2 | 3.524 | 13.504 | 0.394 ± 0.020 | 2.500 ± 0.079 | 0.250 | inches |
| | 89.50 | 343.00 | 10.00 ± 0.50 | 63.50 ± 2.00 | 6.35 | mm |
| RSF3 | 3.740 | 12.008 | 0.394 ± 0.020 | 2.874 ± 0.079 | 0.250 | inches |
| | 95.00 | 305.00 | 10.00 ± 0.50 | 73.00 ± 2.00 | 6.35 | mm |
| RSF5 | 4.331 | 12.008 | 0.394 ± 0.020 | 3.465 ± 0.079 | 0.250 | inches |
| | 110.00 | 305.00 | 10.00 ± 0.50 | 88.00 ± 2.00 | 6.35 | mm |
| Type/Code | A max ⁽¹⁾ | B max | C | D ⁽²⁾ | Tape | Unit |
| RSMF12 | 2.618 | 13.504 | 0.197 ± 0.020 | 2.063 ± 0.079 | 0.250 | inches |
| | 66.50 | 343.00 | 5.00 ± 0.50 | 52.40 ± 2.00 | 6.35 | mm |
| RSMF1 | 2.736 | 13.504 | 0.197 ± 0.020 | 2.063 ± 0.079 | 0.250 | inches |
| | 69.50 | 343.00 | 5.00 ± 0.50 | 52.40 ± 2.00 | 6.35 | mm |
| RSMF2 | 2.815 | 13.504 | 0.197 ± 0.020 | 2.063 ± 0.079 | 0.250 | inches |
| | 71.50 | 343.00 | 5.00 ± 0.50 | 52.40 ± 2.00 | 6.35 | mm |
| RSMF3 | 3.524 | 13.504 | 0.394 ± 0.020 | 2.500 ± 0.079 | 0.250 | inches |
| | 89.50 | 343.00 | 10.00 ± 0.50 | 63.50 ± 2.00 | 6.35 | mm |
| RSMF5 | 3.740 | 12.008 | 0.394 ± 0.020 | 2.874 ± 0.079 | 0.250 | inches |
| | 95.00 | 305.00 | 10.00 ± 0.50 | 73.00 ± 2.00 | 6.35 | mm |

Dimension "E": This is a non-critical dimension that does not have a tolerance in the standard.

Range of diameters is from 0.547 inches (13.90 mm) to 1.500 inches (38.10 mm).

(1) Reference value only. The "A" dimension shall be governed by the overall length of the taped component.

The distance between flanges shall be 0.059 inches (1.50 mm) to 0.315 (8.00 mm) greater than the overall component.


(2) The given dimension "D" expresses the standard width spacing. A 26 mm narrow spacing is available as option "N" packaging code.

RSF / RSMF Series

General Purpose Metal Oxide Resistor


Stackpole Electronics, Inc.
Resistive Product Solutions

Ammo Packaging Specifications



| Type/Code | Size | A | B | C | Unit |
|-----------|------|-------------------------------|-------------------------------|---------------------------------|--------------|
| RSF | 2 | 3.346 ± 0.079 85.00 ± 2.00 | 3.543 ± 0.118 90.00 ± 3.00 | 10.039 ± 0.197 255.00 ± 5.00 | inches mm |
| RSF | 1 | 2.953 ± 0.079 75.00 ± 2.00 | 2.756 ± 0.118 70.00 ± 3.00 | | inches mm |
| RSMF | 3 | 3.346 ± 0.079 85.00 ± 2.00 | 3.543 ± 0.118 90.00 ± 3.00 | | inches mm |
| RSMF | 2 | 2.953 ± 0.079 75.00 ± 2.00 | 2.756 ± 0.118 70.00 ± 3.00 | | inches mm |
| RSMF | 1 | 2.953 ± 0.079 75.00 ± 2.00 | 2.756 ± 0.118 70.00 ± 3.00 | | inches mm |

Pana-Sert Packaging Specifications



| Symbol | Description | PRSM12 | PRSF1 / PRSM2 |
|--------|--------------------------|-------------------------------|------------------------------|
| ØD | Body diameter | 0.157 max. 4.00 max. | 0.217 max. 5.50 max. |
| A | Body length | 0.394 max. 10.00 max. | 0.492 max. 12.50 max. |
| A0 | Mounting height | 0.571 max. 14.50 max. | 0.709 max. 18.00 max. |
| Ød | Lead diameter | 0.028 ± 0.004 0.70 ± 0.10 | 0.028 ± 0.004 0.70 ± 0.10 |
| P | Component pitch | 0.500 ± 0.039 12.70 ± 1.00 | |
| P0 | Feed hole pitch | 0.500 ± 0.012 12.70 ± 0.30 | |
| P1 | Feed hole center to lead | 0.152 ± 0.020 3.85 ± 0.50 | |
| P2 | Feed hole center to body | 0.250 ± 0.016 6.35 ± 0.40 | |

RSF / RSMF Series


General Purpose Metal Oxide Resistor

Stackpole Electronics, Inc.
Resistive Product Solutions


Pana-Sert Packaging Specifications (cont.)

| Symbol | Description | PRSM12 | PRSF1 / PRSM2 |
|--------|-------------------------|--|---------------|
| F | Lead-lead distance | 0.200 +0.24 / -0.008 5.08 +0.60 / -0.20 | |
| Alpha | Performing angle | 45° max | |
| Δh | Component alignment | 0.000 ±0.079 0.00 ±2.00 | |
| Δg | Component alignment | 0.000 ±0.118 0.00 ±3.00 | |
| W | Tape width | 0.709 +0.039 / -0.031 18.00 +1.00 / -0.80 | |
| W0 | Hold down tape width | 0.492 min. 12.50 min. | |
| W1 | Hole position | 0.354 ±0.020 9.00 ±0.50 | |
| W2 | Hold down tape position | 0.079 +0 / -0.059 2.00 +0 / -1.50 | |
| H | Distance to tape center | 0.748 ±0.039 19.00 ±1.00 | |
| H0 | Lead wire clinch height | 0.630 ±0.020 16.00 ±0.50 | |
| I | Lead wire portrait | 0.039 max. 1.00 max. | |
| ØD0 | Feed hole diameter | 0.157 ±0.008 4.00 ±0.20 | |
| i | Total tape thickness | 0.028 max. 0.70 max. | |
| L | Length of shipped lead | 0.433 max. 11.00 max. | |

Pulse Limiting Power (one pulse) / RSMF Series ≤ 5Ω



Pulse Limiting Power (one pulse) / RSMF Series > 5Ω



RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union's directive regarding "Restrictions on Hazardous Substances" (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status

| Standard Product Series | Description | Package / Termination Type | Standard Series RoHS Compliant | Lead-Free Termination Composition | Lead-Free Mfg. Effective Date (Std Product Series) | Lead-Free Effective Date Code (YY/WW) |
|-------------------------|---|----------------------------|--------------------------------|-----------------------------------|--|---------------------------------------|
| RSF | General Purpose Metal Oxide Leaded Resistor | Axial | YES | 99.3/0.7 Sn/Cu 100% Matte Sn | Apr-05 (Japan) Jan-04 (Taiwan, China) | 05/14 04/01 |
| RSMF | Mini-Metal Oxide Leaded Resistor | Axial | YES | 99.3/0.7 Sn/Cu 100% Matte Sn | Apr-05 (Japan) Jan-04 (Taiwan, China) | 05/14 04/01 |

"Conflict Metals" Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the "conflict region" of the Eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to "REACH"

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, "The Registration, Evaluation, Authorization and Restriction of Chemicals", otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

RSF / RSMF Series

General Purpose Metal Oxide Resistor

Stackpole Electronics, Inc.
Resistive Product Solutions

Environmental Policy

It is the policy of Stackpole Electronics, Inc. (SEI) to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

How to Order

| Product Series | | Power Rating | | Tolerance | | | Packaging | | | Resistance Value | |
|----------------|---------------|--------------|-----|-----------|-----|-------|-----------|---------------|--|------------------|--|
| Code | Description | Size | W | Code | Tol | Value | Code | Description | Size | Quantity | |
| RSF | Metal Oxide | 12 | 0.5 | F | 1% | E96 | T | Tape and Reel | RSMF12, PRSM12 | 5000 | Four characters with the multiplier used as the decimal holder. 0.22 ohm = R220 33.2 ohm = 33R2 10.2 Kohm = 10K2 1 Mohm = 1M00 |
| RSMF | Mini | 1 | 1 | G | 2% | E24 | | | RSF12, RSF1 | 2500 | |
| PRSF | Panasert | 2 | 2 | J | 5% | | | | RSMF1, RSMF2 | 2000 | |
| PRSM | Panasert Mini | 3 | 3 | | | | | | PRSF1, PRSM2 | 1000 | |
| | | 5 | 5 | | | | | | RSF2, RSMF3 | 1000 | |
| | | | | | | | T | Tape and Reel | RSF3, RSMF5 | 1000 | |
| | | | | | | | | | RSF5 | 500 | |
| | | | | | | | A | Ammo | RSMF12 | 5000 | |
| | | | | | | | | | RSF12; RSMF1, PRSM12 | 2000 | |
| | | | | | | | | | RSF1, RSF2, RSMF2, PRSF1, PRSM2, RSMF3 | 1000 | |
| | | | | | | | B | Bulk | RSF3, RSF5, RSMF5 | 500 | |
| | | | | | | | | | All Sizes | 1000 | |

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we strictly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.