


# STTH1R04A Datasheet

[www.digi-electronics.com](http://www.digi-electronics.com)



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	STTH1R04A-DG
Manufacturer	<a href="#">STMicroelectronics</a>
Manufacturer Product Number	STTH1R04A
Description	DIODE GEN PURP 400V 1A SMA
Detailed Description	Diode 400 V 1A Surface Mount SMA

This model STTH1R04A is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

STTH1R04A

Series:

-

Technology:

Standard

Current - Average Rectified (Io):

1A

Speed:

Fast Recovery =< 500ns, > 200mA (Io)

Current - Reverse Leakage @ Vr:

5  $\mu$ A @ 400 V

Mounting Type:

Surface Mount

Supplier Device Package:

SMA

Base Product Number:

STTH1

Manufacturer:

STMicroelectronics

Product Status:

Active

Voltage - DC Reverse (Vr) (Max):

400 V

Voltage - Forward (Vf) (Max) @ If:

1.5 V @ 1 A

Reverse Recovery Time (trr):

30 ns

Capacitance @ Vr, F:

-

Package / Case:

DO-214AC, SMA

Operating Temperature - Junction:

175°C (Max)

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8541.10.0080


Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

## 1 A - 400 V ultrafast recovery diode



### Features

- Negligible switching losses
- Low forward voltage drop
- High junction temperature
- ECOPACK compliant

### Applications

- Switching diode
- Telecom power

### Description

The STTH1R04 series uses ST's new 400 V planar Pt doping technology. The STTH1R04 is specially suited for switching mode base drive and transistor circuits.

Packaged in SMA, SMB and DO-15, the STTH1R04 is ideal for use low voltage, high frequency inverters, free wheeling and polarity protection

Product status	
STTH1R04	
Product summary	
Symbol	Value
$I_{F(AV)}$	1 A
$V_{RRM}$	400 V
$T_{j(max.)}$	175 °C
$V_{F(typ.)}$	0.9 V
$t_{rr(typ.)}$	14 ns

# 1 Characteristics

**Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified)**

Symbol	Parameter		Value	Unit	
$V_{RRM}$	Repetitive peak reverse voltage		400	V	
$I_{F(AV)}$	Average forward current $\delta = 0.5$ , square wave	SMA	$T_L = 125\text{ °C}$	1	A
		SMB	$T_L = 140\text{ °C}$		
		DO-15	$T_L = 105\text{ °C}$		
$I_{FSM}$	Surge non repetitive forward current		$t_p = 10\text{ ms}$ sinusoidal	30	A
$T_{stg}$	Storage temperature range		-65 to +175	°C	
$T_j$	Operating junction temperature		+175	°C	

**Table 2. Thermal resistance parameter**

Symbol	Parameter		Max. value	Unit	
$R_{th(j-l)}$	Junction to lead		SMA	35	°C/W
			SMB	25	
	Junction to lead	Lead length = 10 mm on infinite heatsink	DO-15	50	

For more information, please refer to the following application note :

- AN5088 : Rectifiers thermal management, handling and mounting recommendations

**Table 3. Static electrical characteristics**

Symbol	Parameter	Test conditions		Min.	Typ.	Max.	Unit
$I_R^{(1)}$	Reverse leakage current	$T_j = 25\text{ °C}$	$V_R = V_{RRM}$	-		5	$\mu\text{A}$
		$T_j = 125\text{ °C}$		-	5	50	$\mu\text{A}$
$V_F^{(2)}$	Forward voltage drop	$T_j = 25\text{ °C}$	$I_F = 1\text{ A}$	-		1.50	V
		$T_j = 100\text{ °C}$		-	1.0	1.25	
		$T_j = 150\text{ °C}$		-	0.9	1.15	

1. Pulse test:  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$

2. Pulse test:  $t_p = 380\text{ }\mu\text{s}$ ,  $\delta < 2\%$

To evaluate the conduction losses, use the following equation:

$$P = 0.9 \times I_{F(AV)} + 0.250 \times I_F^2_{(RMS)}$$

For more information, please refer to the following application notes related to the power losses :

- AN604: Calculation of conduction losses in a power rectifier
- AN4021: Calculation of reverse losses on a power diode



**Table 4. Dynamic characteristics ( $T_j = 25\text{ °C}$  unless otherwise stated)**

Symbol	Parameters	Test conditions	Min.	Typ.	Max.	Unit
$t_{rr}$	Reverse recovery time	$I_F = 1\text{ A}$ , $di_F/dt = -50\text{ A}/\mu\text{s}$ , $V_R = 30\text{ V}$	-		30	ns
		$I_F = 1\text{ A}$ , $di_F/dt = -100\text{ A}/\mu\text{s}$ , $V_R = 30\text{ V}$	-	14	20	
$I_{RM}$	Reverse recovery current	$I_F = 1\text{ A}$ , $di_F/dt = -200\text{ A}/\mu\text{s}$ , $V_R = 320\text{ V}$ , $T_j = 125\text{ °C}$	-	2.5	3.5	A
$t_{fr}$	Forward recovery time	$I_F = 1\text{ A}$ , $di_F/dt = 100\text{ A}/\mu\text{s}$ , $V_{FR} = 1.1 \times V_{F(max)}$	-		50	ns
$V_{FP}$	Forward recovery voltage	$I_F = 1\text{ A}$ , $di_F/dt = 100\text{ A}/\mu\text{s}$	-	3.5		V




### 1.1 Characteristics (curves)


**Figure 1. Average forward power dissipation versus average forward current**




**Figure 2. Forward voltage drop versus forward current**



**Figure 3. Relative variation of thermal impedance junction to lead versus pulse duration (SMA)**




**Figure 4. Relative variation of thermal impedance junction to lead versus pulse duration (SMB)**







**Figure 5. Relative variation of thermal impedance junction to lead versus pulse duration (DO-15)**




**Figure 6. Reverse recovery charges versus  $di_f/dt$  (typical values)**




**Figure 7. Junction capacitance versus reverse voltage applied (typical values)**




**Figure 8. Reverse recovery time versus  $di_f/dt$  (typical values)**



**Figure 9. Peak reverse recovery current versus  $di_f/dt$  (typical values)**




**Figure 10. Relative variations of dynamic parameters versus junction temperature**







**Figure 11. Transient peak forward voltage versus  $di_F/dt$  (typical values)**




**Figure 12. Forward recovery time versus  $di_F/dt$  (typical values)**




**Figure 13. Thermal resistance junction to ambient versus copper surface under each lead (typical values)**



**Figure 14. Thermal resistance junction to ambient versus copper surface under each lead (typical values)**



**Figure 15. Thermal resistance junction to ambient versus lead length, DO-15**




## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

### 2.1 SMB package information


- Epoxy meets UL94, V0
- Lead-free package

Figure 16. SMB package outline



**Table 5. SMB package mechanical data**

Ref.	Dimensions			
	Millimeters		Inches (for reference only)	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.074	0.097
A2	0.05	0.20	0.001	0.008
b	1.95	2.20	0.076	0.087
c	0.15	0.40	0.005	0.016
D	3.30	3.95	0.129	0.156
E	5.10	5.60	0.200	0.221
E1	4.05	4.60	0.159	0.182
L	0.75	1.50	0.029	0.060

**Figure 17. SMB recommended footprint**


## 2.2 SMA package information

- Epoxy meets UL94, V0
- Cooling method : by conduction (C)

Figure 18. SMA package outline





Table 6. SMA package mechanical data

Ref.	Dimensions			
	Millimeters		Inches (for reference only)	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.074	0.097
A2	0.05	0.20	0.001	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.40	0.005	0.016
D	2.25	2.90	0.088	0.115
E	4.80	5.35	0.188	0.211
E1	3.95	4.60	0.155	0.182
L	0.75	1.50	0.029	0.060

**Figure 19. SMA recommended footprint in mm (inches)**

## 2.3 DO-15 package information

- Epoxy meets UL 94, V0

Figure 20. DO-15 package outline




Table 7. DO-15 package mechanical data

Ref.	Dimensions					
	Millimeters			Inches (for reference only)		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	6.05	-	6.75	0.238	-	0.266
B	2.95	-	3.53	0.116	-	0.139
C	26.00	-	31.00	1.024	-	1.220
D	0.71	-	0.88	0.028	-	0.0035



### 3 Ordering information

**Table 8. Ordering information**

Order code	Marking	Package	Weight	Base qty.	Delivery mode
STTH1R04A	HR4	SMA	0.068 g	5000	Tape and reel
STTH1R04U	BR4	SMB	0.107 g	2500	Tape and reel
STTH1R04QRL	STTH1R04Q	DO-15	0.400 g	6000	Tape and reel



## Revision history

**Table 9. Document revision history**

Date	Revision	Changes
30-May-2008	1	First issue.
12-Nov-2015	2	Updated Figure 3, Figure 4, Figure 5 and Figure 6. Minor text changes.
13-Nov-2018	3	Removed DO-41 package information.
15-Mar-2019	4	Updated <a href="#">Table 3. Static electrical characteristics</a> .

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.