

2MM-HSP-D13-VT-02-H-TB Datasheet



AUTHORIZED DISTRIBUTOR

<https://www.DiGi-Electronics.com>

| | |
|------------------------------|---|
| DiGi Electronics Part Number | 2MM-HSP-D13-VT-02-H-TB-DG |
| Manufacturer | TE Connectivity AMP Connectors |
| Manufacturer Product Number | 2MM-HSP-D13-VT-02-H-TB |
| Description | 26P, AMPMODU 2 MM, SHROUDED HEAD |
| Detailed Description | Connector Header Through Hole 26 position 0.079" (2.00mm) |

This model 2MM-HSP-D13-VT-02-H-TB is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

| | | | |
|------------------------------------|------------------------|-------------------------------|--------------------------------|
| Manufacturer Product Number: | 2MM-HSP-D13-VT-02-H-TB | Manufacturer: | TE Connectivity AMP Connectors |
| Series: | AMPMODU 2MM | Product Status: | Active |
| Connector Type: | Header | Contact Type: | Male Pin |
| Pitch - Mating: | 0.079" (2.00mm) | Number of Positions: | 26 |
| Number of Rows: | 2 | Row Spacing - Mating: | 0.079" (2.00mm) |
| Number of Positions Loaded: | All | Style: | Board to Board or Cable |
| Shrouding: | Shrouded - 2 Wall | Mounting Type: | Through Hole |
| Termination: | Solder | Fastening Type: | Latch Holder |
| Contact Length - Mating: | 0.157" (4.00mm) | Contact Length - Post: | 0.110" (2.80mm) |
| Overall Contact Length: | 0.327" (8.30mm) | Insulation Height: | 0.217" (5.51mm) |
| Contact Shape: | Square | Contact Finish - Mating: | Gold |
| Contact Finish Thickness - Mating: | 30.0µin (0.76µm) | Contact Finish - Post: | Tin |
| Contact Material: | Phosphor Bronze | Insulation Material: | Thermoplastic |
| Features: | Polarizing Key | Operating Temperature: | -40°C ~ 105°C |
| Ingress Protection: | - | Material Flammability Rating: | UL94 V-0 |
| Insulation Color: | Black | Current Rating (Amps): | 2A |
| Voltage Rating: | 250VAC | Mated Stacking Heights: | - |
| Contact Finish Thickness - Post: | 12.0µin (0.30µm) | Applications: | - |

Environmental & Export classification

| | | | |
|------------------|---|-----------------------------------|----------------|
| RoHS Status: | DiGi is a global authorized distributor | Moisture Sensitivity Level (MSL): | Not Applicable |
| ROHS3 Compliant: | | ECCN: | |
| REACH Status: | | | |

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.