

IHTH0750IZEBR47M5A Datasheet

www.digi-electronics.com



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	IHTH0750IZEBR47M5A-DG
Manufacturer	Vishay Dale
Manufacturer Product Number	IHTH0750IZEBR47M5A
Description	FIXED IND 470NH 83A 0.52 MOHM TH
Detailed Description	470 nH Shielded Inductor 83 A 0.52mOhm Max Radial, Vertical Cylinder



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

IHTH0750IZEBR47M5A

Series:

IHTH-0750IZ-5A

Type:

-

Inductance:

470 nH

Current Rating (Amps):

83 A

Shielding:

Shielded

Q @ Freq:

-

Ratings:

AEC-Q200

Inductance Frequency - Test:

100 kHz

Mounting Type:

Through Hole

Supplier Device Package:

-

Height - Seated (Max):

0.354" (8.99mm)

Manufacturer:

Vishay Dale

Product Status:

Active

Material - Core:

Metal Composite

Tolerance:

±20%

Current - Saturation (Isat):

44A

DC Resistance (DCR):

0.52mOhm Max

Frequency - Self Resonant:

67MHz

Operating Temperature:

-55°C ~ 155°C

Features:

-

Package / Case:

Radial, Vertical Cylinder

Size / Dimension:

0.755" Dia (19.18mm)

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8504.50.4000

Moisture Sensitivity Level (MSL):


Not Applicable

ECCN:

EAR99



Automotive High Current, Radial, Through-Hole Power Inductor



Single-coil inductor



FEATURES

- Magnetically shielded, metal alloy construction
- Size: 19.177 mm (dia.) x 8.738 mm
- Radial through-hole termination (THT) with third support lead for added mounting stability (for 33 μ H and higher)
- Flat surface for heat sink mounting
- Coil orientation mark for consistent EMI performance (dot indicates inside start lead)
- High temperature up to 155 °C
- AEC-Q200 qualified
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

AUTOMOTIVE GRADE



RoHS COMPLIANT

HALOGEN FREE

GREEN (5-2008)

LINKS TO ADDITIONAL RESOURCES



Product Page



Calculators

APPLICATIONS

- 48 V / 12 V bi-directional converters
- DC/DC converters using GaN FETs
- Noise suppression for motors

STANDARD ELECTRICAL SPECIFICATIONS

PART NUMBER	L ₀ INDUCTANCE ± 20 % AT 100 kHz, 0.25 V, 0 A (μ H)	DCR TYP. 25 °C (m Ω)	DCR MAX. 25 °C (m Ω)	HEAT RATING CURRENT DC TYP. (A) ⁽¹⁾	SATURATION CURRENT DC TYP. (A) ⁽²⁾		SRF TYP. (MHz)
					20 % DROP	30 % DROP	
IHTH0750IZEBR47M5A	0.47	0.47	0.52	83.0	44.0	64.0	67.00
IHTH0750IZEB1R0M5A	1.0	0.87	0.92	66.0	44.0	70.0	35.70
IHTH0750IZEB2R2M5A	2.2	1.51	1.63	45.0	38.0	52.0	17.85
IHTH0750IZEB3R3M5A	3.3	2.28	2.40	40.0	33.0	46.0	16.70
IHTH0750IZEB4R7M5A	4.7	2.85	3.00	30.0	26.0	36.0	13.22
IHTH0750IZEB6R8M5A	6.8	3.97	4.18	24.5	22.0	31.0	9.50
IHTH0750IZEB8R2M5A	8.2	5.7	6.14	20.0	14.5	20.0	11.60
IHTH0750IZEB100M5A	10	7.32	7.70	17.7	13.0	18.0	9.77
IHTH0750IZEB220M5A	22	12.56	13.22	12.7	11.5	16.0	6.42
IHTH0750IZEB330M5A	33	22.61	23.80	9.5	10.0	14.0	4.58
IHTH0750IZEB470M5A	47	35.34	37.20	6.8	6.5	9.0	4.28
IHTH0750IZEB680M5A	68	46.47	48.92	6.2	6.2	8.5	2.74
IHTH0750IZEB820M5A	82	55.20	58.10	5.2	6.0	8.0	3.09
IHTH0750IZEB101M5A	100	60.80	64.00	5.0	5.2	7.0	2.63


Notes

- All test data is referenced to 25 °C ambient
- Operating temperature range -55 °C to +155 °C
- Operating voltage rating (across inductor) = 100 V
- The part temperature (ambient + temp. rise) should not exceed 155 °C under worst case operating conditions. Circuit design, component placement, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application

(1) DC current (A) that will cause an approximate ΔT of 40 °C(2) DC current (A) that will cause L₀ to drop approximately 20 % and 30 %, respectively



DIMENSIONS in inches [millimeters]



VALUE	A \pm 0.010 (\pm 0.254)	B \pm 0.010 (\pm 0.254)	C \pm 0.010 (\pm 0.254)	D \pm 0.005 (\pm 0.127)
0.47 μ H	0.351 (8.915)	0.244 (6.198)	0.160 (4.064)	0.079 (2.007)
1.0 μ H	0.487 (12.370)	0.172 (4.369)	0.096 (2.438)	0.071 (1.803)
2.2 μ H	0.487 (12.370)	0.172 (4.369)	0.096 (2.438)	0.071 (1.803)
3.3 μ H	0.464 (11.786)	0.179 (4.547)	0.111 (2.819)	0.063 (1.600)
4.7 μ H	0.464 (11.786)	0.179 (4.547)	0.111 (2.819)	0.056 (1.422)
6.8 μ H	0.522 (13.259)	0.147 (3.734)	0.085 (2.159)	0.056 (1.422)
8.2 μ H	0.427 (10.846)	0.245 (6.223)	0.082 (2.083)	0.050 (1.210)
10 μ H	0.427 (10.846)	0.245 (6.223)	0.082 (2.083)	0.050 (1.210)
22 μ H	0.450 (11.430)	0.226 (5.740)	0.079 (2.007)	0.039 (0.991)
33 μ H	0.477 (12.116)	0.197 (5.004)	0.080 (2.032)	0.035 (0.889)
47 μ H	0.435 (11.049)	0.247 (6.274)	0.072 (1.829)	0.031 (0.787)
68 μ H	0.435 (11.049)	0.247 (6.274)	0.072 (1.829)	0.031 (0.787)
82 μ H	0.458 (11.633)	0.227 (5.766)	0.070 (1.778)	0.028 (0.711)
100 μ H	0.458 (11.633)	0.227 (5.766)	0.070 (1.778)	0.028 (0.711)

DESCRIPTION









IHTH-0750IZ-5A MODEL	4.7 μH INDUCTANCE VALUE	$\pm 20 \%$ INDUCTANCE TOLERANCE
--------------------------------	--	---

GLOBAL PART NUMBER

I H T H	0 7 5 0 I Z	E B	4 R 7	M	5 A
PRODUCT FAMILY	SIZE	PACKAGE CODE	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	SERIES
		EB = tray	4R7 = 4.7 μH	M = $\pm 20 \%$	









PERFORMANCE GRAPHS













PERFORMANCE GRAPHS











PERFORMANCE GRAPHS: INDUCTANCE AND Q VS. FREQUENCY





PERFORMANCE GRAPHS: INDUCTANCE AND Q VS. FREQUENCY





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.