

IMC1812ES221J Datasheet



<https://www.DiGi-Electronics.com>

| | |
|------------------------------|---|
| DiGi Electronics Part Number | IMC1812ES221J-DG |
| Manufacturer | Vishay Dale |
| Manufacturer Product Number | IMC1812ES221J |
| Description | FIXED IND 220UH 100MA 10 OHM SMD |
| Detailed Description | 220 μ H Unshielded Drum Core, Wirewound Inductor 100 mA 100ohm Max 1812 (4532 Metric) |



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

IMC1812ES221J

Series:

IMC-1812

Type:

Drum Core, Wirewound

Inductance:

220 μ H

Current Rating (Amps):

100 mA

Shielding:

Unshielded

Q @ Freq:

40 @ 790kHz

Ratings:

-

Inductance Frequency - Test:

790 kHz

Package / Case:

1812 (4532 Metric)

Size / Dimension:

0.177" L x 0.126" W (4.50mm x 3.20mm)

Manufacturer:

Vishay Dale

Product Status:

Active

Material - Core:

Ferrite

Tolerance:

\pm 5%

Current - Saturation (Isat):

-

DC Resistance (DCR):

100hm Max

Frequency - Self Resonant:

4MHz

Operating Temperature:

-55°C ~ 125°C

Mounting Type:

Surface Mount

Supplier Device Package:

1812

Height - Seated (Max):

0.134" (3.40mm)

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8504.50.8000

Moisture Sensitivity Level (MSL):


1 (Unlimited)

ECCN:

EAR99



Wirewound, Surface-Mount, Molded RF Inductors



FEATURES

- Molded construction provides superior strength and moisture resistance
- RF inductors for high frequency filtering and impedance matching
- Size: 4.5 mm x 3.2 mm x 3.2 mm
- Non-RoHS terminations available (see package code options below)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

LINKS TO ADDITIONAL RESOURCES



TEST EQUIPMENT

- H/P 4342A Q meter with Vishay Dale test fixture or equivalent
- H/P 4191A RF impedance analyzer (for SRF measurements)
- Wheatstone bridge

ELECTRICAL SPECIFICATIONS

Inductance range: 0.010 μ H to 1000 μ H

Special tolerances available upon request

Operating temperature: -55 °C to +125 °C

Coilform material: non-magnetic for 0.010 μ H to 0.82 μ H; powdered iron for 1.0 μ H to 120 μ H; ferrite for 150 μ H to 1000 μ H

| STANDARD ELECTRICAL SPECIFICATIONS | | | | | | | |
|------------------------------------|-----------------|------------|------------------|--------|----------------|-----------------------|--------------------------------------|
| PART NUMBER | IND. (μ H) | TOL. | TEST FREQ. (MHz) | Q MIN. | SRF MIN. (MHz) | DCR MAX. (Ω) | RATED DC CURRENT (mA) ⁽¹⁾ |
| | | | L & Q | | | | |
| IMC1812ES10NM | 0.010 | \pm 20 % | 50.0 | 50 | 1000 | 0.20 | 450 |
| IMC1812ES12NM | 0.012 | \pm 20 % | 50.0 | 50 | 1000 | 0.20 | 450 |
| IMC1812ES18NM | 0.018 | \pm 20 % | 50.0 | 50 | 1000 | 0.20 | 450 |
| IMC1812ES22NM | 0.022 | \pm 20 % | 50.0 | 50 | 1000 | 0.20 | 450 |
| IMC1812ES27NM | 0.027 | \pm 20 % | 50.0 | 50 | 1000 | 0.20 | 450 |
| IMC1812ES33NM | 0.033 | \pm 20 % | 50.0 | 50 | 1000 | 0.30 | 450 |
| IMC1812ES39NM | 0.039 | \pm 20 % | 50.0 | 50 | 1000 | 0.30 | 450 |
| IMC1812ES47NM | 0.047 | \pm 20 % | 50.0 | 50 | 1000 | 0.30 | 450 |
| IMC1812ES56NM | 0.056 | \pm 20 % | 50.0 | 40 | 900 | 0.35 | 450 |
| IMC1812ES68NM | 0.068 | \pm 20 % | 50.0 | 40 | 800 | 0.35 | 450 |
| IMC1812ES82NM | 0.082 | \pm 20 % | 50.0 | 40 | 700 | 0.40 | 450 |
| IMC1812ESR10M | 0.10 | \pm 20 % | 25.2 | 30 | 650 | 0.32 | 450 |
| IMC1812ESR12M | 0.12 | \pm 20 % | 25.2 | 30 | 600 | 0.30 | 450 |
| IMC1812ESR15M | 0.15 | \pm 20 % | 25.2 | 30 | 500 | 0.30 | 450 |
| IMC1812ESR18M | 0.18 | \pm 20 % | 25.2 | 30 | 400 | 0.35 | 450 |
| IMC1812ESR22M | 0.22 | \pm 20 % | 25.2 | 30 | 350 | 0.40 | 450 |
| IMC1812ESR27M | 0.27 | \pm 20 % | 25.2 | 30 | 300 | 0.45 | 450 |
| IMC1812ESR33M | 0.33 | \pm 20 % | 25.2 | 30 | 250 | 0.55 | 430 |
| IMC1812ESR39M | 0.39 | \pm 20 % | 25.2 | 30 | 220 | 0.70 | 380 |
| IMC1812ESR47K | 0.47 | \pm 10 % | 25.2 | 30 | 190 | 0.80 | 355 |
| IMC1812ESR56K | 0.56 | \pm 10 % | 25.2 | 30 | 170 | 1.20 | 285 |
| IMC1812ESR68K | 0.68 | \pm 10 % | 25.2 | 30 | 150 | 1.40 | 270 |
| IMC1812ESR82K | 0.82 | \pm 10 % | 25.2 | 30 | 140 | 1.60 | 250 |
| IMC1812ES1R0K | 1.0 | \pm 10 % | 7.96 | 50 | 100 | 0.50 | 450 |
| IMC1812ES1R2K | 1.2 | \pm 10 % | 7.96 | 50 | 80.0 | 0.55 | 430 |
| IMC1812ES1R5K | 1.5 | \pm 10 % | 7.96 | 50 | 70.0 | 0.60 | 410 |
| IMC1812ES1R8K | 1.8 | \pm 10 % | 7.96 | 50 | 60.0 | 0.65 | 390 |



| STANDARD ELECTRICAL SPECIFICATIONS | | | | | | | |
|------------------------------------|-----------|--------|------------------|--------|----------------|--------------|--------------------------------------|
| PART NUMBER | IND. (μH) | TOL. | TEST FREQ. (MHz) | Q MIN. | SRF MIN. (MHz) | DCR MAX. (Ω) | RATED DC CURRENT (mA) ⁽¹⁾ |
| | | | L & Q | | | | |
| IMC1812ES2R2K | 2.2 | ± 10 % | 7.96 | 50 | 55.0 | 0.70 | 380 |
| IMC1812ES2R7K | 2.7 | ± 10 % | 7.96 | 50 | 50.0 | 0.75 | 370 |
| IMC1812ES3R3K | 3.3 | ± 10 % | 7.96 | 50 | 45.0 | 0.80 | 355 |
| IMC1812ES3R9K | 3.9 | ± 10 % | 7.96 | 50 | 40.0 | 0.90 | 330 |
| IMC1812ES4R7K | 4.7 | ± 10 % | 7.96 | 50 | 35.0 | 1.00 | 315 |
| IMC1812ES5R6K | 5.6 | ± 10 % | 7.96 | 50 | 33.0 | 1.10 | 300 |
| IMC1812ES6R8K | 6.8 | ± 10 % | 7.96 | 50 | 27.0 | 1.20 | 285 |
| IMC1812ES8R2K | 8.2 | ± 10 % | 7.96 | 50 | 25.0 | 1.40 | 270 |
| IMC1812ES100K | 10.0 | ± 10 % | 2.52 | 50 | 20.0 | 1.60 | 250 |
| IMC1812ES120K | 12.0 | ± 10 % | 2.52 | 50 | 18.0 | 2.00 | 225 |
| IMC1812ES150K | 15.0 | ± 10 % | 2.52 | 50 | 17.0 | 2.50 | 200 |
| IMC1812ES180K | 18.0 | ± 10 % | 2.52 | 50 | 15.0 | 2.80 | 190 |
| IMC1812ES220K | 22.0 | ± 10 % | 2.52 | 50 | 13.0 | 3.20 | 180 |
| IMC1812ES270K | 27.0 | ± 10 % | 2.52 | 50 | 12.0 | 3.60 | 170 |
| IMC1812ES330K | 33.0 | ± 10 % | 2.52 | 50 | 11.0 | 4.00 | 160 |
| IMC1812ES390K | 39.0 | ± 10 % | 2.52 | 50 | 11.0 | 4.50 | 150 |
| IMC1812ES470K | 47.0 | ± 10 % | 2.52 | 50 | 10.0 | 5.00 | 140 |
| IMC1812ES560K | 56.0 | ± 10 % | 2.52 | 50 | 9.0 | 5.50 | 135 |
| IMC1812ES680K | 68.0 | ± 10 % | 2.52 | 50 | 9.0 | 6.00 | 130 |
| IMC1812ES820K | 82.0 | ± 10 % | 2.52 | 50 | 8.0 | 7.00 | 120 |
| IMC1812ES101K | 100.0 | ± 10 % | 0.79 | 40 | 8.0 | 8.00 | 110 |
| IMC1812ES121K | 120.0 | ± 10 % | 0.79 | 40 | 6.0 | 8.00 | 110 |
| IMC1812ES151K | 150.0 | ± 10 % | 0.79 | 40 | 5.0 | 9.00 | 105 |
| IMC1812ES181K | 180.0 | ± 10 % | 0.79 | 40 | 5.0 | 9.50 | 102 |
| IMC1812ES221K | 220.0 | ± 10 % | 0.79 | 40 | 4.0 | 10.0 | 100 |
| IMC1812ES271K | 270.0 | ± 10 % | 0.79 | 40 | 4.0 | 12.0 | 92 |
| IMC1812ES331K | 330.0 | ± 10 % | 0.79 | 40 | 3.5 | 14.0 | 85 |
| IMC1812ES391K | 390.0 | ± 10 % | 0.79 | 40 | 3.0 | 16.0 | 80 |
| IMC1812ES471K | 470.0 | ± 10 % | 0.79 | 40 | 3.0 | 26.0 | 62 |
| IMC1812ES561K | 560.0 | ± 10 % | 0.79 | 30 | 3.0 | 30.0 | 50 |
| IMC1812ES681K | 680.0 | ± 10 % | 0.79 | 30 | 3.0 | 30.0 | 50 |
| IMC1812ES821K | 820.0 | ± 10 % | 0.79 | 30 | 2.5 | 35.0 | 30 |
| IMC1812ES102K | 1000.0 | ± 10 % | 0.25 | 30 | 2.5 | 40.0 | 30 |

Note

(1) Rated DC current based on the maximum temperature rise, not to exceed 40 °C at +85 °C ambient


| PART MARKING |
|-------------------|
| - DALE |
| - Inductance code |
| - Date code |



| DESCRIPTION | | | |
|-------------|------------------|----------------------|--------------|
| IMC-1812 | 10 μ H | $\pm 10 \%$ | ES |
| MODEL | INDUCTANCE VALUE | INDUCTANCE TOLERANCE | PACKAGE CODE |

| GLOBAL PART NUMBER | | | | |
|--------------------|---------|--------------------|------------------|--|
| I M C | 1 8 1 2 | E S | 1 0 0 | K |
| PRODUCT FAMILY | SIZE | PACKAGE CODE | INDUCTANCE VALUE | INDUCTANCE TOLERANCE |
| | | ES = tape and reel | 100 = 10 μ H | M = $\pm 20 \%$ K = $\pm 10 \%$ J = $\pm 5 \%$ H = $\pm 3 \%$ |

| PACKAGE CODE & TERMINATION OPTIONS |
|--|
| ES = RoHS compliant with tape and reel packaging (2000 pcs on 13-inch reel) |
| ER = RoHS compliant with tape and reel packaging (500 pcs on 7-inch reel) |
| EB = RoHS compliant with bulk packaging (500 pcs/bulk) |
| RQ = non-RoHS tin-lead with tape and reel packaging (2000 pcs on 13-inch reel) |
| RV = non-RoHS tin-lead with tape and reel packaging (500 pcs on 7-inch reel) |
| BN = non-RoHS tin-lead with bulk packaging (500 pcs/bulk) |



Note
 (1) Recommended minimum spacing between components



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.