

ISC1812RQR82K Datasheet

www.digi-electronics.com



<https://www.DiGi-Electronics.com>

| | |
|------------------------------|---|
| DiGi Electronics Part Number | ISC1812RQR82K-DG |
| Manufacturer | Vishay Dale |
| Manufacturer Product Number | ISC1812RQR82K |
| Description | FIXED IND 820NH 271MA 950MOHM SM |
| Detailed Description | 820 nH Shielded Wirewound Inductor 271 mA 950m Ohm Max 1812 (4532 Metric) |



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

ISC1812RQR82K

Series:

ISC-1812

Type:

Wirewound

Inductance:

820 nH

Current Rating (Amps):

271 mA

Shielding:

Shielded

Q @ Freq:

30 @ 25.2MHz

Ratings:

-

Inductance Frequency - Test:

25.2 MHz

Package / Case:

1812 (4532 Metric)

Size / Dimension:

0.177" L x 0.126" W (4.50mm x 3.20mm)

Manufacturer:

Vishay Dale

Product Status:

Active

Material - Core:

Non-Magnetic

Tolerance:

±10%

Current - Saturation (Isat):

-

DC Resistance (DCR):

950mOhm Max

Frequency - Self Resonant:

165MHz

Operating Temperature:

-55°C ~ 125°C

Mounting Type:

Surface Mount

Supplier Device Package:

1812

Height - Seated (Max):

0.134" (3.40mm)

Environmental & Export classification

RoHS Status:

RoHS non-compliant

REACH Status:

REACH Affected

HTSUS:

8504.50.8000

Moisture Sensitivity Level (MSL):


1 (Unlimited)

ECCN:

EAR99



Wirewound, Surface-Mount, Molded, Shielded Inductors



| STANDARD ELECTRICAL SPECIFICATIONS | | | | | | |
|------------------------------------|--------|------------------|--------|----------------|--------------|--------------------------------------|
| IND. (μH) | TOL. | TEST FREQ. (MHz) | Q MIN. | SRF MIN. (MHz) | DCR MAX. (Ω) | RATED DC CURRENT (mA) ⁽¹⁾ |
| | | L & Q | | | | |
| 0.10 | ± 20 % | 25.2 | 30 | 460 | 0.23 | 552 |
| 0.12 | ± 20 % | 25.2 | 30 | 400 | 0.26 | 519 |
| 0.15 | ± 20 % | 25.2 | 30 | 390 | 0.29 | 491 |
| 0.18 | ± 20 % | 25.2 | 30 | 350 | 0.32 | 468 |
| 0.22 | ± 20 % | 25.2 | 30 | 310 | 0.36 | 441 |
| 0.33 | ± 20 % | 25.2 | 30 | 280 | 0.40 | 418 |
| 0.39 | ± 20 % | 25.2 | 30 | 240 | 0.45 | 394 |
| 0.47 | ± 20 % | 25.2 | 30 | 215 | 0.60 | 342 |
| 0.56 | ± 20 % | 25.2 | 30 | 205 | 0.75 | 306 |
| 0.68 | ± 20 % | 25.2 | 30 | 195 | 0.80 | 296 |
| 0.82 | ± 20 % | 25.2 | 30 | 165 | 0.95 | 271 |
| 0.8 | ± 20 % | 25.2 | 30 | 155 | 1.20 | 242 |
| 1.0 | ± 10 % | 7.96 | 30 | 140 | 0.35 | 447 |
| 1.2 | ± 10 % | 7.96 | 30 | 120 | 0.38 | 429 |
| 1.5 | ± 10 % | 7.96 | 30 | 100 | 0.40 | 418 |
| 1.8 | ± 10 % | 7.96 | 30 | 90.0 | 0.43 | 403 |
| 2.2 | ± 10 % | 7.96 | 30 | 80.0 | 0.46 | 390 |
| 2.7 | ± 10 % | 7.96 | 30 | 67.0 | 0.49 | 378 |
| 3.3 | ± 10 % | 7.96 | 30 | 61.0 | 0.55 | 357 |
| 3.9 | ± 10 % | 7.96 | 30 | 56.0 | 0.59 | 344 |
| 4.7 | ± 10 % | 7.96 | 30 | 50.0 | 0.62 | 336 |
| 5.6 | ± 10 % | 7.96 | 30 | 40.0 | 0.69 | 333 |
| 6.8 | ± 10 % | 7.96 | 30 | 32.0 | 0.75 | 306 |
| 8.2 | ± 10 % | 7.96 | 30 | 30.0 | 0.82 | 292 |
| 10.0 | ± 10 % | 2.52 | 50 | 25.0 | 0.90 | 279 |
| 12.0 | ± 10 % | 2.52 | 50 | 22.0 | 1.00 | 265 |
| 15.0 | ± 10 % | 2.52 | 50 | 18.0 | 1.10 | 252 |
| 18.0 | ± 10 % | 2.52 | 50 | 15.0 | 1.24 | 238 |
| 22.0 | ± 10 % | 2.52 | 50 | 14.0 | 1.36 | 227 |
| 27.0 | ± 10 % | 2.52 | 40 | 13.0 | 1.56 | 212 |
| 33.0 | ± 10 % | 2.52 | 40 | 12.0 | 1.72 | 202 |
| 39.0 | ± 10 % | 2.52 | 40 | 11.0 | 1.89 | 192 |
| 47.0 | ± 10 % | 2.52 | 40 | 9.0 | 2.10 | 183 |
| 56.0 | ± 10 % | 2.52 | 40 | 8.0 | 2.34 | 173 |
| 68.0 | ± 10 % | 2.52 | 40 | 7.6 | 2.60 | 164 |
| 82.0 | ± 10 % | 2.52 | 40 | 7.2 | 2.86 | 156 |
| 100.0 | ± 10 % | 0.796 | 40 | 7.0 | 3.25 | 147 |
| 120.0 | ± 10 % | 0.796 | 40 | 6.0 | 3.64 | 139 |
| 150.0 | ± 10 % | 0.796 | 40 | 5.0 | 4.16 | 130 |
| 180.0 | ± 10 % | 0.796 | 40 | 4.5 | 5.72 | 111 |
| 220.0 | ± 10 % | 0.796 | 40 | 4.2 | 6.30 | 105 |
| 270.0 | ± 10 % | 0.796 | 40 | 4.0 | 6.90 | 101 |
| 330.0 | ± 10 % | 0.796 | 40 | 3.7 | 7.54 | 96 |
| 390.0 | ± 10 % | 0.796 | 40 | 3.5 | 8.20 | 92 |
| 470.0 | ± 10 % | 0.796 | 40 | 3.3 | 9.20 | 87 |
| 560.0 | ± 10 % | 0.796 | 30 | 2.8 | 10.50 | 82 |
| 680.0 | ± 10 % | 0.796 | 40 | 2.6 | 12.00 | 76 |
| 820.0 | ± 10 % | 0.796 | 30 | 2.2 | 13.50 | 72 |
| 1000.0 | ± 10 % | 0.252 | 30 | 2.0 | 16.00 | 66 |

Note

⁽¹⁾ Rated DC current based on the maximum temperature rise, not to exceed 40 °C at +85 °C ambient

FEATURES

- Molded construction provides superior strength and moisture resistance
- Tape and reel packaging for automatic handling, 2000/reel, EIA-481
- Compatible with vapor phase and infrared reflow soldering
- Shielded construction minimizes coupling to other components
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT
HALOGEN FREE

ELECTRICAL SPECIFICATIONS

Inductance range: 0.10 μH to 1000 μH

Special tolerances available upon request


Operating temperature: -55 °C to +125 °C

Coilform material: non-magnetic for 0.10 μH to 0.82 μH; powdered iron for 1.0 μH to 22 μH; ferrite for 27 μH to 1000 μH

TEST EQUIPMENT

- H/P 4342A Q meter with Vishay Dale test fixture or equivalent
- H/P 4191A RF impedance analyzer (for SRF measurements)
- Wheatstone bridge

DIMENSIONS in inches [millimeters]



Note


⁽¹⁾ Recommended minimum spacing between components

PART MARKING

- Vishay Dale
- Inductance code
- Date code




COUPLING SPECIFICATIONS (maximum)



DESCRIPTION

| | | | | |
|----------|------------------|----------------------|--------------|--------------------------------|
| ISC-1812 | 10 µH | ± 10 % | ER | e3 |
| MODEL | INDUCTANCE VALUE | INDUCTANCE TOLERANCE | PACKAGE CODE | JEDEC® LEAD (Pb)-FREE STANDARD |

GLOBAL PART NUMBER





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.