


HVR3700002204JA100 Datasheet



<https://www.DiGi-Electronics.com>

| | |
|------------------------------|---|
| DiGi Electronics Part Number | HVR3700002204JA100-DG |
| Manufacturer | Vishay Beyschlag/Draloric/BC Components |
| Manufacturer Product Number | HVR3700002204JA100 |
| Description | RES 2.2M OHM 5% 1/2W AXIAL |
| Detailed Description | 2.2 MOhms ±5% 0.5W, 1/2W Through Hole Resistor Axial High Voltage, Pulse Withstanding Metal Film |

This model HVR3700002204JA100 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

HVR3700002204JA100

Series:

HVR37

Resistance:

2.2 MOhms

Power (Watts):

0.5W, 1/2W

Features:

High Voltage, Pulse Withstanding

Operating Temperature:

-55°C ~ 155°C

Supplier Device Package:

Axial

Height - Seated (Max):

-

Failure Rate:

-

Manufacturer:

Vishay Beyschlag/Draloric/BC Components

Product Status:

Active

Tolerance:

±5%

Composition:

Metal Film

Temperature Coefficient:

±200ppm/°C

Package / Case:

Axial

Size / Dimension:

0.157" Dia x 0.394" L (4.00mm x 10.00mm)

Number of Terminations:

2

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8533.21.0090

Moisture Sensitivity Level (MSL):

Not Applicable


ECCN:

EAR99


www.vishay.com
HVR25, HVR37

Vishay BCcomponents

High Ohmic (up to 10 MΩ) / High Voltage (up to 3.5 kV) Metal Film Leaded Resistors



LINKS TO ADDITIONAL RESOURCES



A homogenous film of metal alloy is deposited on a high grade ceramic body. After a helical groove has been cut in the resistive layer, tinned electrolytic copper wires are welded to the end-caps. The resistors are coated with a blue, non-flammable lacquer, which provides electrical, mechanical, and climatic protection.

FEATURES

- Technology: metal film
- High pulse loading (up to 10 kV) capability
- Small size (0207 / 0411)
- Compatible with lead (Pb)-free and lead containing soldering processes
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

APPLICATIONS

- Power supplies
- Electronic ballast
- White goods
- Television

| TECHNICAL SPECIFICATIONS | | | | | |
|---|------------------------------------|----------------|-----------------|----------------|-----------|
| DESCRIPTION | HVR25 | | HVR37 | | |
| Resistance range | 100 kΩ to 10 MΩ | | 100 kΩ to 10 MΩ | | |
| Resistance tolerance | ± 5 % | ± 1 % | ± 5 % | ± 1 % | |
| E-series | E24 series | E24/E96 series | E24 series | E24/E96 series | |
| Temperature coefficient | ± 200 ppm/K | | | | |
| Climatic category (LCT/UCT/days) | 55/155/56 | | | | |
| Rated dissipation, P_{70} | 0.25 W | | 0.5 W | | |
| Maximum permissible voltage U_{max} . | DC | 1600 V | 3500 V | | |
| | RMS | 1150 V | 2500 V | | |
| Basic specification | IEC 60115-1 | | | | |
| Stability after: | Load (1000 h, P_{70}) | ± 5 % R | ± 1.5 % R | ± 5 % R | ± 1.5 % R |
| | Long term damp heat test (56 days) | ± 5 % R | ± 1.5 % R | ± 5 % R | ± 1.5 % R |
| | Soldering (10 s, 260 °C) | ± 1 % R | ± 1 % R | ± 1 % R | ± 1 % R |



www.vishay.com

HVR25, HVR37

Vishay BCcomponents

| PART NUMBER AND PRODUCT DESCRIPTION (1) | | | | | | |
|--|-------------|----------------|------------------------|----------------------|---|---------------------------------|
| Part Number: HVR250001503JA100 | | | | | | |
| H | V | R | 2 | 5 | 0 | 0 |
| HVR2500 | VARIANT | | TCR/MATERIAL | | VALUE | |
| HVR3700 | 0 = neutral | | 0 = standard | | 3 digit value 1 digit multiplier MULTIPLIER 3 = *10 ³ 4 = *10 ⁴ 5 = *10 ⁵ | |
| | | | TOLERANCE | | PACKAGING (2) | |
| | | | F = ± 1 % J = ± 5 % | | A1 A5 R5 N4 | |
| Product Description: HVR25 5 % A1 150K | | | | | | |
| HVR25 | | 5 % | | A1 | | 150K |
| Model | | TOLERANCE | | PACKAGING (2) | | RESISTANCE VALUE |
| HVR25 HVR37 | | ± 1 % ± 5 % | | A1 A5 R5 N4 | | 150K = 150 kΩ 4M64 = 4.64 MΩ |
| SPECIAL Up to 2 digits 00 = standard | | | | | | |

Notes

- (1) The PART NUMBER is shown to facilitate the introduction of the unified part numbering system
 (2) Please refer to table PACKAGING, see next page


| PACKAGING | | | | | |
|-----------|--------------|-----------|------|--------|------|
| MODEL | TAPING | AMMO PACK | | REEL | |
| | | PIECES | CODE | PIECES | CODE |
| HVR25 | Axial, 52 mm | 5000 | A5 | 5000 | R5 |
| | | 1000 | A1 | | |
| | Radial | 4000 | N4 | | |
| HVR37 | Axial, 52 mm | 1000 | A1 | 5000 | R5 |

MARKING

The nominal resistance and tolerance are marked on the resistor using four or five colored bands in accordance with IEC 60062, marking codes for resistors and capacitors. Standard values of nominal resistance are taken from the E24 and E24 / E96 series for resistors with a tolerance of ± 5 % or ± 1 % respectively. The values of the E24 / E96 series are in accordance with IEC 60063. Yellow and grey are used instead of gold and silver because metal particles in the lacquer could affect high voltage properties.



FUNCTIONAL PERFORMANCE




Derating - Standard Operation

Maximum dissipation (P_{max}) in percentage of rated power as a function of ambient temperature (T_{amb})


PULSE LOADING CAPABILITY

Note

- Maximum allowed peak pulse voltage in accordance with IEC 60065, 14.1.a; 50 discharges from a 1 nF capacitor charged to U_{max} ; 12 discharges/min



HVR25
 $\Delta R = \pm 4.0 \% R$



HVR37
For 5 % tolerance $\Delta R = \pm 4.0 \% R$
For 1 % tolerance $\Delta R = \pm 2.0 \% R$


**TESTS AND REQUIREMENTS**

Essentially all tests are carried out in accordance with IEC 60115-1, category 55 / 155 / 56 (rated temperature range -55 °C to +155 °C; damp heat, long term, 56 days) and along the lines of IEC 60068-2-xx test method. The tests are carried out under standard atmospheric conditions according to IEC 60068-1, 4.3 unless otherwise specified. In some instances deviations from IEC recommendations were necessary for our method of specifying.


| PERFORMANCE | | | | | |
|--|--|---|--|--|--------------------|
| IEC 60115-1 CLAUSE | IEC 60068-2-xx TEST METHOD | TEST | PROCEDURE | REQUIREMENTS PERMISSIBLE CHANGE (δR) | |
| | | | | HVR25 | HVR37 |
| 6.2 | - | Temperature coefficient | Between -55 °C and +155 °C | ± 200 ppm/K | |
| 7.1 | - | Endurance at 70 °C | 1000 h; loaded with P_{70} or U_{max} ; 1.5 h on; 0.5 h off for 5 % tolerance for 1 % tolerance | ± 5 % R ± 1.5 % R | |
| 10.4 | 78 (Cab) | Damp heat, steady state | 56 days; 40 °C; 90 % to 95 % RH loaded with 0.01 P_{70} for 5 % tolerance for 1 % tolerance | ± 5 % R ± 1.5 % R | |
| 10.3 10.3.4.2 10.3.4.3 10.3.4.4 10.3.4.6 | 2 (Bb) 30 (Db) 1 (Ab) 30 (Db) | Climatic sequence Dry heat Damp heat, cyclic Cold Damp heat, (accelerated) remaining cycles | 16 h, 155 °C 24 h; 25 °C to 55 °C 90 % to 100 % RH; 1 cycle 2 h, -55 °C 5 days; 25 °C to 55 °C 90 to 100 % RH | ± 1.5 % R | |
| 10.1 | 14 (Na) | Rapid change of temperature | 30 min at LCT; 30 min at UCT; LCT = -55 °C; UCT = 155 °C; 5 cycles | No visual damage ± 1 % R | |
| 8.1 | - | Short time overload | Room temperature; dissipation 6.25 x P_{70} (voltage not more than 2 x limiting voltage, 10 000 V_{max}); 10 cycles 5 s on and 45 s off for 5 % tolerance for 1 % tolerance | ± 2 % R ± 1 % R | |
| 6.6 | - | Noise | IEC 60195 | Max. 5 $\mu V/V$ | Max. 2.5 $\mu V/V$ |
| 9.5 9.5.4.2 9.5.4.3 9.5.4.4 | 21 (Ua1) 21 (Ub) 21 (Uc) | Robustness of terminations: Tensile all samples Bending half number of samples Torsion other half of samples | Load 10 N; 10 s Load 5 N; 4 x 90° 3 x 360° in opposite direction | No damage ± 1 % R | |
| 9.11 | 6 (Fc) | Vibration | Frequency 10 Hz to 500 Hz; displacement 1.5 mm or acceleration 10 g; 3 directions; total 6 h (3 x 2 h) | ± 1.0 % R | |



| PERFORMANCE | | | | | |
|--------------------|----------------------------|------------------------------|--|--|-------|
| IEC 60115-1 CLAUSE | IEC 60068-2-xx TEST METHOD | TEST | PROCEDURE | REQUIREMENTS PERMISSIBLE CHANGE (δR) | |
| | | | | HVR25 | HVR37 |
| 11.1 | 20 (Ta) | Solderability (after aging) | 2 s; 235 °C: Solder bath method; SnPb40 3 s; 245 °C: Solder bath method; SnAg3Cu0.5 | Good tinning ($\geq 95\%$ covered); no visible damage | |
| 11.2 | 20 (Tb) | Resistance to soldering heat | Thermal shock: 10 s; 260 °C; 3 mm from body | $\pm 1\% R$ | |
| 11.3.2.3 | 45 (XA) | Component solvent resistance | Isopropyl alcohol | No visible damage | |
| 12.1 | - | Insulation resistance | $U = 500 V_{DC}$ during 1 min, V-block method | R_{ins} min. 104 M Ω | |
| 12.2 | - | Voltage proof on insulation | $U_{RMS} = 700 V$ during 1 min, V-block method | No flashover or breakdown | |

DIMENSIONS

| DIMENSIONS - Resistor types, mass and relevant physical dimensions | | | | | | |
|--|-----------------|-----------------|-----------------|----------------------|------------------|-----------|
| TYPE | L_1 max. (mm) | L_2 max. (mm) | $D_{max.}$ (mm) | $\varnothing d$ (mm) | A (mm) | MASS (mg) |
| HVR25 | 6.5 | 7.5 | 2.5 | 0.58 ± 0.05 | $52.5 + 2 / - 1$ | 220 |
| HVR37 | 10 | 12 | 4 | 0.70 ± 0.03 | $52.5 + 2 / - 1$ | 500 |

**PRODUCTS WITH RADIAL LEADS (HVR25)**

| DIMENSIONS - Radial taping | | | | |
|----------------------------|---|-------|-----------|------|
| SYMBOL | PARAMETER | VALUE | TOLERANCE | UNIT |
| P | Pitch of components | 12.7 | ± 1.0 | mm |
| P_0 | Feed-hole pitch | 12.7 | ± 0.2 | mm |
| P_1 | Feed-hole centre to lead at topside at the tape | 3.85 | ± 0.5 | mm |
| P_2 | Feed-hole center to body center | 6.35 | ± 1.0 | mm |
| F | Lead-to-lead distance | 4.8 | +0.7 / -0 | mm |
| W | Tape width | 18.0 | ± 0.5 | mm |
| W_0 | Minimum hold down tape width | 5.5 | - | mm |
| H_1 | Component height | 29 | Max. | mm |
| H_0 | Lead wire clinch height | 16.5 | 0.5 | mm |
| H | Height of component from tape center | 19.5 | ± 1 | mm |
| D_0 | Feed-hole diameter | 4.0 | ± 0.2 | mm |
| L | Maximum length of snapped lead | 11.0 | - | mm |
| L_1 | Minimum lead wire (tape portion) shortest lead | 2.5 | - | mm |

Note

- Please refer document number 28721 "Packaging" for more detail

**12NC INFORMATION FOR HISTORICAL CODING REFERENCE ONLY**

- The resistors have a 12 digit ordering code starting with 2306
- The next 4 or 5 digits indicate the resistor type and packaging
- For 5 % tolerance the last 3 digits indicate the resistance value:
 - The first 2 digits indicate the resistance value
 - The last digit indicates the resistance decade in accordance with table
- For 1 % tolerance the last 4 digits indicate the resistance value:
 - The first 3 digits indicate the resistance value
 - The last digit indicates the resistance decade in accordance with table

Last Digit of 12NC Indicating Resistance Decade

| RESISTANCE DECADE (5 %) | RESISTANCE DECADE (1 %) | LAST DIGIT |
|----------------------------------|----------------------------------|------------|
| 100 k Ω to 910 k Ω | 100 k Ω to 976 k Ω | 4 |
| 1 M Ω to 9.1 M Ω | 1 M Ω to 9.76 M Ω | 5 |
| = 10 M Ω | = 10 M Ω | 6 |

12NC Example

HVR25, 150 k Ω , \pm 5 %, ammpack 1000 pieces is **2306 241 13154**

| 12NC - resistor type and packaging | | | | | | |
|---|------------|-----------|-----------------------|------------|------------|-------------------|
| DESCRIPTION | | | 2306 | | | |
| | | | BANDOLIER IN AMMOPACK | | | BANDOLIER ON REEL |
| TYPE | TAPE WIDTH | TOLERANCE | RADIAL TAPED | 1000 UNITS | 5000 UNITS | 5000 UNITS |
| | | | 4000 UNITS | | | |
| HVR25 | 52.5 | \pm 5 % | 241 36... | 241 13... | 241 53... | 241 23... |
| | | \pm 1 % | 241 0.... | 241 8.... | 241 7.... | 241 6.... |
| HVR37 | 52.5 | \pm 5 % | - | 242 13... | - | 242 23... |
| | | \pm 1 % | - | 242 8.... | - | 242 6.... |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.