

# MKP383436025JC02R0 Datasheet



<https://www.DiGi-Electronics.com>

|                              |  |
|------------------------------|--|
| DiGi Electronics Part Number | MKP383436025JC02R0-DG  |
| Manufacturer                 | <a href="#">Vishay Beyschlag/Draloric/BC Components</a>                      |
| Manufacturer Product Number  | MKP383436025JC02R0   |
| Description                  | CAP FILM 0.36UF 5% 250VDC RADIAL   |
| Detailed Description         | 0.36 $\mu$ F Film Capacitor 125V 250V Polypropylene (P P), Metallized Radial |

This model MKP383436025JC02R0 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

MKP383436025JC02R0

Series:

MKP383

Capacitance:

0.36  $\mu$ F

Voltage Rating - AC:

125V

Dielectric Material:

Polypropylene (PP), Metallized

Mounting Type:

Through Hole

Size / Dimension:

0.689" L x 0.394" W (17.50mm x 10.00mm)

Termination:

PC Pins

Applications:

High Pulse, DV/DT

Features:

-

Manufacturer:

Vishay Beyschlag/Draloric/BC Components

Product Status:

Active

Tolerance:

$\pm$ 5%

Voltage Rating - DC:

250V

Operating Temperature:

-55°C ~ 105°C

Package / Case:

Radial

Height - Seated (Max):

0.728" (18.50mm)

Lead Spacing:

0.295" (7.50mm)

Ratings:

-

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

ECCN:

EAR99

Moisture Sensitivity Level (MSL):

1 (Unlimited)


HTSUS:

8532.25.0070


[www.vishay.com](http://www.vishay.com)
**MKP383**

Vishay BCcomponents

## AC and Pulse Double Metallized Polypropylene Film Capacitors MKP Radial Potted Type

**FEATURES**

- 7.5 mm to 37.5 mm lead pitch; 7.5 mm bent back pitch
- Low contact resistance
- Low loss dielectric
- Small dimensions for high density packaging
- Supplied loose in box and taped on reel or ammopack
- Mounting: radial
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

**APPLICATIONS**

- Where steep pulses occur e.g. SMPS (switch mode power supplies)
- Electronic lighting e.g. ballast
- Motor control circuits
- S-correction
- For flyback applications please use 1400 V series

**QUICK REFERENCE DATA**

|   |  |
|---|--|
| Capacitance range (E24 series)                  | 0.00047 $\mu$ F to 4.7 $\mu$ F   |
| Capacitance tolerance                           | $\pm$ 5 %  |
| Climatic testing class according to IEC 60068-1 | 55/105/56  |
| Rated DC temperature                            | 85 °C  |
| Rated AC temperature                            | 105 °C   |
| Maximum application temperature                 | 105 °C   |
| Reference specifications                        | IEC 60384-17   |
| Dielectric                                      | Polypropylene film   |
| Electrodes                                      | Metallized   |
| Construction                                    | Mono and internal serial construction  |
| Encapsulation                                   | Flame retardant plastic case and epoxy resin<br>UL-class 94 V-0  |
| Leads   | Tinned wire  |
| Marking   | C-value; tolerance; rated voltage; sub-class; manufacturer's type; code for dielectric material; manufacturer location; manufacturer's logo; year and week |

**Note**


- For more detailed data and test requirements, contact [dc-film@vishay.com](mailto:dc-film@vishay.com)

**VOLTAGE RATINGS**

|                            |     |     |     |      |      |      |      |      |
|----------------------------|-----|-----|-----|------|------|------|------|------|
| Rated DC voltage           | 250 | 400 | 630 | 1000 | 1400 | 1600 | 2000 | 2500 |
| Rated AC voltage           | 125 | 200 | 220 | 350  | 500  | 550  | 700  | 900  |
| Rated peak to peak voltage | 350 | 560 | 630 | 1000 | 1400 | 1600 | 2000 | 2500 |



**COMPOSITION OF CATALOG NUMBER**



**Notes**


- For detailed tape specifications refer to packaging information [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139)
- <sup>(1)</sup> Packaging will be bulk for all capacitors with pitch ≤ 15 mm and such with long leads (> 5 mm). Capacitors with short leads up to 5 mm and pitch > 15 mm will be in tray and asking code will be "T".


[www.vishay.com](http://www.vishay.com)
**MKP383**

Vishay BCcomponents

**ELECTRICAL DATA** (For Detailed Ratings go to [www.vishay.com/doc?28183](http://www.vishay.com/doc?28183))

| $U_{RDC}$<br>(V) | CAP.<br>( $\mu$ F) |
|------------------|--------------------|
| 250              | 0.0068 min.        |
|                  | 2.7 max.           |
| 400              | 0.0047 min.        |
|                  | 1.5 max.           |
| 630              | 0.00047 min.       |
|                  | 4.7 max.           |
| 1000             | 0.0043 min.        |
|                  | 1.8 max.           |
| 1400             | 0.0022 min.        |
|                  | 0.68 max.          |
| 1600             | 0.0027 min.        |
|                  | 0.56 max.          |
| 2000             | 0.0010 min.        |
|                  | 0.56 max.          |
| 2500             | 0.0010 min.        |
|                  | 0.3 max.           |

**DIMENSIONS** in millimeters**Note**

- (1)  $|F-F'| < 0.3$  mm  
 $F = 7.5$  mm + 0.6 mm / - 0.1 mm  
 $\text{Ø dt} \pm 10$  % of standard diameter specified



## MOUNTING

### Normal Use

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting on printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to packaging information [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139)

### Specific Method of Mounting to Withstand Vibration and Shock

In order to withstand vibration and shock tests, it must be ensured that the stand-off pips are in good contact with the printed-circuit board:

- For original pitch = 15 mm the capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

### Space Requirements on Printed-Circuit Board


The maximum space for length ( $l_{max.}$ ), width ( $w_{max.}$ ) and height ( $h_{max.}$ ) of film capacitors to take in account on the printed circuit board is shown in the drawings.

For products with pitch  $\leq 15$  mm,  $\Delta w = \Delta l = 0.3$  mm and  $\Delta h = 0.1$  mm

For products with  $15$  mm  $<$  pitch  $\leq 27.5$  mm,  $\Delta w = \Delta l = 0.5$  mm and  $\Delta h = 0.1$  mm

For products with pitch = 37.5 mm,  $\Delta w = \Delta l = 0.7$  mm and  $\Delta h = 0.5$  mm

Eccentricity as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.



## SOLDERING CONDITIONS

For general soldering conditions and wave soldering profile we refer to the document "Soldering Guidelines for Film Capacitors": [www.vishay.com/doc?28171](http://www.vishay.com/doc?28171)

## STORAGE TEMPERATURE

$T_{stg} = -25$  °C to  $+35$  °C with RH maximum 75 % without condensation


## RATINGS AND CHARACTERISTICS REFERENCE CONDITIONS

Unless otherwise specified, all electrical values apply to an ambient free temperature of  $23$  °C  $\pm 1$  °C, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50$  %  $\pm 2$  %.


For reference testing, a conditioning period shall be applied over  $96$  h  $\pm 4$  h by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.




**CHARACTERISTICS**




Capacitance as a function of ambient temperature (typical curve) (1 kHz)




Impedance as a function of frequency (typical curve)




Max. DC and AC voltage as a function of temperature




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency




Max. RMS voltage as a function of frequency



Insulation resistance as a function of the ambient temperature



Maximum allowed component temperature rise ( $\Delta T$ ) as a function of the ambient temperature ( $T_{amb}$ )



Tangent of loss angle as a function of frequency (typical curve)

|  |   |  |  |
|--|---|--|--|
| <p><b>250 V:</b><br/>                     0.0068 ≤ C ≤ 0.091 μF, curve 8<br/>                     0.1 &lt; C ≤ 0.15 μF, curve 9<br/>                     0.15 &lt; C ≤ 0.22 μF, curve 10<br/>                     0.22 &lt; C ≤ 0.27 μF, curve 11<br/>                     0.27 &lt; C ≤ 0.33 μF, curve 12<br/>                     0.33 &lt; C ≤ 0.56 μF, curve 15<br/>                     0.56 &lt; C ≤ 0.82 μF, curve 16<br/>                     0.82 &lt; C ≤ 1.2 μF, curve 18<br/>                     1.2 &lt; C ≤ 1.6 μF, curve 19<br/>                     1.6 &lt; C ≤ 2.7 μF, curve 20</p> | <p><b>400 V:</b><br/>                     0.0047 &lt; C ≤ 0.047 μF, curve 5<br/>                     0.047 &lt; C ≤ 0.068 μF, curve 6<br/>                     0.068 &lt; C ≤ 0.1 μF, curve 7<br/>                     0.1 &lt; C ≤ 0.2 μF, curve 8<br/>                     0.2 &lt; C ≤ 0.24 μF, curve 12<br/>                     0.24 &lt; C ≤ 0.36 μF, curve 13<br/>                     0.36 &lt; C ≤ 0.43 μF, curve 14<br/>                     0.43 &lt; C ≤ 0.56 μF, curve 16<br/>                     0.56 &lt; C ≤ 1.1 μF, curve 17<br/>                     1.1 &lt; C ≤ 1.5 μF, curve 18</p> | <p><b>630 V:</b><br/>                     0.00047 &lt; C ≤ 0.033 μF, curve 4<br/>                     0.033 &lt; C ≤ 0.068 μF, curve 5<br/>                     0.068 &lt; C ≤ 0.1 μF, curve 6<br/>                     0.1 &lt; C ≤ 0.15 μF, curve 7<br/>                     0.15 &lt; C ≤ 0.22 μF, curve 11<br/>                     0.22 &lt; C ≤ 0.27 μF, curve 12<br/>                     0.27 &lt; C ≤ 0.33 μF, curve 15<br/>                     0.33 &lt; C ≤ 0.82 μF, curve 16<br/>                     0.82 &lt; C ≤ 1 μF, curve 18<br/>                     1 &lt; C ≤ 4.7 μF, curve 21</p> | <p><b>1000 V:</b><br/>                     C ≤ 0.01 μF, curve 2<br/>                     0.011 &lt; C ≤ 0.027 μF, curve 3<br/>                     0.027 &lt; C ≤ 0.047 μF, curve 4<br/>                     0.047 &lt; C ≤ 0.062 μF, curve 5<br/>                     0.062 &lt; C ≤ 0.075 μF, curve 6<br/>                     0.075 &lt; C ≤ 0.1 μF, curve 7<br/>                     0.1 &lt; C ≤ 0.15 μF, curve 8<br/>                     0.15 &lt; C ≤ 0.22 μF, curve 9<br/>                     0.22 &lt; C ≤ 0.3 μF, curve 10<br/>                     0.3 &lt; C ≤ 1 μF, curve 16<br/>                     1 &lt; C ≤ 1.8 μF, curve 19</p> |
| <p><b>1400 V:</b><br/>                     C ≤ 0.0047 μF, curve 1<br/>                     0.0051 &lt; C ≤ 0.016 μF, curve 2<br/>                     0.016 &lt; C ≤ 0.033 μF, curve 3<br/>                     0.033 &lt; C ≤ 0.051 μF, curve 4<br/>                     0.051 &lt; C ≤ 0.068 μF, curve 5<br/>                     0.068 &lt; C ≤ 0.082 μF, curve 6<br/>                     0.082 &lt; C ≤ 0.2 μF, curve 7<br/>                     0.2 &lt; C ≤ 0.68 μF, curve 14</p>   | <p><b>1600 V:</b><br/>                     C ≤ 0.0047 μF, curve 3<br/>                     0.0051 &lt; C ≤ 0.0091 μF, curve 4<br/>                     0.0091 &lt; C ≤ 0.068 μF, curve 5<br/>                     0.068 &lt; C ≤ 0.01 μF, curve 6<br/>                     0.01 &lt; C ≤ 0.16 μF, curve 7<br/>                     0.16 &lt; C ≤ 0.56 μF, curve 14</p>  | <p><b>2000 V:</b><br/>                     C ≤ 0.0047 μF, curve 2<br/>                     0.0051 &lt; C ≤ 0.033 μF, curve 3<br/>                     0.033 &lt; C ≤ 0.091 μF, curve 4<br/>                     0.091 &lt; C ≤ 0.56 μF, curve 14</p>   | <p><b>2500 V:</b><br/>                     C ≤ 0.0047 μF, curve 1<br/>                     0.0051 &lt; C ≤ 0.015 μF, curve 2<br/>                     0.015 &lt; C ≤ 0.091 μF, curve 3<br/>                     0.091 &lt; C ≤ 0.33 μF, curve 12</p>   |



### HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C

| W <sub>max.</sub> (mm) | HEAT CONDUCTIVITY (mW/°C) |             |             |               |               |               |
|------------------------|---------------------------|-------------|-------------|---------------|---------------|---------------|
|                        | PITCH 7.5 mm              | PITCH 10 mm | PITCH 15 mm | PITCH 22.5 mm | PITCH 27.5 mm | PITCH 37.5 mm |
| 3.0                    | 4                         | -           | -           | -             | -             | -             |
| 4.0                    | 5                         | 6.5         | -           | -             | -             | -             |
| 4.5                    | 5                         | -           | -           | -             | -             | -             |
| 5.0                    | 6                         | 7.5         | 10          | -             | -             | -             |
| 6.0                    | -                         | 9.0         | 11          | 19            | -             | -             |
| 7.0                    | -                         | -           | 12          | 21            | -             | -             |
| 8.5                    | -                         | -           | 16          | 25            | -             | -             |
| 9.0                    | -                         | -           | -           | -             | 31            | -             |
| 10.0                   | -                         | -           | 18          | 28            | -             | -             |
| 11.0                   | -                         | -           | -           | -             | 36            | -             |
| 13.0                   | -                         | -           | -           | -             | 42            | -             |
| 15.0                   | -                         | -           | -           | -             | 48            | -             |
| 18.0                   | -                         | -           | -           | -             | 57            | -             |
| 18.5                   | -                         | -           | -           | -             | -             | 89            |
| 21.0                   | -                         | -           | -           | -             | 68            | -             |
| 21.5                   | -                         | -           | -           | -             | -             | 102           |
| 24.0                   | -                         | -           | -           | -             | -             | 116           |
| 30.0                   | -                         | -           | -           | -             | -             | 134           |

### POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free air ambient temperature.


The power dissipation can be calculated according type detail specification "HQN-384-01/101: Technical information film capacitors with the typical tgδ of the curves."

The component temperature rise ( $\Delta T$ ) can be measured (see section "Measuring the component temperature" for more details) or calculated by  $\Delta T = P/G$ :

- $\Delta T$  = component temperature rise (°C)
- P = power dissipation of the component (mW)
- G = heat conductivity of the component (mW/°C)

### MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded ( $T_{amb}$ ) and maximum loaded condition ( $T_c$ ).

The temperature rise is given by  $\Delta T = T_c - T_{amb}$ .

To avoid radiation or convection, the capacitor should be tested in a wind-free box.



## APPLICATION NOTE AND LIMITING CONDITIONS

For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: [dc-film@vishay.com](mailto:dc-film@vishay.com)

These capacitors are not suitable for mains applications as across-the-line capacitors without additional protection, as described hereunder. These mains applications are strictly regulated in safety standards and therefore electromagnetic interference suppression capacitors conforming the standards must be used.

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage ( $U_p$ ) shall not be greater than the rated DC voltage ( $U_{RDC}$ )
2. The peak-to-peak voltage ( $U_{p-p}$ ) shall not be greater than the maximum ( $U_{p-p}$ ) to avoid the ionization inception level
3. The voltage pulse slope ( $dU/dt$ ) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by  $U_{RDC}$  and divided by the applied voltage.

For all other pulses following equation must be fulfilled:

$$2 \times \int_0^T \left( \frac{dU}{dt} \right)^2 \times dt < U_{RDC} \times \left( \frac{dU}{dt} \right)_{\text{rated}}$$

T is the pulse duration

4. The maximum component surface temperature rise must be lower than the limits (see graph max. allowed component temperature rise).
5. Since in circuits used at voltages over 280 V peak-to-peak the risk for an intrinsically active flammability after a capacitor breakdown (short circuit) increases, it is recommended that the power to the component is limited to 100 times the values mentioned in the table: "Heat Conductivity"
6. When using these capacitors as across-the-line capacitor in the input filter for mains applications or as series connected with an impedance to the mains the applicant must guarantee that the following conditions are fulfilled in any case (spikes and surge voltages from the mains included).

| VOLTAGE CONDITIONS FOR 6 ABOVE                |   |  |
|---|---|--|
| ALLOWED VOLTAGES                              | $T_{\text{amb}} \leq 85 \text{ }^\circ\text{C}$ | $85 \text{ }^\circ\text{C} < T_{\text{amb}} \leq 105 \text{ }^\circ\text{C}$ |
| Maximum continuous RMS voltage                | $U_{RAC}$                                       | $U_{RAC}$  |
| Maximum temperature RMS-over voltage (< 24 h) | $1.25 \times U_{RAC}$                           | $1.25 \times U_{RAC}$  |
| Maximum peak voltage ( $V_{o-p}$ ) (< 2 s)    | $1.6 \times U_{RDC}$                            | $1.1 \times U_{RDC}$   |

## EXAMPLE

$C = 4n7 - 1600 \text{ V}$  used for the voltage signal shown in next drawing.

$U_{p-p} = 1000 \text{ V}$ ;  $U_p = 900 \text{ V}$ ;  $T_1 = 12 \text{ } \mu\text{s}$ ;  $T_2 = 64 \text{ } \mu\text{s}$ ;  $T_3 = 4 \text{ } \mu\text{s}$


The ambient temperature is  $80 \text{ }^\circ\text{C}$ . In case of failure, the oscillation is blocked.

Checking conditions:

1. The peak voltage  $U_p = 900 \text{ V}$  is lower than  $1600 \text{ V}_{DC}$
2. The peak-to-peak voltage  $1000 \text{ V}$  is lower than  $2\sqrt{2} \times 550 \text{ V}_{AC} = 1600 \text{ V}_{p-p}$
3. The voltage pulse slope ( $dU/dt$ ) =  $1000 \text{ V}/4 \text{ } \mu\text{s} = 250 \text{ V}/\mu\text{s}$ . This is lower than  $8000 \text{ V}/\mu\text{s}$  (see specific reference data for each version).
4. The dissipated power is  $35 \text{ mW}$  as calculated with fourier terms and typical  $\text{tg}\delta$ .  
The temperature rise for  $w_{\text{max.}} = 6.0 \text{ mm}$  and pitch =  $15 \text{ mm}$  will be  $35 \text{ mW} / 11 \text{ mW}/^\circ\text{C} = 3.2 \text{ }^\circ\text{C}$   
This is lower than  $10 \text{ }^\circ\text{C}$  temperature rise at  $80 \text{ }^\circ\text{C}$ , according graph.
5. Oscillation is blocked
6. Not applicable



## VOLTAGE SIGNAL



## INSPECTION REQUIREMENTS

### General Notes

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-17 and Specific Reference Data”.

| GROUP C INSPECTION REQUIREMENTS              |   |  |
|--|---|--|
| SUB-CLAUSE NUMBER AND TEST                   | CONDITIONS  | PERFORMANCE REQUIREMENTS   |
| SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1 |   |  |
| 4.1 Dimensions (detail)                      |   | As specified in chapters “General Data” of this specification  |
| 4.3.1 Initial measurements                   | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 100 kHz or<br>for $C > 1 \mu\text{F}$ at 10 kHz                        |  |
| 4.3 Robustness of terminations               | Tensile: load 10 N; 10 s<br>Bending: load 5 N; $4 \times 90^\circ$  | No visible damage  |
| 4.4 Resistance to soldering heat             | Method: 1A<br>Solder bath: $280 \text{ }^\circ\text{C} \pm 5 \text{ }^\circ\text{C}$<br>Duration: 10 s  |  |
| 4.14 Component solvent resistance            | Isopropylalcohol at room temperature<br>Method: 2<br>Immersion time: $5 \text{ min} \pm 0.5 \text{ min}$<br>Recovery time: min. 1 h, max. 2 h |  |
| 4.4.2 Final measurements                     | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle  | No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 1 \%$ of the value measured initially<br><br>Increase of $\tan \delta$ :<br>$\leq 0.0005$ for: $C \leq 100 \text{ nF}$ or<br>$\leq 0.001$ for: $100 \text{ nF} < C \leq 470 \text{ nF}$ or<br>$\leq 0.0015$ for: $C > 470 \text{ nF}$<br>Compared to values measured in 4.3.1 |



| GROUP C INSPECTION REQUIREMENTS                    |   |   |
|--|---|---|
| SUB-CLAUSE NUMBER AND TEST                         | CONDITIONS  | PERFORMANCE REQUIREMENTS  |
| SUB-GROUP C1B OTHER PART OF SAMPLE OF SUB-GROUP C1 |   |   |
| 4.6.1 Initial measurements                         | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 100 kHz or<br>for $C > 1 \mu\text{F}$ at 10 kHz  |   |
| 4.15 Solvent resistance of the marking             | Isopropylalcohol at room temperature<br>Method: 1<br>Rubbing material: cotton wool<br>Immersion time: 5.0 min $\pm$ 0.5 min   | No visible damage<br>Legible marking  |
| 4.6 Rapid change of temperature                    | $\theta\text{A} = -55 \text{ }^\circ\text{C}$<br>$\theta\text{B} = +105 \text{ }^\circ\text{C}$<br>5 cycles<br>Duration $t = 30 \text{ min}$  |   |
| 4.7 Vibration                                      | Visual examination<br>Mounting: see section "Mounting" for more information<br>Procedure B4<br>Frequency range: 10 Hz to 55 Hz<br>Amplitude: 0.75 mm or<br>Acceleration 98 m/s <sup>2</sup><br>(whichever is less severe)<br>Total duration 6 h | No visible damage   |
| 4.7.2 Final inspection                             | Visual examination  | No visible damage   |
| 4.9 Shock  | Mounting: see section "Mounting" for more information<br>Pulse shape: half sine<br>Acceleration: 490 m/s <sup>2</sup><br>Duration of pulse: 11 ms   |   |
| 4.9.3 Final measurements                           | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance   | No visible damage<br><br>$ \Delta C/C  \leq 2 \%$ for pitch < 10 mm<br>$ \Delta C/C  \leq 1 \%$ for pitch > 10 mm of the value measured in 4.6.1<br><br>Increase of $\tan \delta$ :<br>$\leq 0.0005$ for: $C \leq 100 \text{ nF}$ or<br>$\leq 0.001$ for: $100 \text{ nF} < C \leq 470 \text{ nF}$ or<br>$\leq 0.0015$ for: $C > 470 \text{ nF}$<br>Compared to values measured in 4.6.1<br><br>As specified in section "Insulation Resistance" of this specification |



| GROUP C INSPECTION REQUIREMENTS  |  |  |
|--|--|--|
| SUB-CLAUSE NUMBER AND TEST   | CONDITIONS   | PERFORMANCE REQUIREMENTS   |
| <b>SUB-GROUP C1<br/>COMBINED SAMPLE OF SPECIMENS OF<br/>SUB-GROUPS C1A and C1B</b> |  |  |
| 4.10 Climatic sequence   |  |  |
| 4.10.2 Dry heat  | Temperature: +105 °C<br>Duration: 16 h   |  |
| 4.10.3 Damp heat cyclic<br>Test Db, first cycle                                    |  |  |
| 4.10.4 Cold  | Temperature: -55 °C<br>Duration: 2 h   |  |
| 4.10.6 Damp heat cyclic<br>Test Db, remaining cycles                               |  |  |
| 4.10.6.2 Final measurements  | Voltage proof = $U_{RDC}$ for 1 min within 15 min<br>after removal from testchamber<br><br>Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance | No breakdown or flash-over<br><br>No visible damage<br>Legible marking<br><br>For original pitch = 22.5 mm and 37.5 mm:<br>$ \Delta C/C  \leq 2\%$ or<br>for original pitch $\leq 15$ mm:<br>$ \Delta C/C  \leq 3\%$ of the value measured in<br>4.4.2 or 4.9.3<br><br>Increase of $\tan \delta$ :<br>$\leq 0.0005$ for: $C \leq 100$ nF or<br>$\leq 0.001$ for: $100$ nF $< C \leq 470$ nF or<br>$\leq 0.0015$ for: $C > 470$ nF<br>Compared to values measured in<br>4.3.1 or 4.6.1<br><br>$\geq 50\%$ of values specified in section<br>"Insulation Resistance" of this specification |
| <b>SUB-GROUP C2</b>  |  |  |
| 4.11 Damp heat steady state  | 56 days, 40 °C, 90 % to 95 % RH<br>no load   |  |
| 4.11.1 Initial measurements  | Capacitance<br>Tangent of loss angle at 1 kHz  |  |
| 4.11.3 Final measurements  | Voltage proof = $U_{RDC}$ for 1 min within 15 min<br>after removal from testchamber<br><br>Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance | No breakdown or flash-over<br><br>No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 1\%$ of the value measured in 4.11.1<br><br>Increase of $\tan \delta$ :<br>$\leq 0.0005$ for: $C \leq 100$ nF or<br>$\leq 0.001$ for: $100$ nF $< C \leq 470$ nF or<br>$\leq 0.0015$ for: $C > 470$ nF<br>Compared to values measured in 4.11.1<br><br>$\geq 50\%$ of values specified in section<br>"Insulation Resistance" of this specification  |



| GROUP C INSPECTION REQUIREMENTS  |  |   |
|--|--|---|
| SUB-CLAUSE NUMBER AND TEST   | CONDITIONS   | PERFORMANCE REQUIREMENTS  |
| <b>SUB-GROUP C3A</b>   |  |   |
| 4.12.1 Endurance test at 50 Hz alternating voltage                                     | Duration: 2000 h   |   |
| 4.12.1.1 Initial measurements  | Voltage:<br>1.25 x U <sub>RAC</sub> at 105 °C<br>Capacitance<br>Tangent of loss angle:<br>for C ≤ 1 μF at 100 kHz or<br>for C > 1 μF at 10 kHz |   |
| 4.12.1.3 Final measurements  | Visual examination   | No visible damage<br>Legible marking  |
|  | Capacitance  | $ \Delta C/C  \leq 5\%$ compared to values measured in 4.12.1.1   |
|  | Tangent of loss angle  | Increase of tan δ:<br>≤ 0.0005 for: C ≤ 100 nF or<br>≤ 0.001 for: 100 nF < C ≤ 470 nF or<br>≤ 0.0015 for: C > 470 nF<br>Compared to values measured in 4.12.1.1 |
|  | Insulation resistance  | ≥ 50 % of values specified in section "Insulation Resistance" of this specification   |
| <b>SUB-GROUP C4</b>  |  |   |
| 4.2.6 Temperature characteristics<br>Initial measurements<br>Intermediate measurements | Capacitance<br>Capacitance at -55 °C<br>Capacitance at +20 °C<br>Capacitance at +105 °C  | For -55 °C to +20 °C:<br>+1 % ≤ $ \Delta C/C $ ≤ 3.75 % or<br>for 20 °C to 105 °C:<br>-6 % ≤ $ \Delta C/C $ ≤ 0 %   |
| Final measurements   | Capacitance  | As specified in section "Capacitance" of this specification.  |
|  | Insulation resistance  | As specified in section "Insulation Resistance" of this specification   |
| 4.13 Charge and discharge  | 10 000 cycles<br>Charged to U <sub>RDC</sub><br>Discharge resistance:<br>$R = \frac{U_{RDC}}{5 \times C \times (dU/dt)}$                       |   |
| 4.13.1 Initial measurements  | Capacitance<br>Tangent of loss angle:<br>for C ≤ 1 μF at 100 kHz or<br>for C > 1 μF at 10 kHz  |   |
| 4.13.3 Final measurements  | Capacitance  | $ \Delta C/C  \leq 1\%$ compared to values measured in 4.13.1   |
|  | Tangent of loss angle  | Increase of tan δ:<br>≤ 0.0005 for: C ≤ 100 nF or<br>≤ 0.001 for: 100 nF < C ≤ 470 nF or<br>≤ 0.0015 for: C > 470 nF<br>Compared to values measured in 4.13.1   |
|  | Insulation resistance  | ≥ 50 % of values specified in section "Insulation Resistance" of this specification   |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.