

# P3002AB60 Datasheet



<https://www.DiGi-Electronics.com>

|                              |  |
|------------------------------|--|
| DiGi Electronics Part Number | P3002AB60-DG                                       |
| Manufacturer                 | <a href="#">Littelfuse Inc.</a>                    |
| Manufacturer Product Number  | P3002AB60  |
| Description                  | THYRISTOR 140V/280V 250A TO220-3                   |
| Detailed Description         | 140V, 280V Off-State 250 A Ipp TVS Thyristor 3-SIP |

This model P3002AB60 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

P3002AB60

Series:

SIDACtor®

Voltage - Breakover:

180V, 360V

Voltage - On State:

4 V

Current - Peak Pulse (10/1000µs):

80 A

Number of Elements:

2

Mounting Type:

Through Hole

Supplier Device Package:

TO-220 Modified

Manufacturer:

Littelfuse Inc.

Product Status:

Obsolete

Voltage - Off State:

140V, 280V

Current - Peak Pulse (8/20µs):

250 A

Current - Hold (Ih):

150 mA

Capacitance:

55pF, 95pF

Package / Case:

3-SIP

## Environmental & Export classification

RoHS Status:

RoHS non-compliant

ECCN:

EAR99

Moisture Sensitivity Level (MSL):

1 (Unlimited)

HTSUS:

8541.30.0080

# Pxxx2AxL Series

## Two-Chip SIDACtor® - Modified TO-220



### Description

The Pxxx2AxL Series Modified TO-220 Two-Chip SIDACtor® are designed to protect baseband equipment from damaging overvoltage transients.

The series provides a robust peak surge current capability that enables voice through DS-1 equipment to comply with various global regulatory standards.

### Features & Benefits

- Low voltage overshoot
- Low on-state voltage
- Does not degrade surge capability after multiple surge events within limit.
- Modified TO-220 Package
- Fails short circuit when surged in excess of ratings
- Single-port protection
- Lead forms available
- RoHS Compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/JEDEC J-STD-609A.01)

### Additional Information



Resources




Accessories




Samples

### Pinout Designation



### Schematic Symbol



### Applicable Global Standards

- TIA-968-A
- TIA-968-B
- ITU K.20/21 Enhanced Level\*
- ITU K.20/21 Basic Level
- GR 1089 Inter-building\*
- GR 1089 Intra-building
- IEC 61000-4-5 2nd edition
- YD/T 1082
- YD/T 993
- YD/T 950

\*A/B-rated parts require series resistance

### Agency Approvals

| Agency | Agency File Number |
|--------|--------------------|
|        | E133083            |

### Electrical Characteristics

| Part Number | Marking | $V_{DRM}$          | $V_s$           | $V_{DRM}$          | $V_s$           | $V_T$         | $I_H$ | $I_s$  | $I_T$  | Capacitance                  |        |  |
|-------------|---------|--------------------|-----------------|--------------------|-----------------|---------------|-------|--------|--------|------------------------------|--------|--|
|             |         | @ $I_{DRM}=5\mu A$ | @ 100V/ $\mu s$ | @ $I_{DRM}=5\mu A$ | @ 100V/ $\mu s$ | @ $I_T=2.2 A$ |       |        |        | @ 1MHz, 2V bias              |        |  |
|             |         | V min              | V max           | V min              | V max           | V max         |       |        |        | pF min                       | pf max |  |
|             |         | Pins 1-2, 3-2      |                 | Pins 1-3           |                 | Pins 1-2, 3-2 |       | mA min | mA max | A max                        |        |  |
| P0602AALxx  | P0602AA | 25                 | 40              | 50                 | 80              | 4             | 50    | 800    | 2.2    | See Capacitance Values Table |        |  |
| P1402AALxx  | P1402AA | 58                 | 77              | 116                | 154             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P1602AALxx  | P1602AA | 65                 | 95              | 130                | 190             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P2202AALxx  | P2202AA | 90                 | 130             | 180                | 260             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P2702AALxx  | P2702AA | 120                | 160             | 240                | 320             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P3002AALxx  | P3002AA | 140                | 180             | 280                | 360             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P3602AALxx  | P3602AA | 170                | 220             | 340                | 440             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P4202AALxx  | P4202AA | 190                | 250             | 380                | 500             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P4802AALxx  | P4802AA | 220                | 300             | 440                | 600             | 4             | 150   | 800    | 2.2    |                              |        |  |
| P6002AALxx  | P6002AA | 275                | 350             | 550                | 700             | 4             | 150   | 800    | 2.2    |                              |        |  |

Table continues on next page.

# Pxxx2AxL Series

## Two-Chip SIDACtor® - Modified TO-220

### Electrical Characteristics (continued)

| Part Number | Marking | $V_{DRM}$<br>@ $I_{DRM}=5\mu A$ | $V_S$<br>@ 100V/ $\mu s$ | $V_{DRM}$<br>@ $I_{DRM}=5\mu A$ | $V_S$<br>@ 100V/ $\mu s$ | $V_T$<br>@ $I_T=2.2 A$ | $I_H$  | $I_S$  | $I_T$ | Capacitance                        |
|-------------|---------|---------------------------------|--------------------------|---------------------------------|--------------------------|------------------------|--------|--------|-------|------------------------------------|
|             |         | V min                           | V max                    | V min                           | V max                    | V max                  | mA min | mA max | A max |                                    |
|             |         | Pins 1-2, 3-2                   |                          | Pins 1-3                        |                          | Pins 1-2, 3-2          |        |        |       |                                    |
| P0602ABLxx  | P0602AB | 25                              | 40                       | 50                              | 80                       | 4                      | 50     | 800    | 2.2   | See<br>Capacitance<br>Values Table |
| P1402ABLxx  | P1402AB | 58                              | 77                       | 116                             | 154                      | 4                      | 150    | 800    | 2.2   |                                    |
| P1602ABLxx  | P1602AB | 65                              | 95                       | 130                             | 190                      | 4                      | 150    | 800    | 2.2   |                                    |
| P2202ABLxx  | P2202AB | 90                              | 130                      | 180                             | 260                      | 4                      | 150    | 800    | 2.2   |                                    |
| P2702ABLxx  | P2702AB | 120                             | 160                      | 240                             | 320                      | 4                      | 150    | 800    | 2.2   |                                    |
| P3002ABLxx  | P3002AB | 140                             | 180                      | 280                             | 360                      | 4                      | 150    | 800    | 2.2   |                                    |
| P3602ABLxx  | P3602AB | 170                             | 220                      | 340                             | 440                      | 4                      | 150    | 800    | 2.2   |                                    |
| P4202ABLxx  | P4202AB | 190                             | 250                      | 380                             | 500                      | 4                      | 150    | 800    | 2.2   |                                    |
| P4802ABLxx  | P4802AB | 220                             | 300                      | 440                             | 600                      | 4                      | 150    | 800    | 2.2   |                                    |
| P6002ABLxx  | P6002AB | 275                             | 350                      | 550                             | 700                      | 4                      | 150    | 800    | 2.2   |                                    |
| P0602ACLxx  | P0602AC | 25                              | 40                       | 50                              | 80                       | 4                      | 50     | 800    | 2.2   |                                    |
| P1402ACLxx  | P1402AC | 58                              | 77                       | 116                             | 154                      | 4                      | 150    | 800    | 2.2   |                                    |
| P1602ACLxx  | P1602AC | 65                              | 95                       | 130                             | 190                      | 4                      | 150    | 800    | 2.2   |                                    |
| P2202ACLxx  | P2202AC | 90                              | 130                      | 180                             | 260                      | 4                      | 150    | 800    | 2.2   |                                    |
| P2702ACLxx  | P2702AC | 120                             | 160                      | 240                             | 320                      | 4                      | 150    | 800    | 2.2   |                                    |
| P3002ACLxx  | P3002AC | 140                             | 180                      | 280                             | 360                      | 4                      | 150    | 800    | 2.2   |                                    |
| P3602ACLxx  | P3602AC | 170                             | 220                      | 340                             | 440                      | 4                      | 150    | 800    | 2.2   |                                    |
| P4202ACLxx  | P4202AC | 190                             | 250                      | 380                             | 500                      | 4                      | 150    | 800    | 2.2   |                                    |
| P4802ACLxx  | P4802AC | 220                             | 300                      | 440                             | 600                      | 4                      | 150    | 800    | 2.2   |                                    |
| P6002ACLxx  | P6002AC | 275                             | 350                      | 550                             | 700                      | 4                      | 150    | 800    | 2.2   |                                    |

#### Notes:

- Absolute maximum ratings measured at  $T_A=25^\circ C$  (unless otherwise noted).
- Devices are bi-directional (unless otherwise noted).
- **XX** Part Number Suffix: '**RP**' (Reel Pack), '**Blank**' (Bulk Pack), or '**60**' (Type 60 lead form bulk pack)

### Capacitance Values

| Part Number | pF<br>Pin 1-2, 3-2<br>Tip-Ground, Ring-Ground |     | pF<br>Pin 1-3<br>Tip-Ring |     |
|-------------|---|-----|---------------------------|-----|
|             | MIN   | MAX | MIN                       | MAX |
| P0602AALxx  | 15  | 145 | 10                        | 90  |
| P1402AALxx  | 40  | 60  | 20                        | 35  |
| P1602AALxx  | 35  | 60  | 20                        | 35  |
| P2202AALxx  | 30  | 50  | 15                        | 30  |
| P2702AALxx  | 25  | 45  | 15                        | 25  |
| P3002AALxx  | 25  | 40  | 15                        | 25  |
| P3602AALxx  | 25  | 35  | 10                        | 20  |
| P4202AALxx  | 25  | 35  | 10                        | 20  |
| P4802AALxx  | 20  | 35  | 10                        | 20  |
| P6002AALxx  | 20  | 35  | 10                        | 20  |
| P0602ABLxx  | 15  | 250 | 10                        | 145 |
| P1402ABLxx  | 40  | 155 | 20                        | 90  |
| P1602ABLxx  | 35  | 145 | 20                        | 85  |
| P2202ABLxx  | 30  | 115 | 15                        | 65  |
| P2702ABLxx  | 25  | 105 | 15                        | 60  |
| P3002ABLxx  | 25  | 95  | 15                        | 55  |
| P3602ABLxx  | 25  | 90  | 10                        | 50  |
| P4202ABLxx  | 25  | 85  | 10                        | 50  |
| P4802ABLxx  | 20  | 85  | 10                        | 50  |
| P6002ABLxx  | 20  | 80  | 10                        | 45  |

| Part Number | pF<br>Pin 1-2, 3-2<br>Tip-Ground, Ring-Ground |     | pF<br>Pin 1-3<br>Tip-Ring |     |
|-------------|---|-----|---------------------------|-----|
|             | MIN   | MAX | MIN                       | MAX |
| P0602ACLxx  | 25  | 250 | 10                        | 145 |
| P1402ACLxx  | 55  | 155 | 30                        | 90  |
| P1602ACLxx  | 45  | 145 | 25                        | 85  |
| P2202ACLxx  | 45  | 115 | 25                        | 65  |
| P2702ACLxx  | 40  | 105 | 20                        | 60  |
| P3002ACLxx  | 35  | 95  | 20                        | 55  |
| P3602ACLxx  | 35  | 90  | 15                        | 50  |
| P4202ACLxx  | 30  | 85  | 15                        | 50  |
| P4802ACLxx  | 30  | 85  | 15                        | 50  |
| P6002ACLxx  | 30  | 80  | 15                        | 45  |

Note: Off-state capacitance ( $C_o$ ) is measured at 1 MHz with a 2 V bias.

# Pxxx2AxL Series

## Two-Chip SIDACtor® - Modified TO-220

### Surge Ratings


| Series | $I_{PP}$                                     |  |  |  |  |  |  |  |   | $I_{TSM}$<br>50/60 Hz | di/dt |
|--------|--|--|--|--|--|--|--|--|---|-----------------------|-------|
|        | 0.2x310 <sup>1</sup><br>0.5x700 <sup>2</sup> | 2x10 <sup>1</sup><br>2x10 <sup>2</sup> | 8x20 <sup>1</sup><br>1.2x50 <sup>2</sup> | 10x160 <sup>1</sup><br>10x160 <sup>2</sup> | 10x560 <sup>1</sup><br>10x560 <sup>2</sup> | 5x320 <sup>1</sup><br>9x720 <sup>2</sup> | 10x360 <sup>1</sup><br>10x360 <sup>2</sup> | 10x1000 <sup>1</sup><br>10x1000 <sup>2</sup> | 5x310 <sup>1</sup><br>10x700 <sup>2</sup> |                       |       |
|        | A min  | A min                                  | A min                                    | A min                                      | A min                                      | A min                                    | A min                                      | A min  | A min                                     |                       |       |
| A      | 20   | 150                                    | 150                                      | 90   | 50   | 75                                       | 75   | 45   | 75  | 20                    | 500   |
| B      | 25   | 250                                    | 250                                      | 150  | 100  | 100                                      | 125  | 80   | 100                                       | 25                    | 500   |
| C      | 50   | 500                                    | 400                                      | 200  | 150  | 200                                      | 175  | 100  | 200                                       | 50                    | 500   |

**Notes:**


1. Current waveform in  $\mu s$
2. Voltage waveform in  $\mu s$

- Peak pulse current rating ( $I_{pp}$ ) is repetitive and guaranteed for the life of the product.
- $I_{pp}$  ratings applicable over temperature range of  $-40^{\circ}C$  to  $+85^{\circ}C$
- The device must initially be in thermal equilibrium with  $-40^{\circ}C \leq T_j \leq +150^{\circ}C$


### Thermal Considerations

| Package  | Symbol          | Parameter                               | Value       | Unit          |
|--|-----------------|---|-------------|---------------|
| Modified TO-220<br> | $T_J$           | Operating Junction Temperature Range    | -40 to +150 | $^{\circ}C$   |
|  | $T_S$           | Storage Temperature Range               | -65 to +150 | $^{\circ}C$   |
|  | $R_{\theta JA}$ | Thermal Resistance: Junction to Ambient | 60          | $^{\circ}C/W$ |


### V-I Characteristics




### tr x td Pulse Waveform



### Normalized VS Change vs. Junction Temperature



### Normalized DC Holding Current vs. Case Temperature




# Pxxx2AxL Series

## Two-Chip SIDACtor® - Modified TO-220

### Soldering Parameters

|  |                                    |                               |
|--|------------------------------------|-------------------------------|
| <b>Reflow Condition</b>  |                                    | Pb-Free assembly (see Fig. 1) |
| <b>Pre Heat</b>  | - Temperature Min ( $T_{s(min)}$ ) | +150°C                        |
|  | - Temperature Max ( $T_{s(max)}$ ) | +200°C                        |
|  | - Time (Min to Max) ( $t_s$ )      | 60-180 secs.                  |
| <b>Average ramp up rate (Liquidus Temp (<math>T_L</math>) to peak)</b> |                                    | 3°C/sec. Max.                 |
| <b><math>T_{s(max)}</math> to <math>T_L</math> - Ramp-up Rate</b>      |                                    | 3°C/sec. Max.                 |
| <b>Reflow</b>  | - Temperature ( $T_L$ ) (Liquidus) | +217°C                        |
|  | - Temperature ( $t_L$ )            | 60-150 secs.                  |
| <b>Peak Temp (<math>T_p</math>)</b>                                    |                                    | +260(+0/-5)°C                 |
| <b>Time within 5°C of actual Peak Temp (<math>t_p</math>)</b>          |                                    | 30 secs. Max.                 |
| <b>Ramp-down Rate</b>  |                                    | 6°C/sec. Max.                 |
| <b>Time 25°C to Peak Temp (<math>T_p</math>)</b>                       |                                    | 8 min. Max.                   |
| <b>Do not exceed</b>   |                                    | +260°C                        |




### Physical Specifications

|                        |   |
|------------------------|---|
| <b>Lead Material</b>   | Copper Alloy  |
| <b>Terminal Finish</b> | 100% Matte-Tin Plated                                       |
| <b>Body Material</b>   | UL Recognized epoxy meeting flammability classification V-0 |


### Environmental Specifications

|  |   |
|--|---|
| <b>High Temp Voltage Blocking</b>              | 80% Rated $V_{DRM}$ ( $V_{AC}$ Peak) +125°C or +150°C, 504 or 1008 hrs. MIL-STD-750 (Method 1040) JEDEC, JESD22-A-101 |
| <b>Temp Cycling</b>                            | -65°C to +150°C, 15 min. dwell, 10 up to 100 cycles. MIL-STD-750 (Method 1051) EIA/JEDEC, JESD22-A-104                |
| <b>Biased Temp &amp; Humidity</b>              | 52 $V_{DC}$ (+85°C) 85%RH, 504 up to 1008 hrs. EIA/JEDEC, JESD22-A-101  |
| <b>High Temp Storage</b>                       | +150°C 1008 hrs. MIL-STD-750 (Method 1031) JEDEC, JESD22-A-101  |
| <b>Low Temp Storage</b>                        | -65°C, 1008 hrs.  |
| <b>Thermal Shock</b>                           | 0°C to +100°C, 5 min. dwell, 10 sec. transfer, 10 cycles. MIL-STD-750 (Method 1056) JEDEC, JESD22-A-106               |
| <b>Unbiased Highly Accelerated Stress Test</b> | +130°C, 85%RH, 2atm, 168hrs. JESD22-A-118   |
| <b>Resistance to Solder Heat</b>               | +260°C, 30 secs. MIL-STD-750 (Method 2031)  |

### Part Numbering




### Part Marking



# Pxxx2AxL Series

## Two-Chip SIDACtor® - Modified TO-220


### Dimensions - Modified TO-220



The modified TO-220 package is designed to meet mechanical standards as set forth in JEDEC publication number 95.

|   | Inches |       | Millimeters |       |
|---|--------|-------|-------------|-------|
|   | Min    | Max   | Min         | Max   |
| A | 0.400  | 0.410 | 10.16       | 10.42 |
| D | 0.360  | 0.375 | 9.14        | 9.53  |
| F | 0.110  | 0.130 | 2.80        | 3.30  |
| G | 0.540  | 0.575 | 13.71       | 14.61 |
| H | 0.025  | 0.035 | 0.63        | 0.89  |
| J | 0.195  | 0.205 | 4.95        | 5.21  |
| K | 0.095  | 0.105 | 2.41        | 2.67  |
| L | 0.060  | 0.075 | 1.52        | 1.90  |
| M | 0.070  | 0.085 | 1.78        | 2.16  |
| N | 0.018  | 0.024 | 0.46        | 0.61  |
| O | 0.178  | 0.188 | 4.52        | 4.78  |
| P | 0.290  | 0.310 | 7.37        | 7.87  |

### Tape and Reel Specification – Modified TO-220



### Packing Options

| Package Type | Description                                 | Quantity | Added Suffix  | Industry Standard |
|--------------|---|----------|---|-------------------|
| A            | Modified TO-220 Tape and Reel Pack          | 700      | RP  | EIA-468-B         |
|              | Modified TO-220 Bulk Pack                   | 500      | N/A   | N/A               |
|              | Modified TO-220 Type 60 Lead Form Bulk Pack | 500      | 60<br>(special order item, contact factory for details) | N/A               |

**Disclaimer Notice** - Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse. "Littelfuse" includes Littelfuse, Inc., and all of its affiliate entities. <http://www.littelfuse.com/disclaimer-electronics>.

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we strictly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.