


# MMF25SBRD412R Datasheet




<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	MMF25SBRD412R-DG
Manufacturer	YAGEO
Manufacturer Product Number	MMF25SBRD412R
Description	RES SMD 0.1% 1/4W MELF
Detailed Description	412 Ohms $\pm$ 0.1% 0.25W, 1/4W Chip Resistor MELF, 0204 Metal Film

This model MMF25SBRD412R is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

MMF25SBRD412R

Series:

MMF

Resistance:

412 Ohms

Power (Watts):

0.25W, 1/4W

Features:

-

Operating Temperature:

-55°C ~ 155°C

Supplier Device Package:

MELF

Height - Seated (Max):

-

Failure Rate:

-

Manufacturer:

YAGEO

Product Status:

Active

Tolerance:

±0.1%

Composition:

Metal Film

Temperature Coefficient:

±25ppm/°C

Package / Case:

MELF, 0204

Size / Dimension:

0.055" Dia x 0.138" L (1.40mm x 3.50mm)

Number of Terminations:

2

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8533.21.0040

Moisture Sensitivity Level (MSL):

1 (Unlimited)

ECCN:

EAR99

# DATA SHEET

## MELF METAL FILM RESISTORS

General Purpose

MMF Series

$\pm 0.1\%$ ,  $\pm 0.25\%$ ,  $\pm 0.5\%$ ,  $\pm 1\%$ ,  $\pm 2\%$ ,  $\pm 5\%$

1/6W to 1W

RoHS compliant & Halogen Free





**ORDERING INFORMATION**

Part number of the MELF metal film resistor is identified by the series, power rating, tolerance, packing, temperature coefficient and resistance value.

**APPLICATIONS**

- All general purpose applications
- Power applications
- Energy meter

**FEATURES**

- AEC-Q200 qualified
- MELF, SMD package
- Excellent pulse withstanding capability
- Wide resistance range
- RoHS compliant and halogen free

**PART NUMBER**

MMF    25S    F    R    E    100R  
 (1)    (2)    (3)    (4)    (5)    (6)

**(1) SERIES NAME**

MMF Series

**(2) POWER RATING**

-12 = 1/6W	50S = 1/2W
25S = 1/4W	207 = 0.6W
204 = 0.4W	-50 = 1/2W
-25 = 1/4W	1WS = 1W

**(3) TOLERANCE**

B = ±0.1%	G = ±2%
C = ±0.25%	J = ±5%
D = ±0.5%	- = Based on spec.
F = ±1%	

**(4) PACKAGING**

R = Reel Pack

**(5) TEMPERATURE COEFFICIENT OF RESISTANCE**


C=±15ppm/°C	E=±50ppm/°C
D=±25ppm/°C	F=±100ppm/°C
G=±200ppm/°C	- = Based on spec.

**(6) RESISTANCE VALUE**

0.22Ω-1MΩ for E24 & E96 Series value, 100Ω-100KΩ for E192 Series value  
 Example:  
 1R = 1Ω, 10K = 10,000Ω, 1M = 1,000,000Ω

**DIMENSIONS**


Unit: mm



Normal	Miniature	L	D	C Min.
MMF-12	MMF25S / MMF204	3.50 ± 0.2	1.40 ± 0.15	0.5
MMF-25	MMF50S / MMF207	5.90 ± 0.2	2.20 ± 0.1	0.5
MMF-50	MMF1WS	8.50 ± 0.2	3.20 ± 0.2	0.5


**SUGGESTED PAD LAYOUT**

Unit: mm



Normal	Miniature	Soldering Mode	L Min.	P	W Min.
MMF-12	MMF25S MMF204	Reflow	1.3	1.6 ± 0.1	1.6
		Wave	1.5	1.5 ± 0.1	1.8
MMF-25	MMF50S MMF207	Reflow	2.0	3.0 ± 0.1	3.0
		Wave	2.5	3.0 ± 0.1	3.0
MMF-50	MMF1WS	Reflow	2.3	5.5 ± 0.2	4.0
		Wave	2.8	5.5 ± 0.2	4.0

**DERATING CURVE**



**ELECTRICAL CHARACTERISTICS**

CHARACTERISTICS	MMF-12	MMF25S	MMF204	MMF-25	MMF50S	MMF207	MMF-50	MMF1WS
Power Rating at 70 °C	1/6W	1/4W	0.4W	1/4W	1/2W	0.6W	1/2W	1W
Maximum Working Voltage	150V	200V	200V	250V	250V	250V	350V	350V
Maximum Overload Voltage	300V	400V	400V	500V	500V	500V	700V	700V
Voltage Proof on Insulation	300V	300V	300V	500V	500V	500V	700V	700V
Resistance Range	0.22Ω ~ 3.9Ω for Tol ±5%, E24 series value, 4Ω ~ 1MΩ for Tol ±1% E24 + E96 series value							
Operating Temp. Range	- 55°C to +155°C							
Temperature Coefficient	±15ppm/°C for 10R-9K99 , ±25ppm/°C for 100Ω-470KΩ, ±50ppm/°C for 4Ω ~ 1MΩ, ±100ppm/°C for 1Ω ~1MΩ, ±200ppm/°C for 0.22Ω ~ 0.99Ω							

Note: For resistance value out of above range is by request.

**TEST AND REQUIRMENTS**

TEST	TEST METHOD	PROCEDURE	APPRAISE
Short Time Overload	IEC 60115-1 4.13	2.5 times RCWV for 5 sec. (Not more than maximum overload voltage)	±0.25%+0.005Ω for≤332KΩ ±0.5%+0.005Ω for>332KΩ
Voltage Proof on Insulation	IEC 60115-1 4.7	In V-Block for 60 sec. test voltage as above table	No Breakdown
Temperature Coefficient	IEC 60115-1 4.8	Between -55°C to +155°C	By Type
Insulation Resistance	IEC 60115-1 4.6	In V-Block for 60 sec.	>10,000MΩ
Solderability	IEC 60115-1 4.17	245±5°C for 3±0.5 Sec.	95% Min. coverage
Solvent Resistance of Marking	IEC 60115-1 4.30	IPA for 5±0.5 Min. with ultrasonic	No deterioration of coatings and markings
Periodic-pulse Overload	IEC 60115-1 4.39	4 times RCWV 10,000 cycles (1 Sec. on, 25 Sec.off)	±1.0%+0.005Ω
Damp Heat Steady State	IEC 60115-1 4.24	40±2°C,90-95% RH for 56 days, loaded with 0.1 times RCWV	±1.5%+0.005Ω for≤332KΩ ±2.5%+0.005Ω for>332KΩ
Damp Heat Steady State (accelerated mode)	IEC 60115-1 4.37	85±2°C,85% RH for 56 days, loaded with 0.1 times RCWV(no over 100V)	±3.0%+0.005Ω for≤332KΩ ±5.0%+0.005Ω for>332KΩ
Endurance at 70°C	IEC 60115-1 4.25	70±2°C at RCWV(or Umax., whichever less) for 1,000 Hr.(1.5 Hr.on,0.5 Hr. off)	±0.75%+0.005Ω for≤332KΩ ±1.0%+0.005Ω for>332KΩ
Temperature Cycling	IEC 60115-1 4.19	➔ -55°C ➔ Room Temp. ➔ +155°C Room Temp.(5 cycles)	±0.75%+0.005Ω

Resistance to Soldering Heat	IEC 60115-1 4.18	260±3°C for 10±1 Sec., immersed to a point 3±0.5mm from the body	±0.5%+0.005Ω
Endurance at upper category temperature	IEC 60115-1 4.25	125±2°C for 1,000 Hr.	±1.0%+0.005Ω
Endurance at upper category temperature	IEC 60115-1 4.25	155±2°C for 1,000 Hr.	±2.0%+0.005Ω
Climatic test	IEC 60115-1 4.23	Dry heat: 125°C for 16 Hr. Damp heat: 55°C,95% RH for 24 Hr. Cold: -55°C for 2 Hr. Negative air pressure:8.5KPa at 25±10°C for 2 Hr. Damp heat cyclic: 55°C, 95% RH for 5 days. DC load: -55°C at RCWV for 1 Min. 125°C at RCWV for 1 Min.	±1.0%+0.005Ω

Note:

**RCWV (Rated Continuous Working Voltage):**

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:

$$V = \sqrt{P \times R}$$

or max. working voltage whichever is less

Where


V=Continuous rated DC or

AC (rms) working voltage (V)

P=Rated power (W)

R=Resistance value (Ω)


**PACKING METHODS**



DIMENSIONS

Unit: mm

TYPE	A	B	W	E	F	P0	P1	P2	ΦD0	ΦD1	T
MMF-12 MMF25S MMF204	1.6±0.1	3.7±0.1	8.0±0.2	1.75±0.1	5.5±0.05	4.0±0.1	4.0±0.1	2.0±0.05	1.5±0.1	0.9 Min.	1.45±0.1
MMF-25 MMF50S MMF207	2.4±0.1	6.3±0.1	12.0±0.2	1.75±0.1	7.5±0.05	4.0±0.1	4.0±0.1	2.0±0.05	1.5±0.1	1.4 Min.	2.50±0.1
MMF-50 MMF1WS	3.3±0.1	9.0±0.1	16.0±0.3	1.75±0.1	9.5±0.1	4.0±0.1	8.0±0.1	2.0±0.05	1.5±0.1	1.4 Min.	3.30±0.1



DIMENSIONS


Unit: mm/piece

TYPE	A0	B0	C0	W1	W2	Packaging	Quantity
MMF-12 MMF25S MMF204	178.5±1.5	60.0±1.0	13.0±0.2	9.0±0.5	12.5±0.5	7"	3,000
MMF-25 MMF50S MMF207	178.5±1.5	60.0±1.0	13.0±0.5	13.0±0.5	15.5±0.5	7"	2,000
MMF-50 MMF1WS	330.0±1.5	100.0±1.0	13.0±0.5	17.0±0.5	19.0±0.5	13"	2,500

**MARKING**

3-BAND-CODE

±2%, ±5%



COLOR	1st BAND	2nd BAND	3rd BAND	MULTIPLIER
BLACK	0	0	0	1Ω
BROWN	1	1	1	10Ω
RED	2	2	2	100Ω
ORANGE	3	3	3	1KΩ
YELLOW	4	4	4	10KΩ
GREEN	5	5	5	100K
BLUE	6	6	6	1MΩ
VIOLET	7	7	7	10MΩ
GREY	8	8	8	0.001Ω
WHITE	9	9	9	0.0001Ω
GOLD				0.1Ω
SILVER				0.01Ω

±0.1%, ±0.25%, ±0.5%, ±1%

4-BAND-CODE



**REVISION HISTORY**

REVISION	DATE	CHANGE NOTIFICATION	DESCRIPTION
Version 5	Nov.13, 2024	-	-Updated the resistance range of TCR
Version 4	Sep.05, 2024	-	-Updated packing methods
Version 3	Aug.31, 2023	-	-Revised LEGAL DISCLAIMER
Version 2	Feb.8, 2023	-	-Add TCR $\pm 15\text{ppm}/^\circ\text{C}$
Version 1	Sep.29, 2021	-	-Add TCR $\pm 25\text{ppm}/^\circ\text{C}$
Version 0	Aug.2, 2021	-	- First issue of this specification

*“ Yageo reserves all the rights for revising the content of this datasheet without further notification, as long as the products itse If are unchanged. Any product change will be announced by PCN.”*

## LEGAL DISCLAIMER

YAGEO, its distributors and agents (collectively, "YAGEO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment, Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly **YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.**

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.

## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to  
 Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.