


D4KB80 Datasheet

www.digi-electronics.com



<https://www.DiGi-Electronics.com>

DiGi Electronics Part Number	D4KB80-DG
Manufacturer	Diodes Incorporated
Manufacturer Product Number	D4KB80
Description	MEDIUM/HIGH POWER BRIDGE D3K TUB
Detailed Description	Bridge Rectifier Single Phase Standard 800 V Through Hole D3K

This model D4KB80 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.

Purchase and inquiry

Manufacturer Product Number:

D4KB80

Series:

-

Diode Type:

Single Phase

Voltage - Peak Reverse (Max):

800 V

Voltage - Forward (Vf) (Max) @ If:

1 V @ 2 A

Operating Temperature:

-55°C ~ 150°C (TJ)

Package / Case:

4-ESIP

Base Product Number:

D4KB

Manufacturer:

Diodes Incorporated

Product Status:

Active

Technology:

Standard

Current - Average Rectified (Io):

4 A

Current - Reverse Leakage @ Vr:

10 µA @ 800 V

Mounting Type:

Through Hole

Supplier Device Package:

D3K

Environmental & Export classification

RoHS Status:

ROHS3 Compliant

ECCN:

EAR99

REACH Status:

REACH Unaffected

HTSUS:

8541.10.0080



D4KB80

4.0A SURFACE MOUNT FAST GLASS PASSIVATED BRIDGE RECTIFIER

Product Summary (@T_A = +25°C)

V _{RRM} (V)	I _O (A)	V _F (V)	I _R (μA)
800	4.0	1.0	10

Description and Applications


Suitable for AC to DC bridge full wave rectification for LED lighting, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

Features and Benefits

- Glass Passivated Die Construction
- High Current Capability
- Ideal for SMT Manufacturing
- Low Forward Voltage Drop
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

Mechanical Data

- Case: D3K
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Lead Free Plating (Matte Tin Finish). Solderable per MIL-STD-202, Method 208 (e3)
- Polarity: As Marked on Body
- Mounting Position: Any
- Mounting Torque: 0.8 N.m Max.
- Weight: 0.023 grams (Approximate)




Pin Diagram

Ordering Information (Note 4)

Part Number	Compliance	Case	Packaging
D4KB80	Commercial	D3K	37/Tube

- Notes:
1. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
 2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
 3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
 4. For packaging details, go to our website at <https://www.diodes.com/design/support/packaging/diodes-packaging/>.

Marking Information



D4KB80= Product Type Marking Code
 311= Manufacturers' Code Marking
 YWW = Date Code Marking
 Y = Last Digit of Year (ex: 0 = 2020)
 WW= Week Code (01 to 53)



D4KB80

Maximum Ratings and Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	800	V
Working Peak Reverse Voltage	V _{RWM}		
DC Blocking Voltage	V _R		
RMS Reverse Voltage	V _{R(RMS)}	560	V
Average Rectified Output Current (Note 5)	I _O	@ T _C = +140°C	A
(Without Heatsink)		@ T _C = +30°C	1.3
Non-Repetitive Peak Forward Surge Current, 8.3ms Single Half Sine-Wave Superimposed on Rated Load	I _{FSM}	135	A
I ² t Rating for Fusing (1ms < t < 8.3ms)	I ² t	75	A ² S
Maximum Forward Voltage (Per Element)	V _{FM}	1.0	V
Peak Reverse Current	I _R	@T _A = +25°C	10
At Rated DC Blocking Voltage (Note 6)		@T _A = +125°C	500
Typical Total Capacitance (Per Element) (Note 7)	C _T	17	pF






Thermal Characteristics

Characteristic	Symbol	Value	Unit
Typical Thermal Resistance, Junction to Case (Note 5) (Per Element)	R _{θJC}	1.5	°C/W
Typical Thermal Resistance, Junction to Lead (Per Element)	R _{θJL}	55	°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C

Notes: 5. Device mounted on FR-4 PCB with 75mm x 75mm x 1.6mm aluminum heatsink.
6. Short duration pulse test used to minimize self-heating effect.
7. Measured at 1.0MHz and applied reverse voltage of 4.0V D.C.




D4KB80



Package Outline Dimensions

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

D3K



D3K			
Dim	Min	Max	Typ
A	2.90	3.30	--
A1	0.40	0.60	--
A2	2.00	2.30	--
A4	1.00	1.40	--
A5	--	--	0.60
b	0.66	0.86	--
c	0.40	0.60	--
D	13.50	14.10	--
D3	2.50	2.90	--
E	10.50	11.10	--
E1	11.70	12.30	--
e	3.51	4.11	--
L	11.70	12.30	--
Q	--	--	5.00
Q1	8.255	8.650	--
Q2	6.70	7.30	--
Q3	--	--	1.10
Q4	--	--	0.90
Q5	3.10	3.40	--
ØP	--	--	3.47
ØP1	--	--	4.00
All Dimensions in mm			



IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2020, Diodes Incorporated

www.diodes.com

OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: Info@DiGi-Electronics.com



Tel: +00 852-30501935

RFQ Email: Info@DiGi-Electronics.com

DiGi is a global authorized distributor of electronic components.