

# CLV1L-FKB-CJ1N1E1BB7B3B3 Datasheet



|                              |  |
|------------------------------|--|
| DiGi Electronics Part Number | CLV1L-FKB-CJ1N1E1BB7B3B3-DG  |
| Manufacturer                 | <a href="#">CreeLED, Inc.</a>  |
| Manufacturer Product Number  | CLV1L-FKB-CJ1N1E1BB7B3B3   |
| Description                  | LED RGB 4PLCC SMD  |
| Detailed Description         | Red, Green, Blue (RGB) 622nm Red, 528nm Green, 468nm Blue LED Indication - Discrete 2V Red, 3.1V Green, 3.1V Blue 4-LCC (J-Lead) |

<https://www.DiGi-Electronics.com>

This model CLV1L-FKB-CJ1N1E1BB7B3B3 is available at DiGi Electronics.

DiGi Electronics offers a global database of semiconductor and electronic component datasheets.

We welcome your inquiries regarding pricing, lead time, or other product-related questions.

 [Request a Quote](#)

 [Datasheet Search](#)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.

## Purchase and inquiry

Manufacturer Product Number:

CLV1L-FKB-CJ1N1E1BB7B3B3

Series:

CLV1L-FKB

Color:

Red, Green, Blue (RGB)

Lens Color:

-

Millicandela Rating:

675mcd Red, 1350mcd Green, 268mcd Blue

Lens Size:

-

Current - Test:

20mA Red, 15mA Green, 15mA Blue

Mounting Type:

Surface Mount

Wavelength - Peak:

-

Package / Case:

4-LCC (J-Lead)

Size / Dimension:

3.20mm L x 2.80mm W

Base Product Number:

CLV1L

Manufacturer:

CreeLED, Inc.

Product Status:

Active

Configuration:

Common Anode

Lens Transparency:

-

Lens Style:

Round with Flat Top

Voltage - Forward (Vf) (Typ):

2V Red, 3.1V Green, 3.1V Blue

Viewing Angle:

-

Wavelength - Dominant:

622nm Red, 528nm Green, 468nm Blue

Features:

-

Supplier Device Package:

4-PLCC

Height (Max):

2.10mm

## Environmental & Export classification

RoHS Status:

ROHS3 Compliant

REACH Status:

REACH Unaffected

HTSUS:

8541.41.0000


Moisture Sensitivity Level (MSL):

5A (24 Hours)

ECCN:

EAR99

## CLV1L-FKB: PLCC4 3 in 1 SMD LED



### PRODUCT DESCRIPTION

Cree LED PLCC full-color LEDs offer high-intensity light output and a wide viewing angle in an industry-standard package. Designed to work in a wide array of environmental conditions, Cree LED PLCC full-color LEDs are suited for indoor video screen, decorative lighting and amusement applications.

### FEATURES

- Size (mm): 3.2 x 2.8
- Dominant Wavelength  
Red (619 - 624nm)  
Green (520 - 535nm)  
Blue (460- 475nm)
- Luminous Intensity (mcd)  
Red (450 - 1010)  
Green (900 - 1800)  
Blue (180 - 403)
- Moisture Sensitivity Level: 5a
- Lead-Free
- RoHS Compliant

### APPLICATIONS

- Full-Color Video Screen
- Decorative Lighting
- Amusement

## ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ )

| Items                                  | Symbol     | Absolute Maximum Rating |     |     | Unit                      |
|--|------------|-------------------------|-----|-----|---------------------------|
|  |            | R                       | G   | B   |                           |
| Forward Current <sup>Note 1</sup>      | $I_F$      | 35                      | 20  | 20  | mA                        |
| Peak Forward Current <sup>Note 2</sup> | $I_{FP}$   | 200                     | 100 | 100 | mA                        |
| Reverse Voltage                        | $V_R$      | 5                       | 5   | 5   | V                         |
| Power Dissipation                      | $P_D$      | 91                      | 80  | 80  | mW                        |
| Operation Temperature                  | $T_{opr}$  | -40 ~ +100              |     |     | $^\circ\text{C}$          |
| Storage Temperature                    | $T_{stg}$  | -40 ~ +100              |     |     | $^\circ\text{C}$          |
| Junction Temperature                   | $T_J$      | 110                     | 110 | 110 | $^\circ\text{C}$          |
| Junction/ambient 1 chip on             | $R_{THJA}$ | 336                     | 507 | 474 | $^\circ\text{C}/\text{W}$ |
| Junction/solder point 1 chip on        | $R_{THJS}$ | 138                     | 322 | 298 | $^\circ\text{C}/\text{W}$ |

### Note:

1. Single-color light
2. Pulse width  $\leq 0.1$  msec, duty  $\leq 1/10$ .

## TYPICAL ELECTRICAL & OPTICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ )

| Characteristics                          | Condition  | Symbol           | Values  |         |         | Unit          |
|--|--|------------------|---------|---------|---------|---------------|
|  |  |                  | R       | G       | B       |               |
| Dominant Wavelength                      | $I_F = 20\text{mA(R)}$<br>$I_F = 15\text{mA(G)}$<br>$I_F = 15\text{mA(B)}$ | $\lambda_{DOM}$  | 619~624 | 520~535 | 460~475 | nm            |
| Spectral bandwidth at 50% $I_{REL\_max}$ | $I_F = 20\text{mA(R)}$<br>$I_F = 15\text{mA(G)}$<br>$I_F = 15\text{mA(B)}$ | $\Delta \lambda$ | 24      | 38      | 28      | nm            |
| Forward Voltage                          | $I_F = 20\text{mA(R)}$<br>$I_F = 15\text{mA(G)}$<br>$I_F = 15\text{mA(B)}$ | $V_{F(avg)}$     | 2.0     | 3.1     | 3.1     | V             |
|  |  | $V_{F(max)}$     | 2.6     | 4.0     | 4.0     | V             |
| Luminous Intensity                       | $I_F = 20\text{mA(R)}$<br>$I_F = 15\text{mA(G)}$<br>$I_F = 15\text{mA(B)}$ | $I_{V(min)}$     | 450     | 900     | 180     | mcd           |
|  |  | $I_{V(avg)}$     | 680     | 1250    | 235     | mcd           |
| Reverse Current (max)                    | $V_R = 5\text{V}$  | $I_R$            | 10      | 10      | 10      | $\mu\text{A}$ |

\* Continuous reverse voltage can cause LED damage.

## INTENSITY BIN LIMIT

| Red (20 mA) |           |           | Green (15 mA) |           |           | Blue (15 mA) |           |           |
|-------------|-----------|-----------|---------------|-----------|-----------|--------------|-----------|-----------|
| Bin Code    | Min.(mcd) | Max.(mcd) | Bin Code      | Min.(mcd) | Max.(mcd) | Bin Code     | Min.(mcd) | Max.(mcd) |
| J           | 450       | 560       | N             | 900       | 1120      | E            | 180       | 224       |
| km          | 505       | 635       | st            | 1010      | 1260      | bc           | 202       | 252       |
| K           | 560       | 710       | P             | 1120      | 1400      | F            | 224       | 280       |
| np          | 635       | 805       | vw            | 1260      | 1600      | de           | 252       | 318       |
| M           | 710       | 900       | Q             | 1400      | 1800      | G            | 280       | 355       |
| qr          | 805       | 1010      |               |           |           | fg           | 318       | 403       |

\* Tolerance of measurement of luminous intensity is  $\pm 10\%$ .

## COLOR BIN LIMIT

| Red (20 mA) |          |          | Green (15 mA) |          |          | Blue (15 mA) |          |          |
|-------------|----------|----------|---------------|----------|----------|--------------|----------|----------|
| Bin Code    | Min.(nm) | Max.(nm) | Bin Code      | Min.(nm) | Max.(nm) | Bin Code     | Min.(nm) | Max.(nm) |
| RB          | 619      | 624      | G7            | 520      | 525      | B3           | 460      | 465      |
|             |          |          | G23           | 522.5    | 527.5    | B23          | 462.5    | 467.5    |
|             |          |          | G8            | 525      | 530      | B4           | 465      | 470      |
|             |          |          | G45           | 527.5    | 532.5    | B45          | 467.5    | 472.5    |
|             |          |          | G9            | 530      | 535      | B5           | 470      | 475      |

\* Tolerance of measurement of dominant wavelength is  $\pm 1$  nm.

## ORDER CODE TABLE






| Kit Number                | Color | Luminous Intensity (mcd)                   |      | Dominant Wavelength (nm)           |          |           |           | Package |
|---------------------------|-------|--|------|------------------------------------|----------|-----------|-----------|---------|
|                           |       | Min.                                       | Max. | Color Bin                          | Min.(nm) | Color Bin | Max. (nm) |         |
| CLV1L-FKB-CJqrNQEfBB79353 | Red   | 450  | 1010 | RB                                 | 619      | RB        | 624       | Reel    |
|                           | Green | 900  | 1800 | G7                                 | 520      | G9        | 535       | Reel    |
|                           | Blue  | 180  | 403  | B3                                 | 460      | B5        | 475       | Reel    |
| CLV1L-FKB-CJ1N1E1BB7B3B3  | Red   | Any 1 Intensity bin from J(450) - qr(1010) |      | RB                                 | 619      | RB        | 624       | Reel    |
|                           | Green | Any 1 Intensity bin from N(900) - Q(1800)  |      | Any 1 hue bin from G7(520)-G9(535) |          |           |           | Reel    |
|                           | Blue  | Any 1 Intensity bin from E(180) - fg(403)  |      | Any 1 hue bin from B3(460)-B5(475) |          |           |           | Reel    |

## Notes:

- The above kit numbers represent order codes that include multiple intensity-bin and color-bin codes. Only one intensity-bin code and one color-bin code will be shipped on each bulk. Single intensity-bin code and single color-bin codes will not be orderable.
- Please refer to the [HB LED Lamp Reliability Test Standards](#) document for reliability test conditions.
- Please refer to the [HB LED Lamp Soldering & Handling](#) document for information about how to use this LED product safely.




## GRAPHS

The data below are collected from statistical figures that do not necessarily correspond to the actual parameters of each single LED. Hence, these data will be changed without further notice.



GRAPHS


The data below are collected from statistical figures that do not necessarily correspond to the actual parameters of each single LED. Hence, these data will be changed without further notice.



## MECHANICAL DIMENSIONS

All dimensions are in mm.

Tolerance of measurement of the dimension is  $\pm 0.1$ .



## NOTES

### RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree LED representative or from the [Product Ecology](#) section of the Cree LED website.


### Vision Advisory

WARNING: Do not look at an exposed lamp in operation. Eye injury can result.

**KIT NUMBER SYSTEM**


Cree LED lamps are tested and sorted into performance bins. A bin is specified by ranges of color, forward voltage, and brightness.

Cree LEDs are sold by order codes in combinations of bins called kits. Order codes are configured in the following manner:



## REFLOW SOLDERING

- The CLV1L-FKB is rated as a MSL 5a product.
- The recommended floor life out of bag is 24hrs.
- The temperature profile is as below.




### Use only with CLV1L-FKB

| Solder   |
|--|
| Average ramp-up rate = 4°C/s max                     |
| Preheat temperature = 150°C ~200°C                   |
| Preheat time = 120s max                              |
| Ramp-down rate = 6°C/s max                           |
| Peak temperature = 250°C max                         |
| Time within 5°C of actual Peak Temperature = 10s max |
| Duration above 217°C is 60s max                      |


## NOTES

- The packaging sizes of these SMD products are very small and the resin is still soft after solidification. Users are required to handle with care. Never touch the resin surface of SMD products.
- To avoid damaging the product's surface and interior device, it is recommended to choose a special nozzle to pick up the SMD products during the process of SMT production. If handling is necessary, take special care when picking up these products. The following method is necessary:



## PACKAGING

- The CLV1L-FKB is rated as a MSL 5a product.
- The boxes are not water resistant and they must be kept away from water and moisture.
- The LEDs are packed in cardboard boxes after packaging in normal or anti-electrostatic bags.
- Cardboard boxes will be used to protect the LEDs from mechanical shocks during transportation.
- The reel pack is applied in SMD LED.
- Max 2000 pcs per reel.



## OUR CERTIFICATE

DiGi provide top-quality products and perfect service for customer worldwide through standardization, technological innovation and continuous improvement. DiGi through third-party certification, we stricly control the quality of products and services. Welcome your RFQ to

Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)



Tel: +00 852-30501935

RFQ Email: [Info@DiGi-Electronics.com](mailto:Info@DiGi-Electronics.com)

DiGi is a global authorized distributor of electronic components.